SOURCE: MSC.36(63).pdf
controllability and performance, the Administration should pay particular attention to the following aspects during normal operation and during and subsequent to failures:
.1 yawing;
.2 turning;
.3 stopping in normal and emergency conditions;
.4 stability in the non-displacement mode about three axes and in heave;
.5 trim;
.6 plough in; and
.7 lift power limitations.
17.5.4.2 The terms in 17.5.4.1.2, .6 and .7 are defined as follows:
17.6
17. 7
17.8
.1 "Turning" is the rate of change of direction of a craft at its normal maximum operating speed in specified wind and sea conditions
2 "Plough in" is an involuntary motion involving sustained increase in drag of an air-cushion vehicle at speed, usually associated with partial collapse of the cushion system .
3 "Lift power limitations" are those limitations imposed upon the machinery and components which provide the lift.
Change of operating surface and mode
There should be no unsafe change in the stability, controllability or attitude of the craft during transition from one type of operating surface or mode to another. Information on change in the

---CHUNK---

SOURCE: MSC.36(63).pdf
Change of operating surface and mode
There should be no unsafe change in the stability, controllability or attitude of the craft during transition from one type of operating surface or mode to another. Information on change in the behaviour characteristics of the craft during transition should be available to the master.
Surface irregularities
Factors which limit the ability of the craft to operate over sloping ground and steps or discontinuities should be determined, as applicable, and made available to the master.
Acceleration and deceleration
The Administration should be satisfied that the worst likely acceleration or deceleration of the craft, due to any likely failure, emergency stopping procedures or other likely causes, would not hazard the persons on the craft.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT 17.9
17.10
17.11

17.12
Speeds
MSC 62123/Add.2
ANNEX 18
Page 155
. Safe maximum speeds should be determined, taking account of modes of operation, wind force and direction and the effects of possible

---CHUNK---

SOURCE: MSC.36(63).pdf
FOR HIGH SPEED CRAFT 17.9
17.10
17.11
17.12
Speeds
MSC 62123/Add.2
ANNEX 18
Page 155
. Safe maximum speeds should be determined, taking account of modes of operation, wind force and direction and the effects of possible failures of anyone lift or propulsion system over calm water, rough water and over other surfaces as appropriate to the craft.
Minimum depth of water
The minimum depth of water and other appropriate information required for operations in all modes should be determined.
Rard structure clearance
For amphibious craft, when cushion borne, clearance of the lowest point of the hard structure above a hard flat surface should be determined.
Night operation
The schedule of tests should include sufficient operation to evaluate the adequacy of internal and external lighting and visibility, under conditions of normal and emergency electrical power supply during service, cruising and docking manoeuvres.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 156
18.1
18.1.1
18.1.2
18.1.3
CHAPTER 18 - OPERATIONAL REQUIREMENTS

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

18.1
18.1.1
18.1.2
18.1.3
CHAPTER 18 - OPERATIONAL REQUIREMENTS
PART A - GENERAL
Cr aft opera t ional c on trol
The High Speed Craft Safety Certificate, the Permit to Operate High Speed Craft or certified copies thereof, and copies of the route operational manual, craft operating manual, and a copy of such elements of the maintenance manual as the Administration may require, should be carried on board.
The craft should not be intentionally operated outside the worst intended conditions and limitations specified in the Permit to Operate High Speed Craft, in the High Speed Craft Safety Certificate, or in documents referred to therein.
The Administration should issue a Permit to Operate High Speed Craft when it is satisfied that the operat o r has made adequate provisions from the point of view of safety generally, including the following matters specifically, and should revoke the Permit to Operate if such provisions are not maintained to its satisfaction:

---CHUNK---

SOURCE: MSC.36(63).pdf
from the point of view of safety generally, including the following matters specifically, and should revoke the Permit to Operate if such provisions are not maintained to its satisfaction:
.1 the suitability of the craft for the service intended having regard to the safety limitations and information contained in the route operational manual;
.2 the suitability of the operating conditions in the route operational manual;
.3 the arrangements for obtaining weather information on the basis of which the commencement of a voyage may be authorized;
.4 provision in the area of operation of a base port fitted with facilities in accordance with 18.1.4;
.5 the designation of the person responsible for decisions to cancel or delay a particular voyage, e.g. in the light of the weather information available;
.6 sufficient crew complement required for operating the craft, deploying and manning survival craft, the supervision of passengers, vehicles and cargo in both normal and emergency conditions as defined in the Permit to Operate . The crew complement should be such that two officers are on duty in the operating compartment when the craft is underway, one of whom

---CHUNK---

SOURCE: MSC.36(63).pdf

passengers, vehicles and cargo in both normal and emergency conditions as defined in the Permit to Operate . The crew complement should be such that two officers are on duty in the operating compartment when the craft is underway, one of whom may be the master;

.7 crew qualifications and training, including competence in relation to the particular type of craft and service intended, and their instructions in regard to safe operational procedures;

. 8 restrictions with regard to working hours, rostering of crews and any other arrangements to prevent fatigue including adequate rest periods;

.9 the training of crew in craft operation and emergency procedures;

.10 the maintenance of crew competence in regard to operation and emergency procedures;