assigned who is capable of operating the engine and carrying out minor adjustments.
The master should ensure the equitable distribution of persons referred to in 18.4.1 to 18.4 . 3 among the craft's survival craft.
Emergency ins truc ti on s and drills
On or before departure, passengers should be instructed in the use of lifejackets and the action to be taken in an emergency. The attention of the passengers should be drawn to the emergency instructions required by 8.4.1 and 8.4.3.
Emergency fire and evacuation drills for the crew should be held on board the craft at intervals not exceeding one week for passenger craft and one month for cargo craft.
Each member of each crew should participate in at least one evacuation, fire and damage control drill per month.
On-board drills should, as far as practicable, be conducted to simulate an actual emergency. Su ch simulations should include

---CHUNK---

SOURCE: MSC.36(63).pdf
Each member of each crew should participate in at least one evacuation, fire and damage control drill per month.
On-board drills should, as far as practicable, be conducted to simulate an actual emergency. Su ch simulations should include
instruction and operation of the c raft's evacuation, fire and damage control appliances and systems.
On-board instruction and operation of the craft's evacuation, fire and damage control appliances a nd systems should include appropriate cross-training of crew members .
Emergency instructions including a general diagram of the craft showing the location of all e x its , routes of evacuation, emergency equipment, life-saving equipment and appliances and illustration of lifejacket donning should be a vailable to each passenger and crew member. It should be placed near each passenger and crew seat.
WII687n/pp / EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT r
18.5.7 Records
MSC 62123/Add.2
ANNEX 18
Page 165
. The date when musters are held, details of abandon craft drills and fire drills, drills of other life-saving appliances and on-board

---CHUNK---

SOURCE: MSC.36(63).pdf
FOR HIGH SPEED CRAFT r
18.5.7 Records
MSC 62123/Add.2
ANNEX 18
Page 165

. The date when musters are held, details of abandon craft drills and fire drills, drills of other life-saving appliances and on-board training should be recorded in such log-book as may be prescribed by the Administration. If a full muster, drill or training session is not held at the appointed time, an entry should be made in the log-book stating the circumstances and the extent of the muster, drill or training session held. A copy of such information should be forwarded to the operator's management.
18.5.8 Evacuation drills
18.5.8.1 Evacuation drill scenarios should vary each week so that different emergency conditions are simulated.
18.5.8.2 Each evacuation craft drill should include:
.1 summoning of crew to muster stations with the alarm required by 8.2.2.2 and ensuring that they are made aware of the order to abandon craft specified in the muster list;
.2 reporting to stations and preparing for the duties described in the muster list;
.3 checking that crew are suitably dressed;
.4 checking that lifejackets are . correctly donned;

---CHUNK---

SOURCE: MSC.36(63).pdf
to abandon craft specified in the muster list;
.2 reporting to stations and preparing for the duties described in the muster list;
.3 checking that crew are suitably dressed;
.4 checking that lifejackets are . correctly donned;
.5 operation of davits if any used for launching liferafts;
.6 donning of immersion suits or thermal protective clothing by appropriate crew members;
.7 testing of emergency lighting for mustering and abandonment; and
.8 g1V1ng instructions in the use of the craft's life-saving appliances and in survival at sea.
18.5.8.3 Rescue boat drill
.1 As far as is reasonable and practicable, rescue boats should be launched each month as part of the evacuation drill, with their assigned crew aboard, and manoeuvred in the water. In all cases this requirement should be complied with at least once every three months .
. 2 If rescue boat launching drills are carried out with the craft making headway, such drills should, because of the dangers involved, be practised in sheltered waters only and under the super.vision of an officer experienced in such drills.*
Refer to resolution 11..624(15) concerning Guidelines on training for the

---CHUNK---

SOURCE: MSC.36(63).pdf
involved, be practised in sheltered waters only and under the super.vision of an officer experienced in such drills.*
Refer to resolution 11..624(15) concerning Guidelines on training for the purpose of launching lifeboats and rescue boats from ships making headway

through the water.
WI1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 166
18.5.8.4 Individual instructions may cover different parts of the craft's life-saving system, but all the craft's life-saving equipment and appliances should be covered within any period of one month on passenger craft and two months on cargo craft. Each member of the crew should be given instructions which should include but not necessarily be limited to:
.1 operation and use of the craft's inflatable liferafts;
.2 problems of hypothermia, first-aid treatment of hypothermia and other appropriate first-aid procedures; and
.3 special instructions necessary for use of the craft's life-saving appliances in severe weather and severe sea conditions.

---CHUNK---

SOURCE: MSC.36(63).pdf
.2 problems of hypothermia, first-aid treatment of hypothermia and other appropriate first-aid procedures; and
.3 special instructions necessary for use of the craft's life-saving appliances in severe weather and severe sea conditions.
18.5.8.5 On-board training in the use of davit-launched liferafts should take place at intervals of not mor~ than four months on every craft fitted with such appliances. Whenever practicable, this should include the inflation and lowering of a liferaft. This liferaft may be a special liferaft intended for training purposes only, which is not part of the craft's life-saving equipment. Such a special liferaft should be conspicuously marked.
18.5.9 Fire drills
18.5.9.1 Fire drill scenarios should vary each week so that emergency conditions are simulated for different vessel compartments;
18.5.9.2 Each fire drill should include:
.1 summoning of crew to fire stations;
.2 reporting to stations and preparing for the duties described in the muster list;
.3 donning of fireman's outfits;
.4 operation of fire doors and fire dampers;
.5 operation of fire pumps and fire-fighting equipment;

---CHUNK---

SOURCE: MSC.36(63).pdf
.2 reporting to stations and preparing for the duties described in the muster list;

.3 donning of fireman's outfits;
.4 operation of fire doors and fire dampers;
.5 operation of fire pumps and fire-fighting equipment;
.6 operation of communication equipment, emergency signals and general alarm;
.7 operation of fire detection system; and
.8 instruction in the use of the craft's fire-fighting equipment and sprinkler and drencher systems, if fitted.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62123/Add.2
ANNEX 18
Page 167
18.5.10 Damage control drills
18.5.10.1 Damage control drill scenarios should vary each week so that emergency conditions are simulated for different damage conditions.
18.5.10.2 Each damage control drill should include:
18.6
18.6.1
18.6.2
18.7