(Date of issue)

---CHUNK---

SOURCE: MSC.36(63).pdf
THIS IS TO CERTIFY that this Record is correct in all respects
Issued at ..... " " ..... " " " " " ... " ..... " ... " " " <III
(Date of issue)
(Place of issue of the Record)
" " e, " " " " " " " " " " ..... " .. ..
(Signature of duly authorized official
issuing the Record)
(Seal or stamp of th~ issuing authority, as appropriate)
W/1689n/pp/EWP
r
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 1
2
3
4
5
6
7
8
9
10
ANNEX 2
MSC 63/23/Add.2
ANNEX 18
Page 177
Form of Permit to Operate High Speed Craft
PERMIT TO OPERATE HIGH SPEED CRAFT
Issued under the provision of the
INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT
(Resolution MSC (63»
Name of craft
Manufacturer's model and hull
Distinctive number or letters
IMO number*
Port of registry
Category of craft
Name of operator
Areas or routes of operation
number ....
category A passenger craft/category B
passenger craft/cargo craft**

---CHUNK---

SOURCE: MSC.36(63).pdf
IMO number*
Port of registry

Category of craft
Name of operator
Areas or routes of operation
number ....
category A passenger craft/category B
passenger craft/cargo craft**
.....
.....
.. ..

(Signature of authorized official issuing the
,permit)
(Seal or stamp of the issuing authority, as appropriate)
W/1689n/pp/EWP
r
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT ANNEX 3
USE OF PROBABILITY CONCEPT
1 General
MSC 63/23/Add.2
ANNEX 18
Page 179
1.1 Absolute safety cannot be achieved in any human activity. Naturally, this fact should be taken into account in developing safety requirements, which means that requirements should not imply that safety is absolute. In the case of traditional craft, it has frequently been possible to specify certain aspects of design or construction in some detail, in a way which was consistent with some level of risk which had over the years been intuitively accepted without having to be defined.
1.2 For high speed craft, however, it would often be too restrictive to include engineering specifications into the Code. Requirements therefore need to be written (where this question arises) in the sense of " ... the

---CHUNK---

SOURCE: MSC.36(63).pdf
1.2 For high speed craft, however, it would often be too restrictive to include engineering specifications into the Code. Requirements therefore need to be written (where this question arises) in the sense of " ... the Administration should be satisfied on the basis of tests, investigations and past experience that the probability of ... is (acceptably low)".
Since different undesirable events may be regarded as having different general orders of acceptable probability (e.g. temporary impairment of propulsion as compared with an uncontrollable fire), it is convenient to agree on a series of standardized expressions which can be used to convey the relative acceptable probabilities of various incidents, i.e. to perform a qualitative ranking process. A vocabulary is given below which is intended to ensure consistency between various requirements, where it is necessary to describe the level of risk which should not be exceeded.
2 Terms associated with probabilities
Different undesirable events may have different orders of acceptable probability. In connection with this, it is convenient to agree on

---CHUNK---

SOURCE: MSC.36(63).pdf
2 Terms associated with probabilities
Different undesirable events may have different orders of acceptable probability. In connection with this, it is convenient to agree on standardized expressions to be used to convey the relatively acceptable probabilities of various occurrences, i.e. to perform a qualitative ranking process.

2.1 Occurrences
2.1.1 "Occurrence" is a condition involving a potential lowering of the level of safety.
2.1.2 "Failure" is an occurrence in which a part, or parts, of the craft fail or malfunction, e.g. runaway. A failure includes:
.1 a single failure;
.2 independent failures in combination within a system;
.3 independent failures in combinations involving more than one system, taking into account:
.1 any undetected failure that is already present;

.2 such further failures* as would be reasonably expected to follow the failure under consideration; and
.4 common cause failure (failure of more than one component or system due to the same cause).

---CHUNK---