.2 such further failures* as would be reasonably expected to follow the failure under consideration; and
.4 common cause failure (failure of more than one component or system due to the same cause).
2.1.3 "Event" is an occurrence which has its origin outside the craft (e.g. waves).
2.1.4 "Error" is an occurrence arising as a result of incorrect action by the operating crew or maintenance personnel.
2.2 Probability of occurrences
2.2.1 "Frequent" is one which is likely to occur often during the operational life of a particular craft.
2.2.2 "Reasonably probable" is one which is unlikely to occur often but which may occur several times during the total operational life of a particular craft.
2.2.3 "Recurrent" is a term embracing the total range of frequent and reasonably probable.
2.2.4 "Remote" is one which is unlikely to occur to every craft but may occur to a few craft of a type over the total operational life of a number of craft of the same type.
2.2.5 "Extremely remote" is one which is unlikely to occur when considering the total operational life of a number of craft of the type, but nevertheless should be considered as being possible.

---CHUNK---

SOURCE: MSC.36(63).pdf
number of craft of the same type.
2.2.5 "Extremely remote" is one which is unlikely to occur when considering the total operational life of a number of craft of the type, but nevertheless should be considered as being possible.
2.2.6 "Extremely improbable" is one which is so extremely remote that it should not be considered as possible to occur.
2.3 Effects
2.3.1 "Effect" is a situation arising as a result of an occurrence.
2.3.2 "Minor effect" is an effect which may arise from a failure, an event, or an error, as defined in 2.1.2, 2.1.3, 2.1.4, which can be readily compensated for by the operating crew. It may involve:
.1 a small increase in the operational duties of the crew or in their difficulty in performing their duties; or
.2 a moderate degradation in handling characteristics; or
.3 slight modification of the permissible operating conditions.
* In assessing the further failures which follow, account should be taken of any resulting more severe operating conditions for items that have not up to that time failed.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf
of any resulting more severe operating conditions for items that have not up to that time failed.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 181
2.3.3 "Major effect" is an effect which produces:
2.3.4
.1 a significant increase in the operational duties of the crew or in their difficulty in performing their duties which by itself should not be outside the capability of a competent crew provided that another major effect does not occur at the same time; or
.2 significant degradation in handling characteristics; or
.3 significant modification of the permissible operating conditions, but will not remove the capability to complete a safe journey without demanding more than normal skill on the part of the operating crew.
"Hazardous effect" is an effect which produces:
.1 a dangerous increase in the operational duties of the crew or in their difficulty in performing their duties of such magnitude that they cannot reasonably be expected to cope with them and will probably require outside assistance; or

---CHUNK---

SOURCE: MSC.36(63).pdf
.1 a dangerous increase in the operational duties of the crew or in their difficulty in performing their duties of such magnitude that they cannot reasonably be expected to cope with them and will probably require outside assistance; or
.2 dangerous degradation of handling characteristics; or
.3 dangerous degradation of the strength of the craft; or
.4 marginal conditions for, or injury to, occupants; or
. 5 an essential need for outside rescue operations.
2.3.5 "Catastrophic effect" is an effect which results in the loss of the craft and/or in fatalities.
2.4 Safety level
"Safety level" is a numerical value characterizing the relationship between craft performance represented as horizontal single amplitude acceleration (g) and rate of acceleration (g/s) and the severity of acceleration-load effects on standing and sitting humans.
The safety levels and the corresponding severity of effects on passengers and safety criteria for craft performance should be as defined in table 1.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 182
3 Numerical values
Where numerical probabilities are used in assessing compliance with requirements using the terms similar to those given above, the following approximate values may be used as guidelines to assist in providing a common point of reference. The probabilities quoted should be on an hourly or per journey basis, depending on which is more appropriate to the assessment in question.

Frequent	More than 10- 3
Reasonably probable	10- 3 to 10- 5
Remote	10- 5 to 10- 7
Extremely remote	10- 7 to 10- 9
Extremely improbable	Whilst no approximate numerical probability is given for this, the figures used should be substantially less than 10- 9 .

Note:
Different occurrences may have different acceptable probabilities, according to the severity of their consequences (see table 2).

W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT EFFECT

LEVEL 1
MINOR EFFECT
Moderate degradation of safety
LEVEL 2
MAJOR EFFECT

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT EFFECT
LEVEL 1
MINOR EFFECT
Moderate degradation

of safety
LEVEL 2
MAJOR EFFECT
Significant
degradation of
safety
LEVEL 3
HAZARDOUS EFFECT
Major degradation
of safety
LEVEL 4
CATASTROPHIC EFFECT
CRITERIA NOT TO BE
EXCEEDED
Type of load
Maximum acceleration
measured horizontally~/
Maximum acceleration
measured horizontally~/
Collision design
condition calculated
Maximum structural design
load, based on vertical