Premature operation
Delayed operation
Erroneous input
(increased)
Erroneous input
(decreased)
Erroneous output
(increased)
Erroneous output
(decreased)
Loss of input
Loss of output
Shorted (electrical)
Open (electrical)
Leakage (electrical)
Other unique failure
conditions as
applicable to the
system
characteristics,
requirements and
operational
constraints
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

---CHUNK---

SOURCE: MSC.36(63).pdf
Leakage (electrical)
Other unique failure
conditions as
applicable to the
system
characteristics,
requirements and
operational
constraints
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT Name of system
APPENDIX 2
FHEA WORKSHEET
References _____ _____ _
Mode of operation ___ _ _____ _ System block diagrams _____ _____ _
Sheet No.
Date
Name of analyst Drawings _ _____ _ _ ____ _ ___ _
I I I I
Equipment I I I I FS!il!,!re ~ff~ct Severity
Name or I I Ident. I Fail ure I Failure I Local I End Fail ure Corrective of failure
Number I Functi on I No. I mode I cause I effect I effect detection I action effect

I I I I I I I
I I I I I I I
I I I I I I I
I I I I I I I
I I I I I I I
I I I I I I I
I I I I I I
I I I I I
I I I I I
I I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
I I I I
W/1689n/pp/EWP
I
Probabil i ty I
of failure I
(if applicable)I Remarks
I
I
.,,~:::: III m
o.Q n
(!) t".I
XOI
I-' w
101-"
(}1o)N
w ,
> c.
C.
N
RESOLUTION MSC.36(63)

---CHUNK---

SOURCE: MSC.36(63).pdf
I I I I
I I I I
I I I I
I I I I
I I I I

I I I I
I I I I
W/1689n/pp/EWP
I
Probabil i ty I
of failure I
(if applicable)l Remarks
I
I
.,,~:::: III m
o.Q n
(!) t".I
XOI
I-' w
101-"
(}1o)N
w ,
> c.
C.
N
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 196
ANNEX 5
ICE ACCRETION APPLICABLE TO ALL TYPES OF CRAFT
1 Icing allowances
1.1 For craft operating in areas where ice accretion is likely to occur the following icing allowance should be made in the stability calculations:
.1 30 kg/m 2 on exposed weather decks and gangways;
.2 7.5 kg/m 2 for projected lateral area of each side of the craft above the waterplane;
.3 the projected lateral area of discontinuous surfaces of rail, sundry booms, spars (except masts) and rigging and the projected lateral area of other small objects should be computed by increasing the total projected area of continuous surfaces by 5% and the static moments of this area by 10%;
.4 reduction of stability due to asymmetric ice accumulations in cross-structure.

---CHUNK---

SOURCE: MSC.36(63).pdf
area of other small objects should be computed by increasing the
total projected area of continuous surfaces by 5% and the static
moments of this area by 10%;
.4 reduction of stability due to asymmetric ice accumulations in
cross-structure.
1.2 For craft operating in areas where ice accretion may be expected:
.1 Within the areas defined in 2.1, 2.3, 2.4 and 2.5 known to have icing conditions significantly different from those in 1.1, ice accretion requirements of one half to twice the required allowance

may be applied .
. 2 Within the area defined in 2.2, where ice accretion in excess of twice the allowance required by 1.1 may be expected, more severe requirements than those given in 1.1 may be applied.
1.3 Information should be provided in respect of the assumptions made in calculating the condition of the craft in each of the circumstances set out in this annex for the following:
.1 duration of the voyage in terms of the period spent in reaching the destination and returning to port; and
.2 consumption rates during the voyage for fuel, water, stores and other consumables.
2 Areas of icing conditions

---CHUNK---

SOURCE: MSC.36(63).pdf
.1 duration of the voyage in terms of the period spent in reaching the destination and returning to port; and
.2 consumption rates during the voyage for fuel, water, stores and other consumables.
2 Areas of icing conditions
In the application of 1, the following icing areas should apply:
.1 The area north of latitude 65°30'N, between longitude 28°W and the