West coast of Iceland; north of the north coast of Iceland; north of the rhumb line running from latitude 66°N, longitude 15°W to latitude 73°30'N, longitude 15°E, north of latitude 73°30'N between longitude 15°E and 35°E, and east of longitude 35°E, as well as north of latitude 56°N in the Baltic Sea .
. 2 The area north of latitude 43°N bounded in the west by the North American coast and the east by the rhumb line running from
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 197
latitude 43°N, longitude 48°W to latitude 63°N, longitude 28°W and thence along longitude 28°W .
. 3 All sea areas north of the North American continent, west of the

---CHUNK---

SOURCE: MSC.36(63).pdf
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 197
latitude 43°N, longitude 48°W to latitude 63°N, longitude 28°W and thence along longitude 28°W .
. 3 All sea areas north of the North American continent, west of the
areas defined in subparagraphs .1 and .2 of this paragraph .
. 4 The Bering and Okhotsk Seas and the Tartary Strait during the icing season .
. 5 South of latitude 60
0
S.
A chart to illustrate the areas is attached.
3 Special requirements
Craft intended for operation in areas where ice accretion is known to occur should be:
.1 designed to minimize the accretion of ice; and
.2 equipped with such means for removing ice as the Administration may require.
'JEGENO o -fuM..,. KCJftioft _____ IIIauIII be
-_.
40' tt----;----------i-------+------ ~ v_ -'1IN1 Wt " .. - "-0J ~_.., ... _to"""'J .. . . ~ . , . .._ 01 _ .... __ fill ice --.....Oj~ .
... , ~---.
.... ~. 00' .111' '111'
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 198
ANNEX 6
METHODS RELATING TO THE INTACT STABILITY INVESTIGATION OF HYDROFOIL CRAFT

---CHUNK---

SOURCE: MSC.36(63).pdf
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 198
ANNEX 6
METHODS RELATING TO THE INTACT STABILITY INVESTIGATION OF HYDROFOIL CRAFT
The stability of these crafts should be considered in the hull-borne,
transient and foil-borne modes. The stability investigation should also take
into account the effects of external forces. The following procedures are
outlined for guidance in dealing with stability.
1 Surface-piercing hydrofoils
1.1 Hull-borne mode
1.1.1 The stability should be sufficient to satisfy the provisions of 2.3
and 2.4 of this Code.
1.1.2 Heeling moment due to turning
1.1.3
1.1.4
The heeling moment developed during manoeuvring of the craft in the
displacement mode may be derived from the following formula:
=
where:
MR
Vo
d
L
KG
V 2
0.196 0 .d.KG (kNm)
L
=
=
moment of heeling;
speed of the craft in the turn (m/s)
displacement (t);
length of the craft on the waterline (m)
height of the centre of gravity above keel (m).
This formula is applicable when the ratio of the radius of the
turning circle to the length of the craft is 2 to 4.

---CHUNK---

SOURCE: MSC.36(63).pdf
displacement (t);
length of the craft on the waterline (m)
height of the centre of gravity above keel (m).
This formula is applicable when the ratio of the radius of the
turning circle to the length of the craft is 2 to 4.
Relationship between the capsizing moment and heeling moment to

satisfy the weather criterion
The stability of a hydrofoil boat in the displacement mode can be checked for compliance with the weather criterion K as follows:
K Mc
Mv
where:
~
Mc
1
minimum capsizing moment as determined when account is taken of rolling;
Mv = dynamically applied heeling moment due to the wind pressure.
Heeling moment due to wind pressure
The heeling moment Mv is a product of wind pressure Pv ' the windage area Av and the lever of windage area Z.
The value of the heeling moment is taken as constant during the whole period of heeling.
W/lfiRQn/oo/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 53/23/Add.2
ANNEX 18
Page 199
The windage area Av is considered to include the projections of the lateral surfaces of the hull, superstructure and

---CHUNK---

SOURCE: MSC.36(63).pdf
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 53/23/Add.2
ANNEX 18
Page 199
The windage area Av is considered to include the projections of the lateral surfaces of the hull, superstructure and
various structures above the waterline. The windage area lever Z is the vertical distance to the centre of windage from the waterline and the position of the centre of windage may be taken as the centre of the area.
The values of the wind pressure in Pascal associated with Force 7 Beaufort Scale depending on the position of the centre of windage area are given in table 1.
TABLE 1
Typical wind pressures for Beaufort scale 7,100 nautical miles from land
Z above waterline (m) 1.0 1.5 2.0 2.5 3.0 3.5 4.0 4.5
Pv (Pa) 45 45 50 53 56 58 60 52
~: These values may not be applicable in all areas.
5.0
64
1.1. 5 Evaluation of the minimum capsizing moment Mc in the displacement mode
The minimum capsizing moment is determined from the static and

dynamic stability curves taking rolling into account .
. 1 When the static stability curve is used, Mc is determined by equating the areas under the curves of the capsizing and

---CHUNK---

SOURCE: MSC.36(63).pdf
The minimum capsizing moment is determined from the static and dynamic stability curves taking rolling into account .
. 1 When the static stability curve is used, Mc is determined by equating the areas under the curves of the capsizing and righting moments (or levers) taking rolling into account, as indicated by figure 1, where 9z is the amplitude of roll
WII589n/pp/EWP
and MK is a line drawn parallel to the abscissa axis such that the shaded areas Sl and S2 are equal.
Mc = OM, if the scale of ordinates represents moments,
Mc = OM x Displacement, if the scale of ordinates represents levers,
STATIC STABILITY CURVE
c _
.. ..