.2 The lap belt, if installed, remains attached and on the test dummy's

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 215
.2 The lap belt, if installed, remains attached and on the test dummy's
pelvis during the impact. The shoulder harness, if installed,
remains attached and in the immediate vicinity of the test dummy's
shoulder during the impact. After the impact, the release
mechanisms should be operative .
. 3 The following acceptability criteria are met:
.1 the head injury criterion (HIC), calculated in accordance with
the formula, does not exceed 500
where:
t1 and t2 are the beginning and ending times
(in seconds) of the interval in which the HIC is a
maximum. The term a(t) is the resultant measured
acceleration in the head of the dummy in g;
.2 the thoracic trauma index (TTI), calculated in accordance with
the formula, does not exceed 30 g except for periods totalling
less than 3 ms
.3
.4
or acceleration at the centre of
gravity
where:
the
the
axis
gR is the acceleration in g of either the upper or
lower rib; and
gLS is the acceleration in g of the lower spine;

---CHUNK---

SOURCE: MSC.36(63).pdf
less than 3 ms
.3
.4
or acceleration at the centre of
gravity

where:
the
the
axis
gR is the acceleration in g of either the upper or
lower rib; and
gLS is the acceleration in g of the lower spine;
maximum pelvis acceleration does not exceed 130 g's;
maximum pelvic load does not exceed 6.7 kN measured in
of the spine;
.5 neck flexion does not exceed 88 Nm, if measured;
.6 neck extension does not exceed 48 Nm, if measured; and
.7 the force in the femur does not exceed 10 kN except that it
cannot exceed 8 kN for periods totalling more than 20 ms .
. 4 Loads on the upper torso harness straps do not exceed 7.8 kN or a
total of 8.9 kN if dual straps are used.
W/1689n/pp/EWP
the
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 216
1 General
ANNEX 10
OPEN REVERSIBLE LIFERAFTS
1.1 All open reversible liferafts should:
.1 be constructed with proper workmanship and materials;
.2 not be damaged in stowage throughout the air temperature range
of -18°C to +65°C:
.3 be capable of operating throughout an air temperature range of -18°e

---CHUNK---

SOURCE: MSC.36(63).pdf
.1 be constructed with proper workmanship and materials;
.2 not be damaged in stowage throughout the air temperature range
of -18°C to +65°C:
.3 be capable of operating throughout an air temperature range of -18°e
to +65°C and a seawater temperature range of _1°C to +30°C:
.4 be rot-proof, corrosion-resistant and not be unduly affected by
seawater, oil or fungal attack;
.5 be stable and maintain their shape when inflated and fully laden: and
.6 be fitted with retro-reflective material, where it will assist in
detection, and in accordance with the recommendations adopted by the
Organization*.
2 Construction
2.1 The open reversible liferaft should be so constructed that when it is
dropped into the water in its container from a height of 10 m, the liferaft
and its equipment will operate satisfactorily. If the open reversible
liferaft is to be stowed at a height of more than 10 m above the waterline in
the lightest seagoing condition, it should be of a type which has been
satisfactorily drop-tested from at least that height.

2.2 The open reversible floating liferaft should be capable of withstanding repeated jumps on to it from a height of at least 4.5 m.

---CHUNK---

SOURCE: MSC.36(63).pdf
satisfactorily drop-tested from at least that height.
2.2 The open reversible floating liferaft should be capable of withstanding repeated jumps on to it from a height of at least 4.5 m.
2.3 The open reversible liferaft and its fittings should be so constructed as to enable it to be towed at a speed of 3 knots in calm water when loaded with its full complement of persons and equipment, with the sea-anchor deployed.
2.4 The open reversible liferaft when fully inflated should be capable of being boarded from the water whichever way up it inflates.
2.5 The main buoyancy chamber should be divided into:
.1 not le~s than two separate compartments, each inflated through a nonreturn inflation valve on each compartment: and
Refer to the Recommendation on the use and fitting of retro-reflective materials on life-saving appliances adopted by the Organization by resolution A.658(16).
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 217
.2 the buoyancy chambers should be so arranged that in the event of one

---CHUNK---

SOURCE: MSC.36(63).pdf
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 217
.2 the buoyancy chambers should be so arranged that in the event of one of the compartments being damaged or failing to inflate, the intact compartment should be able to support, with positive freeboard over the open reversible liferaft's entire periphery, the number of persons which the liferaft is permitted to accommodate, . each having a mass of 75 kg and seated in their normal positions.
2.6 The floor of the open reversible liferaft should be waterproof.
2.7 The open reversible liferaft should be inflated with a non-toxic gas by an inflation system complying with the requirements of regulati6n III/39 of the Convention. Inflation should be completed within the period of one minute at an ambient temperature of between 18°C and 20°C and within a period of three minutes at an ambient temperature of -18°C. After inflation the open reversible liferaft should maintain its form when loaded with its full complement o f persons and equipment.

---CHUNK---

SOURCE: MSC.36(63).pdf
three minutes at an ambient temperature of -18°C. After inflation the open reversible liferaft should maintain its form when loaded with its full complement o f persons and equipment.
2.8 Each inflatable compartment should be capable of withstanding a pressure equal to at least three times the working pressure and should be prevented from reaching a pressure exceeding twice the working pressure either by means of relief valves or by a limited gas supply. Means should be provided for fitting the topping-up pump or bellows.
2.9 The surface of the buoyancy tubes should be of non-slip material. At least 25% of these tubes should be of a highly visible colour.
2.10 The number of persons which an open reversible liferaft should be permitted to accommodate should be equal to the lesser of:
.1 the greatest whole number obtained by dividing by 0.096 the volume, measured in cubic metres of the main buoyancy tubes (which for this purpose should not include the thwarts if fitted) when inflated; or
. 2 the greatest whole number obtained by dividing by 0.372 the inner horizontal cross-sectional area of the open reversible liferaft

---CHUNK---