SOURCE: MSC.36(63).pdf
purpose should not include the thwarts if fitted) when inflated; or
. 2 the greatest whole number obtained by dividing by 0.372 the inner horizontal cross-sectional area of the open reversible liferaft measured in square metres (which for this purpose may include the thwart or thwarts, if fitted) measured to the innermost edge of the buoyancy tubes; or
.3 the number of persons having an average mass of 75 kg, all wearing lifejackets, that can be seated inboard of the buoyancy tubes without interfering with the operation of any of the liferaft's equipment.
3 Open reversible liferaft fittings
3.1 Lifelines should be securely becketed around the inside and outside of the open reversible liferaft.
3.2 The open reversible liferaft should be fitted with an efficient painter of a length suitable for automatic inflation on reaching the water. For open reversible liferafts accommodating more than 30 persons an additional bowsing-in line should be fitted.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 218

---CHUNK---

SOURCE: MSC.36(63).pdf
bowsing-in line should be fitted.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 218
3.3 The breaking strength of the painter system including its means of attachment to the open reversible liferaft, except the weak link required by regulation III/39 of the Convention, should be:
.1 7.5 kN for open reversible liferafts accommodating up to 8 persons;
.2 10.0 kN for open reversible l-iferafts accommodating 9 to ' 30 persons; and
.3 15.0 kN for open reversible liferafts accommodating more than 30 persons.
3.4 The open reversible liferaft should be fitted with at least the following number of inflated ramps to assist boarding from the sea whichever way up the raft inflates:
.1 one boarding ramp for open reversible liferafts accommodating up to 30 persons; or
.2 two boarding ramps for open reversible liferafts accommodating more than 30 persons, such boarding ramps should be 180 0 apart.
3.5 The open reversible liferaft should be fitted with water pockets complying with the following requirements:

---CHUNK---

SOURCE: MSC.36(63).pdf
.2 two boarding ramps for open reversible liferafts accommodating more
than 30 persons, such boarding ramps should be 180 0 apart.
3.5 The open reversible liferaft should be fitted with water pockets
complying with the following requirements:
.1 the cross-sectional area of the pockets should be in the shape of an
isosceles triangle with the base of the triangle attached to the buoyancy tubes of the open reversible liferaft;
.2 the design should be such that the pockets fill to approximately 60~
of capacity within 15 s to 25 s of deployment;
.3 the pockets attached to each buoyancy tube should normally have
aggregate capacity of between 125 land 150 1 for inflatable open
reversible liferafts up to and including the 10 person size;
.4 the pockets to be fitted to each buoyancy tube on liferafts
certified to carry more than 10 persons should have as far as
practicable an aggregate capacity of (12 x N) 1itres, where N is the
number of persons carried;
.5 each pocket on a buoyancy tube should be attached so that when the
pocket is in the deployed position it is attached along the full
length of its upper edges to, or close to, the lowest part of the

---CHUNK---

SOURCE: MSC.36(63).pdf
number of persons carried;
.5 each pocket on a buoyancy tube should be attached so that when the
pocket is in the deployed position it is attached along the full
length of its upper edges to, or close to, the lowest part of the
lower buoyancy tube; and
.6 the pockets should be distributed symmetrically round the
circumference of the liferaft with sufficient separation between
each pocket to enable air to escape readily.
3.6 At least one manually controlled lamp complying with the requirements
should be fitted on the upper and lower surfaces of the buoyancy tubes.
3.7 Suitable automatic drain arrangements should be provided on each side of
the floor of the liferaft in the following manner:
W/l689n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 219
.1 one for open reversible liferafts accommodating up to 30 persons; or
.2 two for open reversible liferafts accommodating more than 30 persons.
3.8 The equipment of every open reversible liferaft should consist of:
.1 one buoyant rescue quoit, attached to not less than 30 m of buoyant

---CHUNK---

SOURCE: MSC.36(63).pdf

.2 two for open reversible liferafts accommodating more than 30 persons.
3.8 The equipment of every open reversible liferaft should consist of:
.1 one buoyant rescue quoit, attached to not less than 30 m of buoyant line with a breaking strength of at least 1 kN;
.2 two safety knives of the non-folding type having a buoyant handle should be fitted attached to open reversible liferaft by light lines. They should be stowed in pockets so that, irrespective of the way in which the open reversible liferaft inflates, one will be readily available on the top surface of the upper buoyancy tube in a suitable position to enable the painter to be readily cut; ,
.3 one buoyant bailer:
.4 two sponges;
.5 one sea anchor permanently attached to the open reversible liferaft in such a way as to be readily deployable when the open reversible liferaft inflates. The position of the sea anchor should be clearly marked on both buoyancy tubes;
.6 two buoyant paddles;
'.7 one first-aid outfit in a waterproof case capable of being closed tightly after use;
.8 one whistle or equivalent sound signal:
.9 two hand flares;

---CHUNK---

SOURCE: MSC.36(63).pdf
marked on both buoyancy tubes;
.6 two buoyant paddles;
'.7 one first-aid outfit in a waterproof case capable of being closed tightly after use;
.8 one whistle or equivalent sound signal:
.9 two hand flares;
.10 one waterproof electric torch suitable for Morse signalling together with one spare set of batteries and one spare bulb in a waterproof container:
.11 one repair outfit for repairing punctures in buoyancy compartments; and
.12 one topping-up pump or bellows.
3.9 The equipment specified in 3.8 is designated an HSC Pack.
3.10 Where appropriate, the equipment should be stowed in a container which, if it is not an integral part of, or permanently attached to the open reversible liferaft, should be stowed and secured to the open reversible liferaft and be capable of floating in water for at least 30 min without damage to its contents. Irrespective of whether the equipment container is an integral part of, or is permanently attached to, the open reversible liferaft, the equipment should be readily accessible irrespective of which way up the open reversible liferaft inflates. The line which secures the equipment

---CHUNK---

SOURCE: MSC.36(63).pdf
integral part of, or is permanently attached to, the open reversible liferaft, the equipment should be readily accessible irrespective of which way up the open reversible liferaft inflates. The line which secures the equipment container to the open reversible liferaft should have a breaking strength of

2 kN or a breaking strength of 3:1 based on the mass of the complete equipment pack, whichever is the greater.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 220
4 Contain ers for op e n rev er sible i n f l ata b le lifer a fts
4.1 The open reversible liferafts should be packed in a container that is:
.1 so constructed as to withstand conditions encountered at sea:
.2 of sufficient inherent buoyancy, when packed with the liferaft and its equipment, to pull the painter from within and to operate the inflation mechanism should the craft sink; and
.3 as far as practicable watertight, except for drain holes in the container bottom.
4.2 The container should be marked with :
.1 maker's name or trademark:
.2 serial number;

---CHUNK---