the port of survey where 1.6.11.5 of the Code applies

---CHUNK---

SOURCE: MSC.38(63).pdf
Date ... .
(Seal or stamp of authority, as appropriate)
Endorsement to eztend the validity of the certificate until reaching
the port of survey where 1.6.11.5 of the Code applies
This certificate should, in accordance with 1.6.11.5 of the Code,
be accepted until ....
Signed ....
(Signature of authorized official)
Place ....
Date ....
(Seal or stamp of authority, as appropriate)
Endorsement for the advancement of the anniversary date where
1.6.11.7 of the Code applies
In accordance with 1.6.11.7 of the Code, the new anniversary date
is .. ..
Signed ....
(Signature of authorized official)
Place . ...
Date ....
(Seal or stamp of authority, as appropriate)

---CHUNK---

SOURCE: MSC.38(63).pdf
Signed ....
(Signature of authorized official)
Place . ...
Date ....
(Seal or stamp of authority, as appropriate)
In accordance with 1.6.11.7 of the Code, the new anniversary date
is .. ..
Signed ....
(Signature of authorized official)
Place ..... " ....
Date .....
(Seal or stamp of authority, as appropriate)
W/1649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989 ANNEX 2
MSC 63/23 / Add.1
ANNEX 20
Page 13
AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989, TO INTRODUCE
REFERENCE TO GUIDELINES FOR VESSELS WITH
DYNAMIC POSITIONING SYSTEMS

---CHUNK---

SOURCE: MSC.38(63).pdf
MSC 63/23 / Add.1
ANNEX 20
Page 13
AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989, TO INTRODUCE
REFERENCE TO GUIDELINES FOR VESSELS WITH
DYNAMIC POSITIONING SYSTEMS
Replace paragraph 4.12 Dynamic positioning systems as follows:
"Dynamic positioning systems used as a sole means of position
keeping should provide a level of safety equivalent to that provided
for anchoring arrangements*".
Add a new footnote as follows:
""Reference is made to the Guidelines for Vessels with Dynamic
Positioning Systems approved by the Maritime Safety Committee at
its sixty-third session and disseminated by MSC/Circ.645"
The text of 5.1.2 should be replaced by the following:
"5.1.2 Administrations should take appropriate steps to ensure
uniformity in the implementation and application of the
provisions of these requirements in respect of electrical
installations"".
The text of the related footnote should be replaced by the following:
""Reference is made to the recommendations published by the
International Electrotechnical Commission".
W/1649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
SOURCE: MSC.38(63).pdf
The text of the related footnote should be replaced by the following:
""Reference is made to the recommendations published by the
International Electrotechnical Commission".
W/1649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989 MSC 63/23/Add.l
ANNEX 20
Page 14
ANNEX 3
AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989, ON PROVISIONS
FOR HELICOPTER FACILITIES
The text of Chapter 13 - HELICOPTER FACILITIES should be replaced by the
following:
"13.1 General
Each helicopter deck should be of sufficient size and located so as to
provide a clear take-off and approach to enable the largest helicopter using
the helideck to operate under the most severe conditions anticipated for
helicopter operations.
13.2 Definitions
13.2.1 'Helideck' is a purpose-built helicopter landing platform located on a
mobile offshore drilling unit (MODU).

13.2.2 'RD' means the main rotor diameter of the largest single rotor helicopter intended to use the facility.

---CHUNK---

SOURCE: MSC.38(63).pdf
13.2 Definitions
13.2.1 'Helideck' is a purpose-built helicopter landing platform located on a mobile offshore drilling unit (MODU).
13.2.2 'RD' means the main rotor diameter of the largest single rotor helicopter intended to use the facility.
13.2.3 'LD' means the largest dimension of the helicopter when the rotors are turning.
13.2.4 'Obstacle-free sector' is a sector formed by an arc originating at the reference point of the edge of a helideck and extending outward in the horizontal plane level with the elevation of the helideck.
13.2.5 'Limited obstacle sector' is a sector extending outward which is formed by that portion of the 360
0
arc, excluding the obstacle-free sector,
the centre of which is the reference point from which the obstacle-free sector is determined. Obstacles within the limited obstacle sector are limited to specified heights.
13.3 Construction
13.3.1 The helideck should be of a design and construction, adequate for the intended service and for the appropriate prevailing climatic conditions, approved to the satisfaction of the Administration.
13.3.2 For adverse climates as determined by the coastal State, taking into

---CHUNK---

SOURCE: MSC.38(63).pdf
intended service and for the appropriate prevailing climatic conditions, approved to the satisfaction of the Administration.
13.3.2 For adverse climates as determined by the coastal State, taking into account the type of helicopter used, the conditions of wind, turbulance, sea state, water temperature and icing conditions, the helideck should meet the following requirements with reference to ICAO Annex 14 Volume II (Heliports):
. 1 The helideck should be of sufficient size to contain an area within which can be drawn a circle of diameter not less than LD for single main rotor helicopters and not less than 0.9 LD for tandem main rotor helicopters.
W/1649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF MOBILE OFFSHORE DRILLING UNITS, 1989 MSC 63/23/Add.l
ANNEX 20
Page 15
. 2 Where the provisions of 13.3.2.1 cannot be met for helicopters having tandem main rotors, the helideck may be in the form of a rectangle with a small side not less than 0.75 LD and a long side not less than 0.9 LD, but within this rectangle, bidirectional

---CHUNK---

SOURCE: MSC.38(63).pdf
having tandem main rotors, the helideck may be in the form of a rectangle with a small side not less than 0.75 LD and a long side not less than 0.9 LD, but within this rectangle, bidirectional landings only should be permitted in the direction of the 0.9 LD dimension. Where necessary for design purposes, any corners of the rectangle may be omitted, provided that neither of the two sides forming the right angle of the omitted triangle exceed 5 m in length .
. 3 The obstacle-free sector should be not less than 210° .
. 4 For single main rotor and side by side twin main rotor helicopters, within the 150 0 limited obstacle sector out to a distance of 0.62 LD, measured from the centre of the he1ideck, objects should not exceed a height of 0.05 LD above the helideck. Beyond that arc, out to an overall distance of 0.83 LD, the limited obstacle sector rises at a rate of one unit vertically for each two units horizontally (see figure 13-1) .
. 5 For omnidirectional operations by tandem main rotor helicopters, within the 150° limited obstacle-free sector out to a distance of 0.62 LD, measured from the center of the helideck, no fixed

---CHUNK---