SOURCE: MSC.38(63).pdf
horizontally (see figure 13-1) .
. 5 For omnidirectional operations by tandem main rotor helicopters, within the 150° limited obstacle-free sector out to a distance of 0.62 LD, measured from the center of the helideck, no fixed obstacles should be allowed. Beyond that arc, out to an overall distance of 0.83 LD, the obstacle height is limited to 0.05 LD (see figure 13-2) .
6 For bidirectional operations by tandem main rotor helicopters, within the 0.62 LD arc in the 150 0 limited obstacle-free sector, objects should not penetrate a level surface which has a height equivalent to 1.1 m above the he1ideck (see figure 13-3) .
. 7 In the immediate vicinity of the helideck, over an area of at least 180 0 with the origin at the centre of the helideck, obstacles such as booms, derricks, sponsons, etc., should not protrude beyond a descending gradient having a ratio of one unit horizontal to five units vertically measured from the edge of the helideck downward.
13.3.3 For moderate climates as determined by the coastal State, taking into account the type of helicopter used, the conditions of wind, turbulance, sea

---CHUNK---

SOURCE: MSC.38(63).pdf
units vertically measured from the edge of the helideck downward.
13.3.3 For moderate climates as determined by the coastal State, taking into account the type of helicopter used, the conditions of wind, turbulance, sea state, water temperature and icing conditions, the helideck should meet the following requirements:
.1 The helideck should be of sufficient size to contain a circle of diameter equal to RD. In the case of MODUs expected to be routinely serviced by tandem main rotor helicopters, the helideck should be of sufficient size to contain a circle of diame.ter equal to at least 0.75 LD .
. 2 The helicopter deck should have an obstacle-free sector of at least 180 0 eree of obstructions. The reference point for this sector should be a point on the periphery of the circle referenced in paragraph 13.3.3.1, as shown in figure (13-4).
WI1649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF MOBILE OFFSHORE DRILLING UNITS, 1989 MSC 63/23/Add.1
ANNEX 20
Page 16
.3 The limited obstacle sector should extend out to a distance of 0.83

---CHUNK---

SOURCE: MSC.38(63).pdf
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF MOBILE OFFSHORE DRILLING UNITS, 1989 MSC 63/23/Add.1
ANNEX 20

.3 The limited obstacle sector should extend out to a distance of 0.83 RD for general operating areas. This distance should be measured from the centre of the helicopter deck. Obstructions in the limited obstacle sector should not extend above a plane measures vertically from the edge of the deck with rise at a rate not exceeding one unit vertically for each two units horizontally from the edge of the helideck (see figure 13-4).
13.3.4 The helideck should have a skid resistant surface.
13.3.5 Where the helideck is constructed in the form of a grating, the underdeck should be such that the ground effect is maintained.
13.4 Arrangements
13.4.1 The he1ideck should be free of projections except that landing lights or other essential projections may be installed around the periphery of the deck provided they do not rise more than 0.15 m above the level of the deck.
13.4.2 The he1ideck should have recessed tie-down points for securing a helicopter.

---CHUNK---

SOURCE: MSC.38(63).pdf
or other essential projections may be installed around the periphery of the deck provided they do not rise more than 0.15 m above the level of the deck.
13.4.2 The he1ideck should have recessed tie-down points for securing a helicopter.
13.4.3 The periphery of the helideck should be fitted with a safety net except where structural protection exists. The net should be inclined upward and outwards from below the edge of the helideck to a horizontal distance of 1.5 m and should not rise more than 0.15 m above the edge of the deck.
13.4.4 The helideck should have both a main and an emergency personnel access route located as far apart from each other as practicable.
13.4.5 Reference should be made to 9.11.1 concerning helideck drainage.
13.5 Visual Aids
13.5.1 A wind direction indicator should be located on the unit which, in so far as is practicable, indicates the actual wind conditions over the helideck. Units on which night helicopter operations take place should have provisions to illuminate the wind direction indicator.
13.5.2 The helideck should be marked as follows:
.1 the perimeter with a continuous white line with a width of 0.3 m;

---CHUNK---

SOURCE: MSC.38(63).pdf
provisions to illuminate the wind direction indicator.
13.5.2 The helideck should be marked as follows:
.1 the perimeter with a continuous white line with a width of 0.3 m;
.2 the unit's name should be provided on the he1ideck and be positioned on the obstacle side with characters not less than 1.2 m in height and in a colour contrasting with the background;
.3 an aiming circle, concentric to the helideck, painted yellow with an inside diameter equal to 0.5 LD. The width of the line should be 1 m;
.4 a white "H" centered on the landing area with the horizontal on the bisector of the obstacle-free sector. The "H" should be 3 m high,

1.8 m wide with 0.4 m wide lines; and
W!l649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989 · .
MSC 63123/Add.1
ANNEX 20
Page 17
.5 the helideck obstacle-free sector marking should indicate the or1g1n
of the obstacle-free sector, the direction of the limits of the
sector and the design dimensions (the LD or RD value) of the
helideck, as shown in figure 13-5.
13.5.3

---CHUNK---

SOURCE: MSC.38(63).pdf
.5 the helideck obstacle-free sector marking should indicate the or1g1n
of the obstacle-free sector, the direction of the limits of the
sector and the design dimensions (the LD or RD value) of the
helideck, as shown in figure 13-5.
13.5.3
.1 The helideck should be fitted with omnidirectional yellow lights in
order to enable the landing area to be easily identified at night.
These lights should be uniformly positioned along the perimeter of
the helideck and not more than 3 m apart. The administration may
allow the substitution of red lights for yellow lights to indicate
the position of cranes, and in the case of self-elevating units,
legs
. 2 Helideck floodlights, where fitted, should be located so as to avoid
glare to pilots. The arrangements and aiming of floodlights should
be such that helideck · markings are illuminated and that shadows are
kept to a minimum."
W/1649n/EWP
RESOLUTION MSC.38(63)
(adopted on 19 May 1994)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989 MSC 63/23/Add.l
ANNEX 20
Page 18
210· OBSTACLE-FREE SECTOR
for take-off and approach
Ui1ding An. L ... t
/-

---CHUNK---

SOURCE: MSC.38(63).pdf
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT
OF MOBILE OFFSHORE DRILLING UNITS, 1989 MSC 63/23/Add.l
ANNEX 20
Page 18
210· OBSTACLE-FREE SECTOR

for take-off and approach
Ui1ding An. L ... t
/-
L-D ------ .... ~-;
Limited obstacle
sector of 150
0
(Alternative positions
on the periphery and
swinging the whole
sector :!5· fro: th3t
pnClFIL£ VIEW
shown may be used il:
satisfying the
requirements)
Obsucj.e limit
to t2 slope
Db J.~t hti9't
llmit.d tD
0.05 L. D
riqure 13-1 - He1ideck obstacle limitation sector
5ioq1e main and side-by-side twin rotor helicopters in adverse climate
RESOLUTION MSC.38(63)