---CHUNK---

SOURCE: MEPC.51(32).pdf
all the f ollowing co nd itions are sati sfied:
(a) the oi l y mixt ure does not originate from the car go
pump-room bil ges;
(b) the oi l y mixture is not mixed with oil cargo residue s;
(c) th e ship is no t withi n a special area;
(d) the ship is more than 12 nautical miles from the nearest
land;
(e) the ship is pro ceed i ng en route;
(f) t he oil content o f the efflue nt i s less than 100 pa rts
pe r mi ll ion; a nd
RESOLUTION MEPC.51(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING
TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION
OF POLLUTION FROM SHIPS, 1973- 3 -
(g) the ship has in operation oily-water separating equipment
of a design approved by the Administ r ation. taking into
account the specification recommended by the
Organization*."
A footnote should be added to paragraph (7)(g) as follows;
"* Reference is made to the Rec ommendati on on International Performance
Specifications for Oily-Water Separating Equipment and Oil Content
Met ers adopted by the Organization by resolution A.393{X)."
2 Regulation 10
.1 Paragraph (2)(0) is amended to read:

---CHUNK---

SOURCE: MEPC.51(32).pdf
Specifications for Oily-Water Separating Equipment and Oil Content
Met ers adopted by the Organization by resolution A.393{X)."
2 Regulation 10
.1 Paragraph (2)(0) is amended to read:
"(b) any discharge into the sea of oil or oily mixture from a ship
of less than 400 tons gross tonnage. other than an oi 1 tanker,
shall be prohibited while in a special ares, except when the
oil content of the effluent without dilution does not exceed
15 part s per mill io n",
.2 Paragraph (3)(b)(v) is amended by changing the cross-reference
therein from 16(7) to 16(5).
) Regulation 16
The existing text of this regulation is replaced by the following:
"Regulation 16
Oil diSCharge monitoring and contro l system
and oil filtering equipment
(1) Any ship of 400 tons gross tonnage and above but less than
10,000 tons gross tonnage shall be fitted with oil filtering
equipment complying ~ith paragraph (4) of this regu l ati on. Any such
ship which carries large quantities of oil fuel shall comply with
paragraph (2) of this regulation or paragraph (1) of regulation 14.
(2) Any ship of 10,000 tons gross tonnage and above shall be provided

---CHUNK---

SOURCE: MEPC.51(32).pdf
ship which carries large quantities of oil fuel shall comply with
paragraph (2) of this regulation or paragraph (1) of regulation 14.
(2) Any ship of 10,000 tons gross tonnage and above shall be provided
with oil filtering equipment, and with arrangements for an alarm and
for automatically stopping any discharge of oi ly mixture when the
oil content in the effluent exceeds 15 parts per million.
(3) (a) The Administration may waive the requirements of paragraphs (1)
and (2) of this re gula tion for any ship engaged exclusively on
voyages within special areas provided that all of the following
conditions are complied with:
(i) the ship is fitted with a holding tank havin~ a volume
adequate. to the satisfa ction of the Administration, f or
the total retention on board of th e oily bilge water;
(ii) all oily bilge water is retained on board for subsequent
discharge to reception facilities;
(iii) the Administration has determined that adequate reception
facilities aTe available t o recei ve such oily bi Lge water
in II sufficient number of ports or terminals the ship
cslls at;
RESOLUTION MEPC.51(32) adopted on 6 March 1992

---CHUNK---

SOURCE: MEPC.51(32).pdf
(iii) the Administration has determined that adequate reception
facilities aTe available t o recei ve such oily bi Lge water
in II sufficient number of ports or terminals the ship
cslls at;
RESOLUTION MEPC.51(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING
TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION
OF POLLUTION FROM SHIPS, 1973- , -
(iv) the International oil Pollution Prevention Certificate,
when required, is endorsed t o the effec t that th e ship
is exclusively engaged on the voyages within special
areas; and
(v) the quantity, time, and port of the discharge are
recorded in the oil Record Book .
(b) The Administration shall ensure that ships of l ess than
400 tons gross tonnage are eQuipped, as far as practicable,
to retain on board oi l or oily mixtures or discharge them in
accorda nce with the requirements of regulation 9(1)(b) of
this Annex.
(~) Oil filtering equipment referred to in paragraph (I) of this
regulation sha ll be of a design approved by the Administration and
shall be such as will ensure that any oily mixture discharged in to
the sea after pa ssing thr ough t he system has an oil content not

---CHUNK---

SOURCE: MEPC.51(32).pdf

regulation sha ll be of a design approved by the Administration and shall be such as will ensure that any oily mixture discharged in to the sea after pa ssing thr ough t he system has an oil content not exceeding 15 parts per million. In considering th e design of such equipment, th e Administration shall have r eg ard t o the specification re commended by the Organization*.
(5) Oil filtering equ i pment referred to in pa ragraph (2) of this re gulati on s hall be of a design appr oved by th e Administration and sha ll be such as will ensure t hat any oily mixt ure discharged into the sea after pa9sing through the system or systems has an oil content not exceeding 15 parts per million . It shall be provided wi th alarm arrangements to indicate when this level cannot be maintained. The system shall also be provided with arrangements such as will ensure that any discharge of oily mixtures is automAtically stopped when the oil content of th e effluent exceeds 15 parts per mill i on. In considering the design of such equipment and arra ngemen ts, th e Administration shall have regard to the specification recommended by th e Organization*.

---CHUNK---

SOURCE: MEPC.51(32).pdf
15 parts per mill i on. In considering the design of such equipment and arra ngemen ts, th e Administration shall have regard to the specification recommended by th e Organization*.
(6) For shi ps delivered before 6 July 1993 the requirements of this regulation shall apply by 6 July 1998 provided that these ships can operate with oily-water separating equipment (100 ppm equipment) . "
A foo tn ote shou ld be added to paragraphs (4) and (5) 8S fol10ws~
"* Reference is made t o the Recommendation on Internati onal Perf orma nce Spec ifica tions for Oily -Water Separa tin g Equipment and Oil Content Meters adopted by the Organizati on by resolution A.393(X)."
4 Regulation 21
.1 Subpara graph (c) is amended by deleting the first five \lords, i . e., "in any special area and"
2 Subparagraph (d) is deleted.
5 Forms A and B of Supplements to the IOPP Certificate
Items 2.2 and 2.3 in both Forms A and B of Supplements t o the IOPP Certificate are replaced by the fo l lowing:
RESOLUTION MEPC.51(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973- 5 -

---CHUNK---

SOURCE: MEPC.51(32).pdf
Certificate are replaced by the fo l lowing:
RESOLUTION MEPC.51(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973- 5 -
"2.2 Type of oil filtering equipment fitted;
2.2.1

2.2 . 2
oil filtering (15 ppm) equipment
(regulation 16(4»
oil filtering (15 ppm) equipment with alarm and
automatic stopping device (regulation 16(5»
2.3 The ship is allowed to operate with the existing
equipment until 6 July 1998 (regulation 16(6» and
fi tted wi th:
2.3.1
2. 3. 2
2.3.3
Oily-water separating (100 ppm) equipment
Oil filtering (15 ppm) equipment without alarm
Oil filtering (15 ppm) equipment with alarm
and manual stopping device
If
If
I,"
RESOLUTION MEPC.51(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING
TO THE INTERNATIONAL CONVENTION FOR THE PREVENTION
OF POLLUTION FROM SHIPS, 1973RESOLUTION MEPC.51(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING