(c) Turn of the bilge ar ea or a t loca tion s without a clearly defined
t urn of the bi 1ge
Wh e n t he di st an ces h and wa re differen t , the dis ta nce w shall have
pr efere nce at levels exceed in g 1.5 h above t he base li ne as shown i n
figu re 1.
(d) The aggregate capaci t y of b a lla~t tanks
On crude oil tan kers of 20,000 t ons deadweight and ab ove and product
carriers of 30,000 tons deadwe ight and above, the aggregat e capac ity
of win g tanks, double bottom ta nks, f orepe ak tanks and afterpeak
tank s s ha l l n o t be less th an the capacity of segregated ballast
tan ks nece ssa ry t o meet the requir ements of regulation 13 . Wi ng
tanks or spaces and double bott om tank s used to meet the
requi re ments o f regulation 13 shall be located as un iformly as
pra cticable al ong the cargo tank length. Addi ti ona l segregated

---CHUNK---

SOURCE: MEPC.52(32).pdf
tanks or spaces and double bott om tank s used to meet the
requi re ments o f regulation 13 shall be located as un iformly as
pra cticable al ong the cargo tank length. Addi ti ona l segregated
ballast capacity pr ovid ed for reducing l ongitudi na l hull girder
bending str ess, trim, e t c., may be located anywhere with in the sh i p .
(el Suction well s i n cargo tanks
Suc tion well s in cargo tanks may protrud e int o t he double botto m
below the bound a r y l ine defined by t he distance h provided tha t such
wells are as small as practica ble an d the distance between the well
bottom an d bot tom s hell pl a ti ng is not less than 0 . 5 h.
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 5 -
(f) Ballast and carg o piping
Ballast piping and other piping such as sounding and vent piping to
ballast tanks shall not pass through c argo tanks. Cargo piping and
similar piping to cargo tanks shall not pass through ballast tanks.
Exemptions to this requirement may be granted for short leng ths of

---CHUNK---

SOURCE: MEPC.52(32).pdf
ballast tanks shall not pass through c argo tanks. Cargo piping and
similar piping to cargo tanks shall not pass through ballast tanks.
Exemptions to this requirement may be granted for short leng ths of
piping, provided that they are completely welded or equivalent.
(4) (a) Double bottom tanks or spaces as required by paragraph O)(b) may be
di s pensed with, provided that the design of the tanker is such that
the cargo and vapour pressure exerted on the bottom shell plating
forming a single boundary between the cargo and the sea does not
exceed the external hydrostatic water pressure, as expressed by the
following formu l a:
where~
P,
f

g
height of cargo in contact with the bottom shell platin g
i n metres
maxi mum cargo density in t/m3
m1nlMum operating draught under any expected loading
condition in me tres
density of sea water in t/m3
maximum set pressure of pressure/vacuum valve provided
for the cargo tank in bar s
safety factor 5 1.1
standard acceleration of gravity (9.81 111/92).
(b) Any horizontal partition necessary to fulfil the above requirements
shal l be located at a height of not less than B/6 or 6 metres,

---CHUNK---

SOURCE: MEPC.52(32).pdf
for the cargo tank in bar s
safety factor 5 1.1
standard acceleration of gravity (9.81 111/92).
(b) Any horizontal partition necessary to fulfil the above requirements
shal l be located at a height of not less than B/6 or 6 metres,
whichever is the lesser, but not more than 0.60, above the baseline
where D is the moulded depth amidship s.
(c) The location of wing tanks or spaces shall be as defined in
paragraph (l){a) except that, below a level 1.S h above t he baseline
where h i s as defined in paragraph (3)(b), the cargo tank boundary
line may be vertical down to the bottom plating, as shown in
figure 2.
(5) Other methods of design and constructio n of oil tankers may als o be
accepted as alternatives to the requirements prescribed in paragraph (3) ,
provided that such methods ensure at least the same level of protection
against oil pollution in the event of collision or stranding an d are approved
i n principl e by the Marine Environment Protection Committee based on
gu i de line s developed by the Or ganization.
(6) For oi l tankers of 20,000 tons deadweight and above the damage
assumptions prescribed in regulation 2S(2)(b) shall be supplemented by the

---CHUNK---

SOURCE: MEPC.52(32).pdf
gu i de line s developed by the Or ganization.
(6) For oi l tankers of 20,000 tons deadweight and above the damage
assumptions prescribed in regulation 2S(2)(b) shall be supplemented by the
following assumed bottom raking damage:
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - , -
(8) lon g itudinal ex tent:
(i) ships of 75,000 tons deadweight and above :
0.6 L measured frorn t he forward perpen dicu l ar
(ii) ship s of less than 75 ,000 tons deadlo1eig hc
0.4 L measured from the forward perpendicular

(b) transverse extent: B/3 anywhere in the botto m
(e) verti cal extent: br each of th e ou ter hu ll .
(7) Oil tank ers of lea s than 5,000 tons deadweight shall:
(a) at least be fitted wi t h double bottom ta nks or spaces having such
a depth that t he dis t a nce h s pecified in paragraph (3)(b) complies
with the following:
h - B/15 (m) with a minim um value of h D 0.76 m;
in t he tu rn of the bi lge ar ea and at lo cat ion s wi tho ut a clearly
def ined turn of the bilge, the cargo tank boundary line s hall run

---CHUNK---

SOURCE: MEPC.52(32).pdf
with the following:
h - B/15 (m) with a minim um value of h D 0.76 m;
in t he tu rn of the bi lge ar ea and at lo cat ion s wi tho ut a clearly
def ined turn of the bilge, the cargo tank boundary line s hall run
parallel to the line of the mid-ship flat bottom as shown in
figure 3; and
(b) be pr ovided with cargo tanks so arranged that t he capacity of ea ch
cargo tank does not exceed 700 m3 unless win g tanks or space s are
arranged in accordance with paragraph (3)(a) comply ing with the
following:
w ~ 0.4 + 2.4 OW (m)
20,000
wit h a minimum valu e of w = 0 . 76 m.
(8) Oil shall not be car ried in any space exte nding forward of a co llision
bulkhead located in accordance with re gulation 11-1/11 of the Inte rnationa l
Conve nti on for the Safe t y of Li fe at Sea , 1974, as amended . An oi l tanker
th at i s not required t o have a col lisio n bulkh ead in acco rdan ce wi th that
re gula t ion shall not carry oi l in any space exten ding forwsrd of the
transverse plane perpen di cular to the centreline that is located as if it
were a collision bulkhead lo cated in accordance wi th that regulation.

---CHUNK---

SOURCE: MEPC.52(32).pdf
re gula t ion shall not carry oi l in any space exten ding forwsrd of the
transverse plane perpen di cular to the centreline that is located as if it
were a collision bulkhead lo cated in accordance wi th that regulation.
(9) In appr ov in g the design and construc ti on of oil tanker s to be built in
accordance with the provisions of this re gu lation , Admini s trations shall hav e
due re gard t o the genersl s afet y aspe ct s including the ne ed f or the
maintenance and ins pec t ions of wing and double bottom tank s or spaces.
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 7
w w
h~w
h
Figure 1
Carg o tank boundary lines for the purpose of paragraph (3)
RESOLUTION MEPC.52(32) adopted on 6 March 1992

AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 8 -
w
1.5· h
base line
Figure 2
Cargo tank boundary 1 iues for th e purpose of paragraph (4)
RESOLUTION MEPC.52(32) adopted on 6 March 1992

---CHUNK---

SOURCE: MEPC.52(32).pdf
FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 8 -
w
1.5· h
base line
Figure 2
Cargo tank boundary 1 iues for th e purpose of paragraph (4)
RESOLUTION MEPC.52(32) adopted on 6 March 1992
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1978 RELATING TO THE INTERNATIONAL CONVENTION

FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973 - 9 -
h

base line
Figure 3
Cargo tank boundary lines for the purpose of paragraph (7)