when Designing Cargo Tanks Venting and Gas-Freeing Arrangements

---CHUNK---

SOURCE: MEPC.55(33).pdf
.4 the pressure losses created by ducting, piping, cargo tank inlets
and outlets;
* Reference is made to the Revised Factors to be taken into Consideration
when Designing Cargo Tanks Venting and Gas-Freeing Arrangements
(MSC/Circ.4S0/Rev.1) and to the Revised Standards for the Design, Test ing
and Locating of Devices to Prevent the Passage of Flame into Cargo Tanks
in Tankers (MSC/Circ.373/Rev.l).
RESOLUTION MEPC.55(33) (adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION
AND EQUIPMENT OF SHIPS CARRYING
DANGEROUS CHEMICALS IN BULK (IBC CODE)- 7 -
.5 the pressure achievable in the fan driving medium (e .g. water or
compressed air);
.6 the densities of the carg o vapo ur/air mixtures for the range of
cargoes to be carried.
In the existing text of 11.1.2 the words " Caustic potash solution, phosphoric
acid or sodium hydroxide solution" are re placed by the followl.ng words;
"products which are non-flammable (entry NF in column 1 i' of the table of
minimum requirements)".
New parag ra ph 11 .1 . 3 is added as follows:
For ships engaged solely in the car riage of products with flashpoint

---CHUNK---

SOURCE: MEPC.55(33).pdf
"products which are non-flammable (entry NF in column 1 i' of the table of
minimum requirements)".
New parag ra ph 11 .1 . 3 is added as follows:
For ships engaged solely in the car riage of products with flashpoint
above 60·C (entry "yea" in column' i' of the table of mimimum
requirements) requirements of chapter tl-2 of the 1983 SOLAS amendments
may apply as specified in regulation II-2/55.4 in lieu of the provisions
of this chapter.
At the end of th e existi ng t ext of t he introdu ct or y paragraph of c hapter 12 -
Mechnical ventilation in the cargo area the following sentence is added;
However, for products addressed under 11.1.2 and 11.1.3, except acids
and products for which pa ragra ph 15.17 apply, regulation 11-2 /59.3 of the
1983 saLAS amendments may appLy in lie u of the provisions of this ch apter.
The existing text of 14.2.8.1 is replaced by the following:
filt er type respirat or y protection is unacceptable;
The exist ing text of 15.13 is amended to read as follows:
15 . 13 Car goes protecte d by additives
15.1 3. 1 Certain cargoes with a referen ce in column '0' in the table of

---CHUNK---

SOURCE: MEPC.55(33).pdf
filt er type respirat or y protection is unacceptable;
The exist ing text of 15.13 is amended to read as follows:

15 . 13 Car goes protecte d by additives
15.1 3. 1 Certain cargoes with a referen ce in column '0' in the table of chapter 17 by the nature of their chemical make-up tend, under certai n con dit ions of temperat ure, exposu re to air or cOntac t with a catalyst, to undergo polymerization, decomposition, oxidation or oth er che mi cal changes. Mitigation of this tendency is carri ed out by introdu c ing small amounts of chemical additives into the liquid cargo or by controlling the cargo tank environment.
15.13.2 No change.
15.13.3 Care should be taken to ensure that these cargoes are sufficiently protected to prevent del e terio us chemical change at all times during the voyage. Ships carrying such cargoes should be provided with a certificate of protection from t he manufa cture r and kept during the voyage specifying:
.1 the name and amount of additive present;
.2 whether the additive is oxygen-dependent;
RESOLUTION MEPC.55(33) (adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION

---CHUNK---

SOURCE: MEPC.55(33).pdf
the voyage specifying:
.1 the name and amount of additive present;
.2 whether the additive is oxygen-dependent;
RESOLUTION MEPC.55(33) (adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION
AND EQUIPMENT OF SHIPS CARRYING
DANGEROUS CHEMICALS IN BULK (IBC CODE)The

,3 date additive was put in the product and duration of effectiveness;
.4 any temperature limitations qualifying the additive's effective life time; and
.5 the action to be taken should the length of voyage exceed the effective lifetime of the additive.
15.13.4 Ships us i ng the exclusion of air as the method of prevent ing oxidation of the cargo should comply with 9.1.3.
15.13.5 A product containing an oxygen-dependent additive should be carried without inertian (in tanks of a size not greater than 3,000 m3). Such cargoes should not be carried in a tank requiring inertian under the requirements of SaLAS chapter 11-2.
15.13.6 A, existing 15 .13.5.
15.13.7 A, existing 15.13.6.
existing text of 15.15 is reElaced bl the word:
"Deleted"
In the existing text of 15.8.29 the following words are inserted after the second sentence!

---CHUNK---

SOURCE: MEPC.55(33).pdf
15.13.6 A, existing 15 .13.5.
15.13.7 A, existing 15.13.6.

existing text of 15.15 is reElaced bl the word:
"Deleted"
In the existing text of 15.8.29 the following words are inserted after the second sentence!
Remote manual operation should be arrange~ such that remote starting of pumps supplying the water spray system and remote operation of any normally closed va l ves in the system can be carried out from a suitable location outside the cargo area, adjacent to the accomodation spaces and readily accessible and operable in the even of fire in the areas protected.
A new 15.21 is added as follows;
15.21 Temperature sensors
Temperature sensors should be used to monitor the cargo pump temperature to detect overheating due to pump failures.
The existing text of Chapter 17 is replaced by the following:
CHAPTER 17 - SUMMARY OF MINIMUM REQUIREMENTS
Mixtures of noxious Equid substances presenting pollution hazards only and which are provisionally a ssesse d under regulation 3(4) of Annex II of MARPOL 73/78. may be carried under the requirements of the Code applicable to the appropriate position of the entry in this chapter for noxious liquids not

---CHUNK---

SOURCE: MEPC.55(33).pdf
and which are provisionally a ssesse d under regulation 3(4) of Annex II of MARPOL 73/78. may be carried under the requirements of the Code applicable to the appropriate position of the entry in this chapter for noxious liquids not otherwise specified.
RESOLUTION MEPC.55(33) (adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING
DANGEROUS CHEMICALS IN BULK (IBC CODE)Product name
(column a)
UN number
(column b)
Pollu tion ca tegory
(column c)
Hazards
(co l umn d)
Ship type
(co lumn e)
Tank type
(column f)
Tank vents
(column g)
Tank environmental
control'"
(column h)

EXPLANATORY NOTES
The product names are not identical with the names given in previous is sues of the Code, or the BCH Code (for explanation see i ndex of chemical!!)

The number re latin g to eac h product shown in the recommendations proposed by the United Nations Committe e of Experts on the Transport of Dangerous Goods. UN numbers, where available, are given for information only.
The lett er A, B, C or D means the pollution category assigned to each product under

---CHUNK---

SOURCE: MEPC.55(33).pdf
Nations Committe e of Experts on the Transport of Dangerous Goods. UN numbers, where available, are given for information only.
The lett er A, B, C or D means the pollution category assigned to each product under
Annex U of MARPOL 73/78. "UI" means the product was evaluated and found to fall outside the categ ories A, B, C or D.
Pollution category in brackets indicates t hat the product is provisionally ca tegorized and that further data are nece ssary t o complete the evaluation of their pollution hazards.