---CHUNK---

SOURCE: MEPC.56(33).pdf
(adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE
CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS
CHEMICALS IN BULK (BCH CODE)- 5 -
Chapter VI
The existing text of Cha pter VI is replaced by the following:
CHAPTER VI - SUMMARY OF MINIMUM REQUIREMENTS
The summary of minimum requirements of the products covered by th e
Code is set out in chap ter 17 of the IBC Code.
For the purpose of application of the minimum requirements under
this Code. the cross references in the laC Code shown in the left hand
column of the following table should be taken to mean references to the
BCH Code shown in the right hand column. Where a reference is made in
the 8eH Code to co lumn "m" in the table of chapter VI it should be tsken
to mean any of t.he columns "mil, lin" and "0" in the table of chapter 11 of
the lBe Code.
IBC/BCH CODES CROSS REFERENCES TO THE REQUIREMENTS
IBC Code chapter 17 items ISC Code reference BCH Code reference
Ship type (column e)
1 .. ship type 1 (2.1.2) (2.2.4(a))
2 ship type 2 (2.1.2) (2.2.4(b))
3 "' ship type 3 (2.1.2) (2.2.4(c))
Tank type (column f)
1 independent tank (4. 1.ll (2.3.2)
2 ,. integral tank (4.1.2) (2.3.1)

---CHUNK---

SOURCE: MEPC.56(33).pdf
Ship type (column e)
1 .. ship type 1 (2.1.2) (2.2.4(a))
2 ship type 2 (2.1.2) (2.2.4(b))
3 "' ship type 3 (2.1.2) (2.2.4(c))
Tank type (column f)
1 independent tank (4. 1.ll (2.3.2)
2 ,. integral tank (4.1.2) (2.3.1)
G gravity tank (4.1.3) (2.4)
p preS8ure tank (4.1.4)
Tank environmental control
(column h)
Inert~ inerting (9.1.2.ll (2.19.2(a))
Pad: liquid or gas (9.1.2.2) (2.19.2(b))
Dry : drying (9.1.2.3) (2.19.2(c))
Vent: natural or forced (9.1.2.4) (2.19.2(d))
RESOLUTION MEPC.56(33)
(adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE
CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS
CHEMICALS IN BULK (BCH CODE)IRC Code chapter 17 items
Electrical equipment
(column i)

NF: non-flammable
product
Yes: Flashpoint
exceeding 60~C
(closed cup)
No: Product having a
a flashp oint not
exceeding 60~C
(closed cup)
Gauging (co lumn j)
0: open gauging
R; restricted gauging
c; closed gauging
I: indirect gauging
Materials and constructi on
(column m)
Respiratory and
eye pr otection
(column n)
- 6 -
Inc Code reference
(10.1.6)
(10.1.6)
(10.1.6)
(13.1.1.1)
(13.1.1.2)
(13.1.1.3)
(13.1.1.3)
Nl
N2
N3
N4
N5
N6
N7

---CHUNK---

SOURCE: MEPC.56(33).pdf
I: indirect gauging
Materials and constructi on
(column m)
Respiratory and
eye pr otection
(column n)
- 6 -
Inc Code reference
(10.1.6)
(10.1.6)
(10.1.6)
(13.1.1.1)
(13.1.1.2)
(13.1.1.3)
(13.1.1.3)

Nl
N2
N3
N4
N5
N6
N7
N8
Z
11
12
13
14
15
E; see 14.2.8
BCH Code reference
Standard electrical system
Standard electrical syste m
Special electrical syste ms
Open device (3.9(a»
Restricted device (3.9(b))
Closed device (3 . 9(c»
Indirect device (3.9(d))
4.12. 1
4. 12.2
4.12.3
4.12.4
4.12.5
4.12 . 8
4.12.9
4.12.1, except copper and copper alloys may be used
4.12.6
4.12 .7 (a)
4.12.7(b)
4. 12.10
4.12.6 except aluminium is not permitted
3.16.10
RESOLUTION MEPC.56(33)
(adopted on 30 October 1992)
ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (BCH CODE)IBe Code chapter 17 items
Special requirements (column 0)
Chaptet" VII

IBC Code referen ce

15.1
15.2
15.3
15.4
15.5.1 - 13
15.5.14 - 26
15.6
15.7
15.8
15.9
15.10
15.11
15.12
15 .13
15.14
15.16
15.17
15.18
15.19
15.19.6
15.20