ANNEX 10
Page 4
1 INTRODUCTION
1.1 General

---CHUNK---

SOURCE: MEPC.60(33).pdf
Documentation of approval
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPSMEPC 33/20/Add.1
ANNEX 10
Page 4
1 INTRODUCTION
1.1 General
1.1.1 The specifications in respect of oil filtering equipment are considered to be applicable for use in conjunction with oily bilge-water and ballast water from fuel oil tanks, as these are of a low or medium capacity, and are conditioned by the need to avoid discharging oily mixtures with an oil content more than 15 ppm of the mixture.
1.1.2 It is recognized that the development and testing of high capacity separating equipment designed for dealing with effluent from cargo tanks on tankers pose special problems and such equipment does not require to be tested under these specifications. Such development and tests should not be hindered and Administrations should be prepared to accept deviations from these specifications when they are considered necessary in this context.
1.1.3 It should be understood that a gravitational filtering equipment cannot be expected to be effective over the complete range of oils which might be

---CHUNK---

SOURCE: MEPC.60(33).pdf
specifications when they are considered necessary in this context.
1.1.3 It should be understood that a gravitational filtering equipment cannot be expected to be effective over the complete range of oils which might be carried on board ship, nor can it deal satisfactorily with oil of very high relative density or with a mixture presented to it as an emulsion. Cleansing agents used for cleaning purposes in machinery spaces may cause these emulsions in bilge water. To avoid this, only those cleansing agents which do not affect the performance of the equipment should be used, and care should be taken that the bilge water is fed to the filtering equipment after the emulsion has broken. Considering that not all designs of equipment are affected in the same way by cleansing agents, the manufacturers of filtering and monitoring equipment should supply recommendations concerning the use of cleans ,ing agents, and these recommendations should be followed in shipboard practice.
1.1.4 Where a range of filtering equipment of the same design, but of different capacities, requires certification in accordance with these

---CHUNK---

SOURCE: MEPC.60(33).pdf

cleans ,ing agents, and these recommendations should be followed in shipboard practice.
1.1.4 Where a range of filtering equipment of the same design, but of different capacities, requires certification in accordance with these specifications, and where the largest capacity in the range does not exceed , 50 m3 per hour, the Administration may accept tests in two capacities within the range, in lieu of tests on every size, providing that the two tests actually performed are from the lowest quarter and highest quarter of the range.
1.1.5 Regulations referred to in these Guidelines and Specifications are those contained in Annex I of MARPOL 73/78.
1.2 Purpose
1.2.1 These Guidelines and Specifications contain requirements regarding the design, installation, performance and testing of pollution prevention equipment required by regulation 16.
1.2 . 2 The purpose of these Guidelines and Specifications is:
.1 to provide a uniform interpretation of the requirements of regulation 16;
.2 to assist Administrations in determining appropriate design, construction and operational parameters for pollution prevention

---CHUNK---

SOURCE: MEPC.60(33).pdf
.1 to provide a uniform interpretation of the requirements of regulation 16;
.2 to assist Administrations in determining appropriate design, construction and operational parameters for pollution prevention equipment when such equipment is fitted in ships flying the flag of their States;
W/9146D/EWP
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPS)
MEPC 33/20/Add.l
ANNEX 10
Page 5
.3 to define test and performance requirements for pollution prevention equipment: and
.4 to provide guidance for ~nstallatipn r~quirements.
1.3 Applicability
1.3.1 These Guidelines and Specifications apply:
. 1 to installations fitted to ships, the keel of which are laid or which are at a similar stage of construction on or after 30 April 1994: and
. 2 to new installations fitted on or after 30 April 1994 to ships, the keel of which were laid or which were at a similar stage of construction before 30 April 1994 in so far as is reasonable and practicable.
1.3.2 The Guidelines and Specifications adopted under resolution A.393(X) are

---CHUNK---

SOURCE: MEPC.60(33).pdf
the keel of which were laid or which were at a similar stage of construction before 30 April 1994 in so far as is reasonable and practicable.
1.3.2 The Guidelines and Specifications adopted under resolution A.393(X) are not applicable to ships to which these new Guidelines and Specifications apply.
1.3.3 Installations fitted to ships the keel of which were laid or which were at a similar stage of construction before 30 April 1994 should comply either with the requirements contained in the Guidelines and Specifications adopted under resolution A.393(X) or with the requirements contained in these Guidelines and Specifications.
1.4 Summary of requirements
1.4.1 The approval requirements for pollution prevention equipment specified in these Guidelines and Specifications are summarized below:
.1 the oil filtering equipment should be tested for type approval in accordance with the procedures described in part 1 of the annex, subject to environmental tests specified part 3 of the annex: and
.2 the oil content meter for the bilge alarms should be tested for type approval in accordance with part 2 of the annex, subject to

---CHUNK---

SOURCE: MEPC.60(33).pdf
subject to environmental tests specified part 3 of the annex: and
.2 the oil content meter for the bilge alarms should be tested for type approval in accordance with part 2 of the annex, subject to the environmental tests specified in part 3 of the annex.
2 BACKGROUND
2.1 The requirements of Annex I of MARPOL 73/78 relating to pollution prevention equipment for ships are set out in regulation 16, which stipulates that ships of 400 tons gross tonnage and above should be installed with approved equipment.
2.2 Regulation 16(5) stipulates that the effluent from oil filtering equipment should not exceed 15 ppm. The bilge alarm shall activate to indicate when this level cannot be maintained.
3 DEFINITIONS
3.1 Pollution prevention equipment
3.1.1 For the purpose of these Guidelines and Specifications pollution prevention equipment installed in a ship in compliance with regulation 16 comprises:
W/9146D/EWP
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPSMEPC 33/20/Add.l
ANNEX 10
Page 6
.1 oil filtering equipment (15 ppm); and
.2 15 ppm bilge alarms.

---CHUNK---

SOURCE: MEPC.60(33).pdf
adopted on 30 October 1992

.1 oil filtering equipment (15 ppm); and
.2 15 ppm bilge alarms.
3.2 Oil filtering equipment
3.2.1 Oil filtering equipment may include any combination of a separator, filter or coalescer, and also a single unit designed to produce an effluent with oil content not exceeding 15 ppm.
3.3 Bilge alarm
3.3.1 The bilge alarm arrangements specified in regulation 16(5) are referred to in these Guidelines and Specifications as a "bilge alarm".
3.4 ppm
3.4.1 "ppm" means parts of oil per million parts of water by volume.
4 TECHNICAL SPECIFICATIONS
4.1 Oil filtering equipment
4.1.1 The equipment should be strongly constructed and suitable for shipboard use, bearing in mind its intended location on the ship.
4.1.2 It should, if intended to be fitted in locations where flammable atmospheres may be present, comply with the relevant safety regulations for such spaces. Any electrical equipment which is part of the equipment should be based in a non-hazardous area, or should be certified by the Administration