---CHUNK---

SOURCE: MEPC.60(33).pdf
atmospheres may be present, comply with the relevant safety regulations for such spaces. Any electrical equipment which is part of the equipment should be based in a non-hazardous area, or should be certified by the Administration as safe for use in a haza 'rdous area. Any moving parts which are fitted in hazardous areas should be arranged so as to avoid the formation of static electricity.
4.1.3 The equipment should be so designed that it functions automatically. However, provisions should be made for emergency manual control.
4.1.4 Changing the feed to the oil filtering equipment from oily-water to oil, or from oil and/or water to air should not result in the discharge overboard of any mixture containing more than 15 ppm of oil.
4.1.5 The system should require the minimum of attention to bring it into operation. In the case of equipment used for engine room bilges, there should be no need for any adjustment to valves and other equipment to bring the system into operation, and when fitted in unattended machinery spaces the equipment should be capable of operating for at least 24 hours of normal duty without attention.

---CHUNK---

SOURCE: MEPC.60(33).pdf
the system into operation, and when fitted in unattended machinery spaces the equipment should be capable of operating for at least 24 hours of normal duty without attention.
4.1.6 All working parts of the equipment which are liable to wear or to damage should be easily accessible for maintenance.
4.2 Oil content meters
4.2.1 These Specifications relate to oil content meters for bilge alarms.
W/9l46D/EWP
)
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPS)
ME PC 33/20/Add.l
ANNEX 10
Page 7
4.2.2 The meters should resist corrosion in conditions of the marine environment.
4.2.3 The meters should, if intended to be fitted in locations where flammable atmospheres may be present, comply with the relevant safety regulations for such spaces. Any electrical equipment which is part of the meter should be placed in a non-hazardous area, or should be certified by the Administration as safe for use in a hazardous atmosphere. Any moving parts which are fitted in hazardous areas should be arranged so as to avoid the formation of static electricity.

---CHUNK---

SOURCE: MEPC.60(33).pdf

Administration as safe for use in a hazardous atmosphere. Any moving parts which are fitted in hazardous areas should be arranged so as to avoid the formation of static electricity.
4.2.4 The meter should not contain or use any substance of a dangerous nature, unless adequate arrangements, acceptable to the Administration, are provided to eliminate any hazards introduced thereby.
4.2.5 It is desirable that the reading should not be affected by the type of oil. If it is, it should not be necessary to calibrate the meter on board ship, but pre-set alterations in the calibration in accordance with instructions drawn up at the time of manufacture are permitted. In the latter case, means should be available to check that the correct calibration has been selected for the oil in question. The accuracy of the readings should at all times remain within the limit specified in paragraph 2.2.1 of part 2 of the annex.
4.2.6 The response time of the meter, that is, the time which elapses between an alteration in the sample being supplied to the meter and the meter showing the correct response, should not exceed 20 seconds.

---CHUNK---

SOURCE: MEPC.60(33).pdf
4.2.6 The response time of the meter, that is, the time which elapses between an alteration in the sample being supplied to the meter and the meter showing the correct response, should not exceed 20 seconds.
4.2.7 The meter should be fitted with an alarm device which can be set to operate automatically at any pre-stated value either to alert the crew of the ship or to operate control valves. The meter for the bilge alarm should be fitted with an alarm device which should be pre-set by the manufacturer to activate when the effluent exceeds 15 ppm. These alarms should also operate automatically if at any time the meter should fail to function, require a warm-up period or otherwise be de-energized.
4.2.8 It is recommended that a simple means be provided aboard ship to check on instrument drift, and to confirm the accuracy and repeatability of the instrument reading.
5 SPECIFICATIONS FOR TYPE APPROVAL TESTING OF POLLUTION PREVENTION EQUIPMENT
5.1 Testing requirements
5.1.1 The production model of pollution prevention equipment, for which the approval will apply, should be identical to the equipment, type-tested in

---CHUNK---

SOURCE: MEPC.60(33).pdf
PREVENTION EQUIPMENT
5.1 Testing requirements
5.1.1 The production model of pollution prevention equipment, for which the approval will apply, should be identical to the equipment, type-tested in accordance with the Test and Performance Specifications contained in part 1 or 2 of the annex to these Guidelines and Specifications. The equipment should also be type-tested in accordance with the specifications for environmental testing contained in part 3 of the annex.
W/9l46D/EWP
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION

5.2 Approval and certification procedures
5.2.1 Pollution prevention equipment which in every respect fulfil the requirements of these Guidelines and Specifications may be approved by the Administration for fitting on board ships. The approval should take the form of a certificate of type approval specifying the main particulars of the apparatus and any limiting conditions on its usage necessary to ensure its proper performance. Such certificate should be issued in the format shown in

---CHUNK---

SOURCE: MEPC.60(33).pdf
form of a certificate of type approval specifying the main particulars of the apparatus and any limiting conditions on its usage necessary to ensure its proper performance. Such certificate should be issued in the format shown in part 5 of the annex. A copy of the certificate of type approval for pollution prevention equipment should be carried on board ships fitted with such equipment at all times.
5.2.2 A certificate of type approval for an oil content meter should be issued for the bilge alarm.
5.2.3 Approved pollution prevention equipment may be accepted by other countries for use on their vessels on the basis of the first trials, or after new tests carried out under the supervision of their own representatives. Should equipment pass a test in one country but fail a test of a similar nature in another country, then the two countries concerned should consult one another with a view to reaching a mutually acceptable agreement.
6 INSTALLATION REQUIREMENTS
6.1 Oil filtering equipment
6.1.1 For future inspection purposes on board ship, a sampling point should be provided in a vertical section of the water effluent piping as close as is

---CHUNK---

SOURCE: MEPC.60(33).pdf
6 INSTALLATION REQUIREMENTS
6.1 Oil filtering equipment
6.1.1 For future inspection purposes on board ship, a sampling point should be provided in a vertical section of the water effluent piping as close as is practicable to the equipment outlet. Recirculating facilities should be provided to enable the oil filtering equipment to be tested with the overboard discharge closed at initial and periodic surveys.
6.1.2 Means should be taken to ensure that, in practice, the rated capacity of the equipment is not exceeded by:
.1 connecting only pumps of a capacity equal to, or less than, that of the equipment; or
. 2 permanently restricting the discharge to the equipment where larger pumps may be connected.
6.1.3 In any case, equipment should not be supplied from a pump which has a capacity more than 1.5 times the rated capacity of the equipment.
6.1.4 The equipment should be fitted with a permanently attached plate giving any operational or installation limits considered necessary by the manufacturer or the Administration.

6.2 Oil content meters for bilge alarms
6.2.1 The layout of the shipboard installation should be arranged so that the

---CHUNK---

SOURCE: MEPC.60(33).pdf
any operational or installation limits considered necessary by the manufacturer or the Administration.
6.2 Oil content meters for bilge alarms
6.2.1 The layout of the shipboard installation should be arranged so that the overall response time between an alteration in the mixture being pumped and the alteration in the meter reading should be as short as possible and in any case not more than 40 seconds, to allow for remedial action being taken before the oil content of the mixture being discharged exceeds the permissible limit.
W/9146D/EWP
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPSJ
MEPC 33/20/Add.1
ANNEX 10
Page 9
6.2.2 The arrangement on board ship for the extraction of samples from the