Air cOCK
Observation
window
Sample point
Conditioning pipe
(see 1.2.5)
Bypass orifice or
regulating valve
Sample point
Figure 1 a
,
I
Reserve
oil tanl::
I W8~er ~===::J"-
:::::::::J S cu m
drain
Oil
filtering
equipment
, tank I--" '"
"T"T"-----!...---' sample point '--rr-- -l

---CHUNK---

SOURCE: MEPC.60(33).pdf
(see 1.2.5)
Bypass orifice or
regulating valve
Sample point
Figure 1 a
,
I
Reserve
oil tanl::
I W8~er ~===::J"-
:::::::::J S cu m
drain
Oil
filtering
equipment
, tank I--" '"
"T"T"-----!...---' sample point '--rr-- -l
t..::::::=::::::::zq " i
Reclaimed Waler oil ~ank dram L..- ---I.. _ _ --'
Sample point
W/9146D/EWP
Air cock
Sample point
Conditioning pipe
>,(t:=:;:=====~:::::::::::::::::J (se e 1.2.51
Flow meter
Sample point
Figure 1 b

Reserve
oil tank:
J
I ,
)
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION
EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPS)
MEPC 33/20/Add.1
ANNEX 10
Page 13
In order to approach isokinetic sampling, i.e. the sample enters the
sampling pipe at stream velocity, the sampling arrangement should be as
shown in figure 2 and, if a cock is fitted, free flow should be effected for
at least one minute before any sample is taken. The sampling points should
be in pipes running vertically.
1. 2.6
. 1
.2
The
for
Figure 2 - Diagram of sampling arrangements
-----,,'- " .....
"' .... "' " / " ~ ,
I \
I \
I '. \ I ~ \
I ~ T \ I f I
I 0 :' :
\ ~ C I

---CHUNK---

SOURCE: MEPC.60(33).pdf
be in pipes running vertically.
1. 2.6
. 1
.2
The
for
Figure 2 - Diagram of sampling arrangements
-----,,'- " .....
"' .... "' " / " ~ ,
I \
I \
I '. \ I ~ \
I ~ T \ I f I
I 0 :' :
\ ~ C I
\ ~ 1 I Jr\ " I
/ I
/ \ E I /' ~
/ '-'. ,/

/ .... '" / ',;~
" ' .... _-_ .... ""
~~~..-.~ Straight -through
stoPCOfk (oPtional! ~
6mm bore PiPe)J U
~-A ~-r
Funnel rOD ~
d,,;nage 'rl
A Distance A, not greater than 400 mm.
B Distance B, sufficient to insert sampling bottle.
e Dimension C, straight length should not be less than 60 mm.
o Dimension D, pipe thickness should not be greater than 2 mm.
E Detail E. chis.'-edged chamfer (30°).
following tests should be carried out:
residual fuel oils of relative density of not less than
15°C, with water having a relative density of not more than
15°C;
for residual fuel oils of relative density of 0.98 and above
0.94 at
1.015 at
at
15°C, with water having a relative density of not more than 1. 015 at
15°C.
W/9146D/EWP
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION
EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPSMEPC 33/20/Add.1
ANNEX 10
Page 14

---CHUNK---

SOURCE: MEPC.60(33).pdf
15°C.
W/9146D/EWP
Resolution MEPC.60(33)
adopted on 30 October 1992
GUIDELINES AND SPECIFICATIONS FOR POLLUTION PREVENTION
EQUIPMENT FOR MACHINERY SPACE BILGES OF SHIPSMEPC 33/20/Add.1
ANNEX 10
Page 14
1.2.7 In the case of equipment depending essentially on gravity, the feed to the system of the test water and oil water mixture should be maintained at a temperature not greater than 40°C, and heating and cooling coils should be provided where necessary. In other forms of separation where the dependence of separation efficiency on temperature is not established, tests should be carried out over a range of influent temperatures representing the normal shipboard operating range of 10°C to 40°C or should be taken at a temperature in this range where the separation efficiency is known to be worst.
1.2.8 In those cases where, for the equipment, it is necessary to heat water up to a given temperature and to supply heat to maintain that temperature, the tests should be carried out at the given temperature.
1.2.9 To ensure that the equipment commences the test with the oil section
~~~

full of oil and with the supply line impregnated with oil, the equipment

---CHUNK---

SOURCE: MEPC.60(33).pdf
tests should be carried out at the given temperature.
1.2.9 To ensure that the equipment commences the test with the oil section full of oil and with the supply line impregnated with oil, the equipment should, after filling with water and while in the operating condition, be fed with pure oil for not less than five minutes.
1.2.10 The equipment should be fed with a mixture composed of between 5,000 and 10,000 ppm of oil in water until steady conditions have been established. Steady conditions are assumed to be the conditons established after pumping through the equipment a quantity of oil/water mixture not less than twice the volume of the equipment. The test should then proceed for 30 minutes. Samples should be taken at the water outlet at 10 minutes and 20 minutes from the start of this period. At the end of this test, an air cock should be opened on the suction side of the pump and, if necessary, the oil and water valves should be slowly closed together, and a sample taken at the water discharge as the flow ceases (this point can be checked from the observation window).
1.2.11 A test identical to that described in 1.2.10, including the opening of