FOR VHF RADIO INSTALLATIONS CAPABLE OF VOICE COMMUNICATION
AND DIGITAL SELECTIVE CALLING
Modify paragraphs 11.2.5 and 11.2.6 of the Annex, as follows:
".5 facilities to automatically update the ship's position and the time at which the position was

---CHUNK---

SOURCE: MSC.68(68).pdf
AND DIGITAL SELECTIVE CALLING
Modify paragraphs 11.2.5 and 11.2.6 of the Annex, as follows:
".5 facilities to automatically update the ship's position and the time at which the position was determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard; 1
.6 means for manual entry of position information and the time at which the position was determined; and"
Add new paragraph 11.2.7 :
".7 means to activate an alarm when no position data is received from the electronic position-fixing aid or, in the case of manual input, the position information is over 4 hours old. Any position information not updated for more than 23 Y2 hours should be erased."
Modify paragraph 11.3.2, as follows:
".3.2 These messages should be stored until readout and should be erased 48 hours after their reception. II
Modify the second sentence of paragraph 11.4, as follows:
"11. 4 ..... The means for initiating a distress alert should be as prescribed in 2.6 to 2.8. II

---CHUNK---

SOURCE: MSC.68(68).pdf
reception. II
Modify the second sentence of paragraph 11.4, as follows:
"11. 4 ..... The means for initiating a distress alert should be as prescribed in 2.6 to 2.8. II
IEC 1162
J:\MSC\68\23-Add .l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT ANNEX 2
MSC 68/23/ Add . 1
ANNEX 10
Page 3
AMENDMENTS TO RESOLUTION A.804(19) - PERFORMANCE STANDARDS
FOR MF RADIO INSTALLATIONS CAPABLE OF VOICE COMMUNICATION
AND DIGITAL SELECTIVE CALLING
Modify paragraphs 2.4,2 .5 and 2.6 of Part D of the Annex, as follows :
".4 means to display, in plain language with a minimum of 160 characters in two or more lines, the information contained in a received call;
.5 facilities to automatically update the ship's position and the time at which the position was determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard; 1

---CHUNK---

SOURCE: MSC.68(68).pdf
of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard; 1
.6 means for manual entry of position information and the time at which the position was determined ; and"
Add new paragraph 2.7 of Part D, the Annex, as follows :
".7 means to activate an alarm when no position data is received from the electronic position-fixing aid or, in the case of manual input , the position information is over 4 hours old . Any position information not updated for more than 23 Yz hours should be erased."
Modify paragraph 3.2 of Part D, the Annex, as follows :
"3.2 These messages should be stored until readout and should be erased 48 hours after their reception . "
Modify the second sentence of paragraph 4 of Part D, the Annex, as follows :
"4 ..... The means for initiating a distress alert should be as prescribed in 2.5 to 2.7 of Part A."
IEC 1162
I:\MSC \68\23-Add .l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT MSC 68/231 Add. 1
ANNEX 10
Page 4

---CHUNK---

SOURCE: MSC.68(68).pdf
IEC 1162
I:\MSC \68\23-Add .l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT MSC 68/231 Add. 1
ANNEX 10
Page 4
ANNEX 3
AMENDMENTS TO RESOLUTION A.806(19) - PERFORMANCE STANDARDS FOR MF/HF RADIO INSTALLATIONS CAPABLE OF VOICE COMMUNICATION NARROW-BAND DIQECT-PRINTING AND DIGITAL SELECTIVE CALLING
Modify paragraphs 2.4, 2.5 and 2.6 of Part D, the Annex, as follows :
".4 means to display, in plain language with a minimum of 160 characters in two or more lines, the information contained in a received call;
.5 facilities to automatically update the ship's position and the time at which the position was determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard; 1
.6 means for manual entry of position information and the time at which the position was determined; and"
Add new paragraph 2.7 of Part D, the Annex :

---CHUNK---

SOURCE: MSC.68(68).pdf
international standard; 1
.6 means for manual entry of position information and the time at which the position was determined; and"
Add new paragraph 2.7 of Part D, the Annex :
".7 means to activate an alarm when no position data is received from the electronic position-fixing aid or, in the case of manual input, the position information is over 4 hours old. Any position information not updated for more than 2312 hours should be erased. II
Modify paragraph 3.2 of Part D, the Annex, as follows:
".3.2 These messages should be stored until readout and should be erased 48 hours after their reception . II
Modify the second sentence of paragraph 4 of Part D, the Annex, as follows:
"4 ..... The means for initiating a distress alert should be as prescribed in 2.5 to 2.7 of Part A"
IEC 1162
I:\MSC\68\23-Add.l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT ANNEX 4
MSC 68/23/ Add . 1
ANNEX 10
Page 5
AMENDMENTS TO RESOLUTION A.807(19) - PERFORMANCE STANDARDS FOR INMARSAT-C SHIP EARTH STATIONS CAPABLE OF TRANSMITTING AND RECEIVING DIRECT-PRINTING COMMUNICATIONS

---CHUNK---

SOURCE: MSC.68(68).pdf
MSC 68/23/ Add . 1
ANNEX 10
Page 5
AMENDMENTS TO RESOLUTION A.807(19) - PERFORMANCE STANDARDS FOR INMARSAT-C SHIP EARTH STATIONS CAPABLE OF TRANSMITTING AND RECEIVING DIRECT-PRINTING COMMUNICATIONS
Modify papragraph 3.8 of the Annex, as follows:
"3.8 Facilities should be provided to automatically update the ship's position and the time at which the position was determined from a suitable electronic position-fixing aid which may be an integral part of the equipment. For equipment which does not have an integral electronic position-fixing aid, such facilities should include a suitable interface conforming to the appropriate international standard. I"
Add'new paragraphs 3.9 and 3.10 to the Annex, as follows:
"3.9 Provisions should also be made for manual entry of position information and of the time at which the position was determined.
3.10 An alarm should be activated when no position data is received from the electronic position-fixing aid or, in the case of manual input, the position information is over 4 hours old. Any position information not updated for more than 24 hours should be clearly identified."
lEC 1162
I:\MSC\68\23-Add.l
RESOLUTION MSC.68(68)

---CHUNK---

SOURCE: MSC.68(68).pdf
aid or, in the case of manual input, the position information is over 4 hours old. Any position information not updated for more than 24 hours should be clearly identified."
IEC 1162
I:\MSC\68\23-Add.l
RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT RESOLUTION MSC.68(68)
(adopted on 6 June 1997)
ADOPTION OF AMENDMENTS TO PERFORMANCE STANDARDS
FOR SHIPBORNE RADIOCOMMUNICATION EQUIPMENT

---CHUNK---

SOURCE: MSC.133(76).pdf
RESOLUTION MSC.133(76)
(adopted on 12 December 2002)
ADOPTION OF TECHNICAL PROVISIONS FOR MEANS OF
ACCESS FOR INSPECTIONSMSC 76/23/Add.1