access manual shall include the following for each space in the cargo area:

.1 plans showing the means of access to the space, with appropriate technical specifications and dimensions;

.2 plans showing the means of access w ithin each space to enable an overall inspection to be carried out, with a ppropriate technical specifications and dimensions. The plans shall indicat e from where each area in the space can be inspected;

.3 plans showing the means of access w ithin the space to enable close-up inspections to be carried out, with a ppropriate technical specifications and dimensions. The plans shall indicate the positions of critical structural areas, whether the means of access is permanent or portable and from where each area can be inspected;

---CHUNK---

SOURCE: MSC.134(76).pdf
dimensions. The plans shall indicate the positions of critical structural areas, whether the means of access is permanent or portable and from where each area can be inspected;

_____

* Refer to the Recommendations for entering enclosed spaces aboard ships, adopted by the Organization by resolution A.864(20).

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDMSC 76/23/Add.1
ANNEX 3

.4 instructions for inspecting and main taining the structural strength of all means of access and means of attachment, taking into account any corrosive atmosphere that may be within the space;

.5 instructions for safety guidance when rafting is used for close-up inspections and thickness measurements;

.6 instructions for the rigging and use of any portable means of access in a safe manner;

.7 an inventory of all portable means of access; and

.8 records of periodical inspections and maintenance of the ship’s means of access.

---CHUNK---

SOURCE: MSC.134(76).pdf
.6 instructions for the rigging and use of any portable means of access in a safe manner;

.7 an inventory of all portable means of access; and

.8 records of periodical inspections and maintenance of the ship's means of access.

4.2 For the purpose of this regulation "critical structural areas" are locations which have been identified from calculations to require monitoring or from the service history of similar or sister ships to be sensitive to cracking, buckling, deformation or corrosion which would impair the structural integrity of the ship.

5 General technical specifications

5.1 For access through horizontal openings, hatc hes or manholes, the dimensions shall be sufficient to allow a person wearing a self-contained air-breathing apparatus and protective equipment to ascend or desce nd any ladder without obstruction and also provide a clear opening to facilitate the hoisti ng of an injured person from the bottom of the space. The minimum clear opening sha ll not be less than 600 mm x 600 mm. When access to a cargo hold is arranged through the cargo hatch, the top of the ladder shall be

---CHUNK---

SOURCE: MSC.134(76).pdf
the space. The minimum clear opening sha ll not be less than 600 mm x 600 mm. When access to a cargo hold is arranged through the cargo hatch, the top of the ladder shall be placed as close as possible to the hatch coam ing. Access hatch coamings having a height greater than 900 mm shall also have steps on the outside in conjunction with the ladder.

5.2 For access through vertical openings, or manholes, in swash bulkheads, floors, girders and web frames providing passage th rough the length and breadth of the space, the minimum opening shall be not less than 600 mm x 800 mm at a height of not more than 600 mm from the bottom shell plating unless gratings or other foot holds are provided.

5.3 For oil tankers of less than 5,000 tonne s deadweight, the Administration may approve, in special circumstances, smaller dimensions for the openings referred to in paragraphs 5.1 and 5.2, if the ability to traverse such openings or to remove an injured person can be proved to the satisfaction of the Administration."

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL

---CHUNK---

SOURCE: MSC.134(76).pdf
person can be proved to the satisfaction of the Administration."

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL

PART B

SUBDIVISION AND STABILITY

Regulation 12-2 - Access to spaces in the cargo area of oil tankers

2 The existing regulation 12-2 is deleted.

PART C

MACHINERY INSTALLATIONS

Regulation 31 - Machinery control

3 The following new subparagraph .10 is added to paragraph 2 of the regulation:

".10 automation systems shall be designed in a manner which ensures that threshold warning of impending or imminent sl owdown or shutdown of the propulsion system is given to the officer in charge of the navigational watch in time to assess navigational circumstances in an emerge ncy. In particular, the systems shall control, monitor, report, alert and take safety action to slow down or stop propulsion while providing the officer in charge of the navigational watch an opportunity to manually intervene, except for those cases where manual

---CHUNK---

SOURCE: MSC.134(76).pdf
control, monitor, report, alert and take safety action to slow down or stop propulsion while providing the officer in charge of the navigational watch an opportunity to manually intervene, except for those cases where manual intervention will result in total failure of the engine and/or propulsion equipment within a short time, for example in the case of overspeed."

CHAPTER II-2

CONSTRUCTION – FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION

Regulation 3 – Definitions

4 In paragraph 20, the words “regulation V II/2” are replaced by the words “the IMDG Code, as defined in regulation VII/1.1”.

Regulation 19 – Carriage of dangerous goods

5 In table 19.3, in vertical columns 7 and 8 (c oncerning flashpoints of class 3), the numbers “3.1 3.2” and “3.3”, respectively, are replaced by the number “3”.

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDMSC 76/23/Add.1
ANNEX 3
Page 6

I:\MSC\76\23-ADD.1.DOC
6 In table 19.3, in vertical column 13 (concer ning class 5.2), the character “X” in rows 15

---CHUNK---

SOURCE: MSC.134(76).pdf
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDMSC 76/23/Add.1
ANNEX 3
Page 6