6 In table 19.3, in vertical column 13 (concer ning class 5.2), the character “X” in rows 15 (concerning paragraph 3.10.1) and 16 (concerning pa ragraph 3.10.2) is replaced by the character “X16” and a new note 16 is added as follows:

“16 Under the provisions of the IMDG Code, as amended, stowage of class 5.2 dangerous goods under deck or in enclosed ro-ro spaces is prohibited.”

CHAPTER III

LIFE-SAVING APPLIANCES AND ARRANGEMENTS

Regulation 26 - Additional requirements for ro-ro passenger ships

7 The following new subparagraph .4 is added at the end of paragraph 1:

".4 before 1 July 2004 shall comply with the requirements of paragraph 2.5 not later than the first survey on or after that date."

8 The following new subparagraph .5 is added at the end of paragraph 2:

".5 Liferafts carried on ro-ro passenger ship s shall be fitted with a radar transponder * in the ratio of one transponder for every four liferafts. The transponder shall be mounted inside the liferaft so its antenna is more than one metre above the sea

---CHUNK---

SOURCE: MSC.134(76).pdf
in the ratio of one transponder for every four liferafts. The transponder shall be mounted inside the liferaft so its antenna is more than one metre above the sea level when the liferaft is deployed, except th at for canopied reversible liferafts the transponder shall be so arranged as to be readily accessed and erected by survivors. Each transponder shall be a rranged to be manually erected when the liferaft is deployed. Containers of lifer afts fitted with transponders shall be clearly marked.

_____

* Refer to the Performance standards for survival craft radar transponders for use in search and rescue operations, adopted by the Organization by resolution A.802(19).”

CHAPTER XII

ADDITIONAL SAFETY MEASURES FOR BULK CARRIERS

9 The following new regulations 12 and 13 are added after existing regulation 11:

“Regulation 12

Hold, ballast and dry space water level detectors

(This regulation applies to bulk carriers regardless of their date of construction)

1 Bulk carriers shall be fitted with water level detectors:

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL

---CHUNK---

SOURCE: MSC.134(76).pdf
1 Bulk carriers shall be fitted with water level detectors:

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDMSC 76/23/Add.1
ANNEX 3
Page 7

I:\MSC\76\23-ADD.1.DOC
.1 in each cargo hold, giving audible and visual alarms, one when the water level above the inner bottom in any hold reaches a height of 0.5 m and another at a height not less than 15% of the depth of the cargo hold but not more than 2 m. On bulk carriers to which regulation 9.2 applies, detectors with only the latter alarm need be installed. The water level detectors shall be fitted in the aft end of the cargo holds. For cargo holds which are used for water ballast, an alarm overriding de vice may be installed. The visual alarms shall clearly discriminate be tween the two different water levels detected in each hold;

.2 in any ballast tank forward of the collision bulkhead required by regulation II-1/11, giving an audible a nd visual alarm when the liquid in the tank reaches a level not exceeding 10% of the tank capacity. An alarm

---CHUNK---

SOURCE: MSC.134(76).pdf
detected in each hold;

.2 in any ballast tank forward of the collision bulkhead required by regulation II-1/11, giving an audible a nd visual alarm when the liquid in the tank reaches a level not exceeding 10% of the tank capacity. An alarm
overriding device may be installed to be activated when the tank is in use; and

.3 in any dry or void space other than a chain cable locker, any part of which extends forward of the foremost cargo hold, giving an audible and visual alarm at a water level of 0.1 m above the deck. Such alarms need not be provided in enclosed spaces the volume of which does not exceed 0.1% of the ship’s maximum displacement volume.

2 The audible and visual alarms specified in paragraph 1 shall be located on the navigation bridge.

3 Bulk carriers constructed before 1 July 2004 shall comply with the requirements of this regulation not later than the date of the annual, intermediate or renewal survey of the ship to be carried out after 1 July 2004, whichever comes first.

Regulation 13

Availability of pumping systems

(This regulation applies to bulk carriers regardless of their date of construction)

---CHUNK---

SOURCE: MSC.134(76).pdf
the ship to be carried out after 1 July 2004, whichever comes first.

Regulation 13

Availability of pumping systems

(This regulation applies to bulk carriers regardless of their date of construction)

1 On bulk carriers, the means for draining and pumping ballast tanks forward of the collision bulkhead and bilges of dry spaces a ny part of which extends forward of the foremost cargo hold shall be capable of being brought into operation from a readily accessible enclosed space, the location of which is accessible from the navigation bridge or propulsion machinery control position without traversing exposed freeboard or superstructure decks. Where pipes servi ng such tanks or bilges pierce the collision bulkhead, valve operation by means of remote ly operated actuators may be accepted, as an alternative to the valve control specifi ed in regulation II-1/11.4, provided that the location of such valve controls complies with this regulation.

2 Bulk carriers constructed before 1 July 2004 shall comply with the requirements of this regulation not later than the date of th e first intermediate or renewal survey of the

---CHUNK---

SOURCE: MSC.134(76).pdf
location of such valve controls complies with this regulation.

2 Bulk carriers constructed before 1 July 2004 shall comply with the requirements of this regulation not later than the date of th e first intermediate or renewal survey of the ship to be carried out after 1 July 2004, but in no case later than 1 July 2007.”

***

RESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDRESOLUTION MSC.134(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL
CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

---CHUNK---

SOURCE: MSC.135(76).pdf
RESOLUTION MSC.135(76)
(adopted on 12 December 2002)
ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE
FOR THE SAFE CARRIAGE OF ACKAGED IRRADIATED NUCLEAR FUEL, PLUTONIUM AND HIGH-LEVEL RADIOACTIVE WASTES ON BOARD SHIPS
(INF CODE)

RESOLUTION MSC.135(76)
(adopted on 12 December 2002)

ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE
FOR THE SAFE CARRIAGE OF PACKAGED IRRADIATED NUCLEAR FUEL,
PLUTONIUM AND HIGH-LEVEL RADIOACTIVE WASTES ON BOARD SHIPS
(INF CODE)

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

NOTING resolution MSC.88(71), by which it adopted the International Code for the Safe