I:\MSC\76\23-ADD.1.DOC
ANNEX

RECOMMENDATION ON PERFORMANCE STANDARDS
FOR A SHIP SECURITY ALERT SYSTEM

1 Introduction

1.1 The ship security alert system is provided to a ship for the purpose of transmitting a security alert to the shore to indicate to a competent authority that the security of the ship is under threat or has been compromised. It comprises a minimum of two activation points, one of which is on the navigation bridge. These initiate the transmission of a ship security alert. The system is intended to allow a covert activation to be made which alerts the competent authority ashore and does not raise an alarm on board ship nor alert other ships.

1.2 As required by its Administration, the compet ent authority receiving the alert notifies the authority responsible for maritime security with in its Administration, the coastal State(s) in whose vicinity the ship is presently operating, or other Contracting Governments.

1.3 The procedures for the use of the ship s ecurity alert system and the location of the activation points are given in the ship security plan agreed by the Administration.

---CHUNK---

SOURCE: MSC.136(76).pdf
1.3 The procedures for the use of the ship s ecurity alert system and the location of the activation points are given in the ship security plan agreed by the Administration.

1.4 The ship security alert system may utilise the radio installation provided for compliance with chapter IV of the SO LAS Convention, other radio systems provided for general communications or dedicated radio systems.

2 General

2.1 In addition to complying with the genera l requirements set out in resolution A.694(17) 1, the ship security alert system should comply with the following performance standards.

2.2 The radio system used for the ship security alert systems should comply with relevant international standards.

3 Power supply

Where the ship security alert system is powered from the ship’s main source of electrical power, it should, in addition, be possible to operate the system from another appropriate source of power.

4 Activation points

Activation points should be capable of being used on the navigation bridge and in other locations.

They should be protected against inadvertent opera tion. It should not be necessary for the user to

---CHUNK---

SOURCE: MSC.136(76).pdf
power.

4 Activation points

Activation points should be capable of being used on the navigation bridge and in other locations. They should be protected against inadvertent opera tion. It should not be necessary for the user to remove seals or to break any lid or cover in order to operate any control.

1 Publication IEC60945

RESOLUTION MSC.136(76)
(adopted on 11 December 2002)
PERFORMANCE STANDARDS FOR A SHIP
SECURITY ALERT SYSTEMMSC 76/23/Add.1
ANNEX 5
Page 3

I:\MSC\76\23-ADD.1.DOC
5 Operation

5.1 The activation points should operate a radio system such that transmission of the security alert does not require any adjustment of the ra dio system, i.e. tuning of channels, setting of modes or menu options. Operation of the ac tivation point should not cause any alarm or indication to be raised on the ship.

5.2 The operation of the ship security alert system should not impair the functionality of the GMDSS installation.

6 Transmission of security alerts

6.1 In all cases, transmission initiated by secu rity alert system activation points should

---CHUNK---

SOURCE: MSC.136(76).pdf
5.2 The operation of the ship security alert system should not impair the functionality of the GMDSS installation.

6 Transmission of security alerts

6.1 In all cases, transmission initiated by secu rity alert system activation points should include a unique code/identifier indicating that the alert has not been generated in accordance with GMDSS distress procedures. The transmissi on should include the ship identity and current position. The transmission should be addressed to a shore station and should not be addressed to ship stations.

6.2 The ship security alert system, when activat ed, should continue the ship security alert until deactivated and/or reset.

7 Testing

The ship security alert system should be capable of being tested.

***

RESOLUTION MSC.136(76)
(adopted on 11 December 2002)
PERFORMANCE STANDARDS FOR A SHIP
SECURITY ALERT SYSTEMRESOLUTION MSC.136(76)
(adopted on 11 December 2002)
PERFORMANCE STANDARDS FOR A SHIP
SECURITY ALERT SYSTEM

---CHUNK---

SOURCE: MSC.137(76).pdf
RESOLUTION MSC.137(76)
(adopted on 4 December 2002)
STANDARDS FOR SHIP MANOEUVRABILITYMSC 76/23/Add.1

I:\MSC\76\23-ADD.1.DOC

ANNEX 6

RESOLUTION MSC.137(76)
(adopted on 4 December 2002)

STANDARDS FOR SHIP MANOEUVRABILITY

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO that by resolution A.751(18) the Assembly approved Interim Standards for ship manoeuvrability (the Interim standards), whereby Governments were recommended to encourage those responsible for the design, construction, repair and operation of ships to apply the Interim Standards and invited to collect data obtained by the application of the Interim Standards and report them to the Organization,

RECALLING FURTHER that by circular MSC/Circ.1053 the Committee approved Explanatory notes to the Standards for ship manoeuvrability, to provide Administrations with specific guidance so that adequate data may be collected by the Organization on the manoeuvrability of ships,

RECOGNIZING the manoeuvring capability of ship s to be an important contribution to

---CHUNK---

SOURCE: MSC.137(76).pdf
specific guidance so that adequate data may be collected by the Organization on the manoeuvrability of ships,

RECOGNIZING the manoeuvring capability of ship s to be an important contribution to the safety of navigation,

BELIEVING that the development and im plementation of standards for ship manoeuvrability, particularly for large ships and ships carrying dangerous goods in bulk, will improve maritime safety and enhance marine environmental protection,

HAVING CONSIDERED the recommendation made by the Sub-Committee on Ship Design and Equipment at its forty-fifth session,

1. ADOPTS the Standards for ship manoeuvrabilit y, the text of which is set out in the Annex to the present resolution;

2. INVITES Governments to encourage those re sponsible for the design, construction, repair and operation of ships to apply the Standards to ships constructed on or after 1 January 2004;

3. RESOLVES that the provisions annexed to the present resolution supersede the provisions annexed to resolution A.751(18).