MANDATORY SHIP REPORTING SYSTEMS

---CHUNK---

SOURCE: MSC.140(76).pdf
RESOLUTION MSC.140(76)
(adopted on 5 December 2002)
RECOMMENDATION FOR THE PROTECTION
OF THE AIS VHF DATA LINKMSC 76/23/Add.1

I:\MSC\76\23-ADD.1.DOC
ANNEX 14

RESOLUTION MSC.140(76)
(adopted on 5 December 2002)

RECOMMENDATION FOR THE PROTECTION
OF THE AIS VHF DATA LINK

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution A.886(21), by which the Assembly resolved that the functions of adopting performance standards and technical specifications for radio and navigational equipment, as well as amendments thereto, shall be performed by the Maritime Safety Committee on behalf of the Organization,

RECALLING FURTHER resolution MSC.74(69), Annex 3 - Recommendation on Performance Standards for an Universal Shipborne Automatic Identification System (AIS),

REALIZING the application of AIS devices to safety of navigation as well as security,

NOTING that the International Tel ecommunications Union Sector for Radiocommunications (ITU-R) recognizes a Cla ss A category of AIS meeting the requirements

---CHUNK---

SOURCE: MSC.140(76).pdf
REALIZING the application of AIS devices to safety of navigation as well as security,

NOTING that the International Tel ecommunications Union Sector for Radiocommunications (ITU-R) recognizes a Cla ss A category of AIS meeting the requirements of resolution MSC.74(69), as well as Class B and other categories of AIS not meeting the requirements of resolution MSC.74(69), Annex 3,

NOTING ALSO that Class A devices are in tended to meet compulsory AIS fitting requirements of the 1974 SOLAS Convention, and Class B devices are intended to meet the needs of vessels, which fit AIS on a voluntary basis,

NOTING FURTHER the benefit of Class B devices,

RECOGNIZING that the radio channels used by AIS, particular ly AIS 1 (161.975 MHz) and AIS 2 (162.025 MHz), are regarded as an AIS network, and any disruption to those channels by any one AIS device could affect the operation of all AIS devices on that network,

RECOGNIZING FURTHER the compelling need to ensure the integrity of the AIS VHF data link,

RECOMMENDS that:

.1 Class B AIS devices, as well as any devi ce which transmits on the radio channels

---CHUNK---

SOURCE: MSC.140(76).pdf
RECOGNIZING FURTHER the compelling need to ensure the integrity of the AIS VHF data link,

RECOMMENDS that:

.1 Class B AIS devices, as well as any devi ce which transmits on the radio channels AIS 1 or AIS 2, should meet the appr opriate requirements of Recommendation ITU-R M.1371 (series);

.2 Class B AIS devices should be approved by the Administration;

.3 Administrations should take steps necessary to ensure the integrity of the radio channels used for AIS in their waters.

***

RESOLUTION MSC.140(76)
(adopted on 5 December 2002)
RECOMMENDATION FOR THE PROTECTION
OF THE AIS VHF DATA LINKRESOLUTION MSC.140(76)
(adopted on 5 December 2002)
RECOMMENDATION FOR THE PROTECTION
OF THE AIS VHF DATA LINK

---CHUNK---

SOURCE: MSC.141(76).pdf
RESOLUTION MSC.141(76)
(adopted on 5 December 2002)
REVISED MODEL TEST METHOD UNDER RESOLUTION 14
OF THE 1995 SOLAS CONFERENCEMSC 76/23/Add.1

I:\MSC\76\23-ADD.1.DOC

ANNEX 17

RESOLUTION MSC.141(76)
(adopted on 5 December 2002)

REVISED MODEL TEST METHOD UNDER RESOLUTION 14
OF THE 1995 SOLAS CONFERENCE

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 38(c) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution 14 on Regi onal agreements on specific stability requirements for ro-ro passenger ships, adopted by the Conference of C ontracting Governments to the International Convention for the Sa fety of Life at S ea, 1974 (the 1995 SOLAS Conference),

NOTING that resolution 14 of the 1995 SOLA S Conference includes an option whereby the Administration may, as an alternative to calculation of the stability properties of a ship, accept model tests carried out for an individual ship in accordance with the model test method developed by the Organization, as appended to the Annex to the said resolution,

---CHUNK---

SOURCE: MSC.141(76).pdf
accept model tests carried out for an individual ship in accordance with the model test method developed by the Organization, as appended to the Annex to the said resolution,

BEING AWARE of the experience gained from model tests carried out in the past by Administrations using the aforementioned model test method,

BEARING IN MIND the compelling need to keep pace with new technology and knowledge,

HAVING CONSIDERED the recommendation made by the Sub-Committee on Stability and Load Lines and on Fishing Vessels Safety at its forty-fifth session,

1. ADOPTS the Revised Model Test Method under resolution 14 of the 1995 SOLAS Conference, including the associated Guidance Notes appended thereto, the text of which is set out in the Annex to the present resolution;

2. INVITES Member Governments which are party to regional agreements under resolution 14 of the 1995 SOLAS Conference to use the annexed Revised Model Test Method and associated Guidance Notes in lieu of the or iginal model test method appended to the said resolution.

RESOLUTION MSC.141(76)
(adopted on 5 December 2002)
REVISED MODEL TEST METHOD UNDER RESOLUTION 14

---CHUNK---

SOURCE: MSC.141(76).pdf
and associated Guidance Notes in lieu of the or iginal model test method appended to the said resolution.

ANNEX

REVISED MODEL TEST METHOD

1 Objectives

This revised model test method is a revision of the method contained in the Appendix to the Annex to resolution 14 of the 1995 SOLAS Conf erence. Since the entry into force of the Stockholm Agreement a number of model tests has been carried out in accordance with the test method previously in force. During these tests a number of refinements in the procedures have been identified. This new model test method aims to include these refinements and, together with the appended Guidance Notes, provide a more robust procedure for the assessment of survivability of a damaged ro-ro passenger ship in a seaway. In this respect, the model should prove capable of withstanding the seaway define d in paragraph 4 below, in the worst damage case scenario.