---CHUNK---

SOURCE: MSC.194(80).pdf
access to the bow even in severe weather conditions. Such means of access shall be approved by the Administration based on the guidelines developed by the Organization.

Regulation 3-4
Emergency towing arrangements on tankers

1 Emergency towing arrangements shall be fitted at both ends on board every tanker of not less than 20,000 tonnes deadweight.

2 For tankers constructed on or after 1 July 2002:

.1 the arrangements shall, at all times, be capable of rapid deployment in the absence of main power on the ship to be towed and easy connection to the towing ship. At least one of the em ergency towing arrangements shall be pre-rigged ready for rapid deployment; and

.2 emergency towing arrangements at both ends shall be of adequate strength taking into account the size and deadwei ght of the ship, and the expected forces during bad weathe r conditions. The desi gn and construction and prototype testing of the emergency towing arrangements shall be approved by the Administration, based on the Guidelines developed by the Organization.

3 For tankers constructed before 1 July 2002, the design and construction of
SOURCE: MSC.194(80).pdf
prototype testing of the emergency towing arrangements shall be approved by the Administration, based on the Guidelines developed by the Organization.

3 For tankers constructed before 1 July 2002, the design and construction of emergency towing arrangements shall be approved by the Administration, based on the Guidelines developed by the Organization.

Regulation 3-5
New installation of materials containing asbestos

1 This regulation shall appl y to materials used for the structure, machinery, electrical installations and equipment covered by the present Convention.

2 For all ships, new installation of mate rials which contain asbestos shall be prohibited except for:

.1 vanes used in rotary vane compressors and rotary vane vacuum pumps;

.2 watertight joints and linings used for the circulation of fluids when, at high temperature (in excess of 350C) or pressure (in excess of 7 x 10 6 Pa), there is a risk of fire, corrosion or toxicity; and

.3 supple and flexible thermal insulation assemblies used for temperatures above 1,000C.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)

---CHUNK---

SOURCE: MSC.194(80).pdf
there is a risk of fire, corrosion or toxicity; and

.3 supple and flexible thermal insulation assemblies used for temperatures above 1,000C.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-4 -

Regulation 3-6
Access to and within spaces in, and forward of, the cargo area of oil tankers and bulk carriers

1 Application

1.1 Except as provided for in paragraph 1.2, th is regulation applie s to oil tankers of 500 gross tonnage and over and bulk carri ers, as defined in regulation IX/1, of 20,000 gross tonnage and over, constructed on or after 1 January 2006.

1.2 Oil tankers of 500 gross t onnage and over constructed on or after 1 October 1994 but before 1 January 2005 shall comply with the provisions of regulation II-1/12-2 adopted by resolution MSC.27(61).

2 Means of access to cargo and other spaces

2.1 Each space shall be provided with mean s of access to enable, throughout the life of a ship, overall and close-up inspections and thickness measurements of the ship's structures to be carried out by the Ad ministration, the company, as defined in

---CHUNK---

SOURCE: MSC.194(80).pdf
of a ship, overall and close-up inspections and thickness measurements of the ship's structures to be carried out by the Ad ministration, the company, as defined in regulation IX/1, and the ship's personnel and ot hers as necessary. Such means of access shall comply with the requirements of paragr aph 5 and with the Technical provisions for means of access for inspections, adopted by the Maritime Safety Committee by resolution MSC.133(76), as may be amended by the Organization, provided that such amendments are adopted, brought into force and take effect in accordance with the provisions of article VIII of the present Convention concerning the amendment procedures applicable to the Annex other than chapter I.

2.2 Where a permanent means of access may be susceptible to damage during normal cargo loading and unloading operations or where it is impracticable to fit permanent means of access, the Administration may allow, in lieu thereof, the provision of movable or portable means of access, as specified in the Technical provision s, provided that the

means of attaching, rigging, suspending or s upporting the portable means of access forms

---CHUNK---

SOURCE: MSC.194(80).pdf
or portable means of access, as specified in the Technical provision s, provided that the means of attaching, rigging, suspending or s upporting the portable means of access forms a permanent part of the ship's structure. All portable equipment shall be capable of being readily erected or deployed by ship's personnel.

2.3 The construction and materials of all mean s of access and their attachment to the ship's structure shall be to the satisfaction of the Admi nistration. The means of access shall be subject to survey prior to, or in conjunction with, its use in carrying out surveys in accordance with regulation I/10.

3 Safe access to cargo holds, cargo ta nks, ballast tanks and other spaces

3.1 Safe access to cargo holds, cofferdams, ballast tanks, cargo tanks and other spaces in the cargo area shall be direct from the open deck and such as to ensure their complete inspection. Safe access to double bottom spaces or to forward ballast tanks may be from a pump-room, deep cofferdam, pipe tunnel, cargo hold, double hu ll space or similar compartment not intended for the carriage of oil or hazardous cargoes.

---CHUNK---

SOURCE: MSC.194(80).pdf
inspection. Safe access to double bottom spaces or to forward ballast tanks may be from a pump-room, deep cofferdam, pipe tunnel, cargo hold, double hu ll space or similar compartment not intended for the carriage of oil or hazardous cargoes.

3.2 Tanks, and subdivisions of tanks, having a length of 35 m or more, shall be fitted with at least two access hatchways and ladders, as far apart as practicable. Tanks less than 35 m in length shall be served by at l east one access hatchway and ladder. When a tank is subdivided by one or more swash bulkheads or similar obstructions which do not allow ready means of access to the other part s of the tank, at least two hatchways and ladders shall be fitted.
RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-5 -

3.3 Each cargo hold shall be provided with at least two means of access as far apart as practicable. In general, these accesses should be arranged diagonally, for example one access near the forward bulkhead on the port side, the other one near the aft bulkhead on the starboard side.

4 Ship structure access manual

---CHUNK---

SOURCE: MSC.194(80).pdf
practicable. In general, these accesses should be arranged diagonally, for example one access near the forward bulkhead on the port side, the other one near the aft bulkhead on the starboard side.

4 Ship structure access manual

4.1 A ship’s means of access to carry out overall and close- up inspections and thickness measurements shall be described in a Ship structure access manual approved by the Administration, an updated copy of which shall be kept on board. The Ship structure access manual shall include the following for each space:

.1 plans showing the means of access to the space, with appropriate technical specifications and dimensions;

.2 plans showing the means of access w ithin each space to enable an overall inspection to be carried out, with appr opriate technical specifications and dimensions. The plans shall indicate from where each area in the space can be inspected;

.3 plans showing the means of access with in the space to enable close-up inspections to be carried out, with a ppropriate technical specifications and dimensions. The plans shall indicate the positions of critical structural

---CHUNK---

SOURCE: MSC.194(80).pdf
.3 plans showing the means of access with in the space to enable close-up inspections to be carried out, with a ppropriate technical specifications and