dimensions. The plans shall indicate the positions of critical structural areas, whether the means of access is permanent or portable and from where each area can be inspected;

.4 instructions for inspecti ng and maintaining the stru ctural strength of all means of access and means of a ttachment, taking into account any corrosive atmosphere that may be within the space;

.5 instructions for safety guidance wh en rafting is used for close-up inspections and thickness measurements;

.6 instructions for the rigging and use of any portable means of access in a safe manner;

.7 an inventory of all portable means of access; and

.8 records of periodical inspections an d maintenance of the ship's means of access.

4.2 For the purpose of this re gulation "critical structural areas" are locations which have been identified from calculations to require monitoring or from the service history of similar or sister ships to be sensitive to cracking, buckling, deformation or corrosion

---CHUNK---

SOURCE: MSC.194(80).pdf
have been identified from calculations to require monitoring or from the service history of similar or sister ships to be sensitive to cracking, buckling, deformation or corrosion which would impair the structural integrity of the ship.

5 General technical specifications

5.1 For access through horizontal openings, hatc hes or manholes, the dimensions shall be sufficient to allow a person wearing a self-contained air-breat hing apparatus and protective equipment to ascend or desce nd any ladder without obstruction and also provide a clear opening to faci litate the hoisting of an injure d person from the bottom of the space. The minimum clear opening shall not be less than 600 mm x 600 mm. When access to a cargo hold is arranged through the cargo hatch, the top of the ladder shall be

placed as close as possible to the hatch coaming. Access hatch coamings having a height greater than 900 mm shall also have steps on the outside in conjunction with the ladder.

---CHUNK---

SOURCE: MSC.194(80).pdf
placed as close as possible to the hatch coaming. Access hatch coamings having a height greater than 900 mm shall also have steps on the outside in conjunction with the ladder.

5.2 For access through vertical openings, or manholes, in swash bulkheads, floors, girders and web frames providing passage th rough the length and breadth of the space,

the minimum opening shall be not less than 600 mm x 800 mm at a height of not more than 600 mm from the bottom shell plating unless gratings or other foot holds are provided.

5.3 For oil tankers of less than 5,000 tonne s deadweight, the Administration may approve, in special circumstances, smaller di mensions for the openings referred to in paragraphs 5.1 and 5.2, if the ability to traverse such openings or to remove an injured person can be proved to the satisfaction of the Administration.

Regulation 3-7
Construction drawings maintained on board and ashore

1 A set of as-built construction drawings and other plans showing any subsequent structural alterations shall be kept on board a ship constructed on or after 1 January 2007.

2 An additional set of such drawings sh all be kept ashore by the Company, as

---CHUNK---

SOURCE: MSC.194(80).pdf
structural alterations shall be kept on board a ship constructed on or after 1 January 2007.

2 An additional set of such drawings sh all be kept ashore by the Company, as defined in regulation IX/1.2.

Regulation 3-8
Towing and mooring equipment

1 This regulation applies to ships constructed on or after 1 January 2007, but does not apply to emergency towing arrangements provided in accordance with regulation 3-4.

2 Ships shall be provided with arrangemen ts, equipment and fittings of sufficient safe working load to enable the safe conduct of all towing and mooring operations associated with the normal operation of the ship.

3 Arrangements, equipment and fittings provided in accordance with paragraph 2 shall meet the appropriate requirements of the Administ ration or an organization recognized by the Administration under regulation I/6.

4 Each fitting or item of equipment provide d under this regulati on shall be clearly marked with any restrictions associated w ith its safe operation, taking into account the strength of its attachment to the ship’s structure.”

PART B
SUBDIVISION AND STABILITY

---CHUNK---

SOURCE: MSC.194(80).pdf
marked with any restrictions associated w ith its safe operation, taking into account the strength of its attachment to the ship’s structure.”

PART B
SUBDIVISION AND STABILITY

3 The following new regulation 23-3 is added after existing regulation 23-2:

“Regulation 23-3
Water level detectors on single hold cargo ships other than bulk carriers

1 Single hold cargo ships other than bulk carriers constructed before 1 January 2007 shall comply with the requirements of this regulation not later than the date of the first intermediate or renewal survey of the sh ip to be carried out after 1 January 2007, whichever comes first.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-7 -

2 For the purpose of this regulation, freeboard deck has the meaning defined in the International Convention on Load Lines in force.

3 Ships having a length (L) of less than 80 m, or 100 m if constructed before 1 July 1998, and a single cargo hold be low the freeboard deck or cargo holds below the freeboard deck which are not separated by at least one bulkhead made

---CHUNK---

SOURCE: MSC.194(80).pdf
3 Ships having a length (L) of less than 80 m, or 100 m if constructed before 1 July 1998, and a single cargo hold be low the freeboard deck or cargo holds below the freeboard deck which are not separated by at least one bulkhead made watertight up to that deck, shall be fitte d in such space or spaces with water level detectors.

4 The water level detectors re quired by paragraph 3 shall:

.1 give an audible and visual alarm at the navigation bridge when the water level above the inner bottom in the cargo hold reaches a height of not less than 0.3 m, and another when such level reaches not more than 15% of the mean depth of the cargo hold; and

.2 be fitted at the aft end of the hold, or above its lowest part where the inner bottom is not parallel to the designed waterline. Where webs or partial watertight bulkheads are fitted above the inner bottom, Administrations may require the fitting of additional detectors.

5 The water level detectors required by paragrap h 3 need not be fitted in ships complying with regulation XII/ 12, or in ships having waterti ght side compartments each

---CHUNK---

SOURCE: MSC.194(80).pdf
Administrations may require the fitting of additional detectors.

5 The water level detectors required by paragrap h 3 need not be fitted in ships complying with regulation XII/ 12, or in ships having waterti ght side compartments each

side of the cargo hold length extending vertica lly at least from inner bottom to freeboard deck."

PART C
MACHINERY INSTALLATIONS

Regulation 31 Machinery controls

4 The existing paragraph 2.10 is deleted.

5 The following new paragraph 6 is a dded after the existing paragraph 5:

"6 Ships constructed on or after 1 July 2004 shall comply with the requirements of paragraphs 1 to 5, as amended, as follows:

.1 a new subparagraph .10 is added to paragraph 2 to read as follows:

".10 automation systems shall be designed in a manner which ensures that threshold warning of impe nding or imminent slowdown or shutdown of the propulsion system is given to the officer in charge of the navigational watch in time to assess navigational circumstances in an emergency. In particular, the systems shall control, monitor, report, alert a nd take safety action to slow down

---CHUNK---