above the waterline when the ship heels to an angle of 15, or the maximum angle of heel during intermediate stages of flooding, as de termined by direct calculation, whichever is

---CHUNK---

SOURCE: MSC.194(80).pdf
above the waterline when the ship heels to an angle of 15, or the maximum angle of heel during intermediate stages of flooding, as de termined by direct calculation, whichever is the greater. Alternatively, air pipes from tanks other than oil tanks may discharge through the side of the superstructure. The provision s of this paragraph ar e without prejudice to the provisions of the International Convention on Load Lines in force.

4 Sidescuttles, gangway, cargo and fuelli ng ports and other means for closing openings in the shell plating above the bulkhead deck shall be of efficient design and construction and of sufficient strength having regard to the spaces in which they are fitted and their positions relative to the deepest subdivision draught.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-41 -

5 Efficient inside deadlights, so arranged that they can be easily and effectively closed and secured watertight, shall be provided for all side scuttles to spaces below the first deck above the bulkhead deck.

Regulation 17-1

---CHUNK---

SOURCE: MSC.194(80).pdf
5 Efficient inside deadlights, so arranged that they can be easily and effectively closed and secured watertight, shall be provided for all side scuttles to spaces below the first deck above the bulkhead deck.

Regulation 17-1
Integrity of the hull and superstructure, damage prevention and control on ro-ro passenger ships

1.1 Subject to the provisions of paragraphs 1.2 and 1.3, all accesses that lead to spaces below the bulkhead deck shall have a lowest point which is not less than 2.5 m above the bulkhead deck.

1.2 Where vehicle ramps are installed to give access to spaces below the bulkhead deck, their openings shall be ab le to be closed weathertight to prevent ingress of water below, alarmed and indicated to the navigation bridge.

1.3 The Administration may permit the fitting of particular accesses to spaces below the bulkhead deck provided they are necessary for the essential working of the ship, e.g. the movement of machinery and stores, subject to such accesses being made watertight, alarmed and indicated on the navigation bridge.

2 Indicators shall be provided on the navi gation bridge for all shell doors, loading

---CHUNK---

SOURCE: MSC.194(80).pdf
e.g. the movement of machinery and stores, subject to such accesses being made watertight, alarmed and indicated on the navigation bridge.

2 Indicators shall be provided on the navi gation bridge for all shell doors, loading doors and other closing appliances which, if left open or not properly secured, could, in the opinion of the Administration, lead to flooding of a special category space or ro-ro space. The indicator system shall be designed on the fail-safe principle and shall show by visual alarms if the door is not fully closed or if any of the securing arrangements are not in place and fully locked and by audible alarms if such door or closing appliances become open or the securing arrangements become unsecured. The indicator panel on the navigation bridge shall be equipped with a mode selection function “harbour/sea voyage” so arranged that an audible alarm is given on the navigation bridge if the ship leaves harbour with the bow doors, inner doors, ster n ramp or any other side shell doors not closed or any closing device not in the co rrect position. The power supply for the

---CHUNK---

SOURCE: MSC.194(80).pdf
harbour with the bow doors, inner doors, ster n ramp or any other side shell doors not closed or any closing device not in the co rrect position. The power supply for the indicator system shall be independent of th e power supply for operating and securing the doors.

3 Television surveillance and a water leakag e detection system shall be arranged to provide an indication to the navigation bridge and to the engine control station of any leakage through inner and outer bow doors, stern doors or any other shell doors which could lead to flooding of special category spaces or ro-ro spaces.

PART B-3
SUBDIVISION LOAD LINE ASSIGNMENT FOR PASSENGER SHIPS

Regulation 18
Assigning, marking and recording of subdivision load lines for passenger ships

1 In order that the required degree of s ubdivision shall be maintained, a load line corresponding to the approved subdivision draught shall be assigned and marked on the ship’s sides. A ship intended for alternat ing modes of operation may, if the owners desire, have one or more additional load lines assigned and marked to correspond with the

---CHUNK---

SOURCE: MSC.194(80).pdf
ship’s sides. A ship intended for alternat ing modes of operation may, if the owners desire, have one or more additional load lines assigned and marked to correspond with the subdivision draughts which the Administration may approve fo r the alternative service configurations. Each service configuration so approved shall comply with part B-1 of this chapter independently of the results obtained for other modes of operation.
RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED

2 The subdivision load lines a ssigned and marked shall be recorded in the Passenger Ship Safety Certificate, and shall be dist inguished by the notation P1 for the principal passenger service configuration, and P2, P3, et c., for the alternative configurations. The principal passenger configuration shall be taken as the mode of operation in which the required subdivision index R will have the highest value.

3 The freeboard corresponding to each of these load lines shall be measured at the same position and from the same deck line as the freeboards determined in accordance

---CHUNK---

SOURCE: MSC.194(80).pdf
required subdivision index R will have the highest value.

3 The freeboard corresponding to each of these load lines shall be measured at the same position and from the same deck line as the freeboards determined in accordance with the International Convention on Load Lines in force.

4 The freeboard corresponding to each approved subdivision load line and the service configuration, for which it is approved, shall be clearly indicated on the Passenger Ship Safety Certificate.

5 In no case shall any subdivision load lin e mark be placed a bove the deepest load line in salt water as determined by the strength of the ship or the International Convention on Load Lines in force.

6 Whatever may be the position of the subdivi sion load line marks, a ship shall in no case be loaded so as to submerge the load line mark appropriate to the season and locality as determined in accordance with the International Convention on Load Lines in force.

7 A ship shall in no case be so loaded that when it is in salt water the subdivision load line mark appropriate to the particular voyage and service configuration is submerged.

PART B-4
STABILITY MANAGEMENT

Regulation 19

---CHUNK---

SOURCE: MSC.194(80).pdf
7 A ship shall in no case be so loaded that when it is in salt water the subdivision load line mark appropriate to the particular voyage and service configuration is submerged.

PART B-4
STABILITY MANAGEMENT

Regulation 19
Damage control information

1 There shall be permanently exhibited, or readily available on the navigation

bridge, for the guidance of the officer in ch arge of the ship, plans showing clearly for each deck and hold the boundaries of the wate rtight compartments, the openings therein with the means of closure and position of any controls thereof, and the arrangements for the correction of any list due to flooding. In addition, booklets containing the aforementioned information shall be made available to the officers of the ship.

2 Watertight doors in passenger ships permitted to remain open during navigation shall be clearly indicated in the ship's stability information.

3 General precautions to be included shal l consist of a listing of equipment, conditions, and operational procedures, considered by the Administration to be necessary to maintain watertight integrity under normal ship operations.

---CHUNK---

SOURCE: MSC.194(80).pdf
3 General precautions to be included shal l consist of a listing of equipment, conditions, and operational procedures, considered by the Administration to be necessary to maintain watertight integrity under normal ship operations.

4 Specific precautions to be included shall consist of a listing of elements (i.e. closures, security of cargo, sounding of alarms, etc.) considered by the Administration to be vital to the survival of the ship, passengers and crew.

5 In case of ships to which damage stability requirements of part B-1 apply, damage