stability information shall provide the mast er a simple and easily understandable way of assessing the ship's survivability in all damage cases involving a compartment or group of compartments.
RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-

Regulation 20
Loading of passenger ships

1 On completion of loading of the ship and prior to its departure, the master shall determine the ship's trim and stability and also ascertain and record that the ship is in

---CHUNK---

SOURCE: MSC.194(80).pdf
Regulation 20
Loading of passenger ships

1 On completion of loading of the ship and prior to its departure, the master shall determine the ship's trim and stability and also ascertain and record that the ship is in compliance with stability criteria in relevant regulations. The determination of the ship's stability shall always be made by calculation. The Administration may accept the use of an electronic loading and stability computer or equivalent means for this purpose.

2 Water ballast should not in general be car ried in tanks intended for oil fuel. In ships in which it is not practicable to avoid putting water in oil fuel tanks, oily-water separating equipment to the satisfaction of th e Administration shall be fitted, or other alternative means, such as discharge to shor e facilities, acceptable to the Administration shall be provided for disposing of the oily-water ballast.

3 The provisions of this regulation are without prejudice to th e provisions of the International Convention for the Prevention of Pollution from Ships in force.

Regulation 21
Periodical operation and inspection of watertight doors, etc. in passenger ships

---CHUNK---

SOURCE: MSC.194(80).pdf
International Convention for the Prevention of Pollution from Ships in force.

Regulation 21
Periodical operation and inspection of watertight doors, etc. in passenger ships

1 Drills for the operating of watertight doors, sidescuttles, valves and closing mechanisms of scuppers, ash-chutes and rubbish -chutes shall take place weekly. In ships in which the voyage exceeds one week in duration a complete drill shall be held before leaving port, and others thereafter at least once a week during the voyage.

2 All watertight doors, both hinged and powe r-operated, in watertight bulkheads, in use at sea, shall be operated daily.

3 The watertight doors and all mechanisms and indicators conn ected therewith, all valves, the closing of which is necessary to make a compartment watertight, and all valves the operation of which is necessary for damage control cross connections shall be periodically inspected at sea at least once a week.

4 A record of all drills and inspections re quired by this regulation shall be entered in the log-book with an explicit record of any defects which may be disclosed.

Regulation 22
Prevention and control of water ingress, etc.

---CHUNK---

SOURCE: MSC.194(80).pdf
4 A record of all drills and inspections re quired by this regulation shall be entered in the log-book with an explicit record of any defects which may be disclosed.

Regulation 22
Prevention and control of water ingress, etc.

1 All watertight doors shall be kept closed during navi gation except that they may be opened during navigation as sp ecified in paragraphs 3 and 4. Watertight doors of a width of more than 1.2 m in machinery sp aces as permitted by regulation 13.10 may only be opened in the circumstances detailed in th at regulation. Any door which is opened in accordance with this paragraph shall be ready to be immediately closed.

2 Watertight doors located below the bulkhead deck having a maximum clear opening width of more than 1.2 m shall be kept closed when the ship is at sea, except for limited periods when absolutely necessary as determined by the Administration.

3 A watertight door may be opened duri ng navigation to permit the passage of passengers or crew, or when work in the im mediate vicinity of the door necessitates it being opened. The door must be immediatel y closed when transit through the door is

---CHUNK---

SOURCE: MSC.194(80).pdf
passengers or crew, or when work in the im mediate vicinity of the door necessitates it being opened. The door must be immediatel y closed when transit through the door is
complete or when the task which necessitated it being open is finished.
RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-

4 Certain watertight doors may be permitted to remain open during navigation only if considered absolutely necessary; that is, being open is determined essential to the safe and effective operation of the ship’s m achinery or to permit passengers normally unrestricted access throughout the passenger area. Such determination shall be made by the Administration only after careful consideration of the impact on ship operations and survivability. A watertight door permitted to re main thus open shall be clearly indicated in the ship’s stability information and shall always be ready to be immediately closed.

5 Portable plates on bulkheads shall always be in place before the ship leaves port, and shall not be removed during navigation except in case of urgent necessity at the

---CHUNK---

SOURCE: MSC.194(80).pdf
5 Portable plates on bulkheads shall always be in place before the ship leaves port, and shall not be removed during navigation except in case of urgent necessity at the discretion of the master. The necessary precautions shall be taken in replacing them to ensure that the joints are watertight. Power-operated sliding watertight doors permitted in machinery spaces in accordance with regulation 13.10 shall be closed before the ship leaves port and shall remain closed during navigation except in case of urgent necessity at the discretion of the master.

6 Watertight doors fitted in watertight bulkheads divi ding cargo between deck spaces in accordance with regulation 13.9.1 shall be closed before the voyage commences and shall be kept closed during navigation; the time of opening such doors in port and of closing them before the ship leaves port shall be entered in the log-book.

7 Gangway, cargo and fuelling ports fitted below the bulkhead deck shall be effectively closed and secured watertight befo re the ship leaves por t, and shall be kept closed during navigation.

8 The following doors, located above the bulkhead deck, sh all be closed and locked

---CHUNK---

SOURCE: MSC.194(80).pdf
effectively closed and secured watertight befo re the ship leaves por t, and shall be kept closed during navigation.

8 The following doors, located above the bulkhead deck, sh all be closed and locked before the ship proceeds on any voyage and shal l remain closed and locked until the ship is at its next berth:

.1 cargo loading doors in the shel l or the boundaries of enclosed superstructures;

.2 bow visors fitted in positions as indicated in paragraph 8.1;

.3 cargo loading doors in th e collision bulkhead; and

.4 ramps forming an alternative closur e to those defined in paragraphs 8.1 to 8.3 inclusive.

9 Provided that where a door cannot be opened or closed while the ship is at the berth such a door may be opened or left open while the ship appro aches or draws away from the berth, but only so far as may be n ecessary to enable the door to be immediately operated. In any case, the inner bow door must be kept closed.

10 Notwithstanding the requirements of para graphs 8.1 and 8.4, the Administration may authorize that particular doors can be op ened at the discretion of the master, if

---CHUNK---

SOURCE: MSC.194(80).pdf
operated. In any case, the inner bow door must be kept closed.

10 Notwithstanding the requirements of para graphs 8.1 and 8.4, the Administration may authorize that particular doors can be op ened at the discretion of the master, if necessary for the operation of the ship or the embarking and disembarking of passengers when the ship is at safe anchorage and provided that the safety of the ship is not impaired.

11 The master shall ensure that an effec tive system of supervision and reporting of the closing and opening of the doors referred to in paragraph 8 is implemented.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-45 -

12 The master shall ensure, before the ship proceeds on any voyage, that an entry in the log-book is made of the time of the last closing of the doors specified in paragraph 13 and the time of any opening of particular doors in accordance with paragraph 14.

13 Hinged doors, portable plates, sidescut tles, gangway, cargo and bunkering ports and other openings, which are required by th ese regulations to be kept closed during

---CHUNK---