SOURCE: MSC.194(80).pdf
13 Hinged doors, portable plates, sidescut tles, gangway, cargo and bunkering ports and other openings, which are required by th ese regulations to be kept closed during navigation, shall be closed before the ship leaves port. The time of closing and the time of opening (if permissible under these regulation s) shall be recorded in such log-book as may be prescribed by the Administration.

14 Where in a between-decks, the sills of a ny of the sidescuttles referred to in regulation 15.3.2 are below a line drawn parallel to the bulkhead deck at side and having its lowest point 1.4 m plus 2.5% of the breadth of the ship above the water when the ship departs from any port, all the sidescuttles in that between-decks shall be closed watertight and locked before the ship leaves port, a nd they shall not be ope ned before the ship arrives at the next port. In the application of this paragraph the appropriate allowance for fresh water may be made when applicable.

.1 The time of opening such sidescuttles in port and of closing and locking them before the ship leaves port sha ll be entered in such log-book as may be prescribed by the Administration.

---CHUNK---

SOURCE: MSC.194(80).pdf
fresh water may be made when applicable.

.1 The time of opening such sidescuttles in port and of closing and locking them before the ship leaves port sha ll be entered in such log-book as may be prescribed by the Administration.

.2 For any ship that has one or more sidescuttles so placed that the requirements of paragraph 14 would apply when it was floating at its deepest subdivision draught, the Admi nistration may indicate the limiting mean draught at which these sidescuttles will have their sills above the line drawn parallel to the bulkhead deck at side, and having its lowest point 1.4 m plus 2.5% of the breadt h of the ship above the waterline corresponding to the limiting mean draught, and at which it will therefore be permissible to depart from port w ithout previously closing and locking them and to open them at sea on the re sponsibility of the master during the voyage to the next port. In tropical zones as defi ned in the International Convention on Load Lines in force, this limiting draught may be increased by 0.3 m.

15 Sidescuttles and their deadlights which wi ll not be accessible during navigation

---CHUNK---

SOURCE: MSC.194(80).pdf
Convention on Load Lines in force, this limiting draught may be increased by 0.3 m.

15 Sidescuttles and their deadlights which wi ll not be accessible during navigation
shall be closed and secured before the ship leaves port.

16 If cargo is carried in spaces referred to in regulation 15.5.2, the sidescuttles and their deadlights shall be closed watertight and locked before the cargo is shipped and such

closing and locking shall be recorded in such log-book as may be prescribed by the Administration.

17 When a rubbish-chute, etc. is not in us e, both the cover and the valve required by regulation 15.10.2 shall be kept closed and secured.

Regulation 23
Special requirements for ro-ro passenger ships

1 Special category spaces and ro-ro spaces shall be continuously patrolled or monitored by effective means, such as televi sion surveillance, so that any movement of vehicles in adverse weather conditions and unauthorized access by passengers thereto can be detected whilst the ship is underway.

---CHUNK---

SOURCE: MSC.194(80).pdf
be detected whilst the ship is underway.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-
46 -

2 Documented operating procedures for clos ing and securing all shell doors, loading doors and other closing appliances which, if left open or not properly secured, could, in the opinion of the Administration, lead to flooding of a special category space or ro-ro space, shall be kept on board and posted at an appropriate place.

3 All accesses from the ro-ro deck and vehi cle ramps that lead to spaces below the bulkhead deck shall be closed before the ship leaves the berth on any voyage and shall remain closed until the ship is at its next berth.

4 The master shall ensure that an effec tive system of supervision and reporting of the closing and opening of such accesses referred to in paragraph 3 is implemented.

5 The master shall ensure, before the ship leaves the berth on any voyage, that an entry in the log-book, as requir ed by regulation 22. 13, is made of the time of the last closing of the accesses referred to in paragraph 3.

---CHUNK---

SOURCE: MSC.194(80).pdf
5 The master shall ensure, before the ship leaves the berth on any voyage, that an entry in the log-book, as requir ed by regulation 22. 13, is made of the time of the last closing of the accesses referred to in paragraph 3.

6 Notwithstanding the requirements of para graph 3, the Administration may permit some accesses to be opened during the voyage, but only for a period sufficient to permit

through passage and, if required, for the essential working of the ship.

7 All transverse or longitudinal bulkheads which are taken into account as effective to confine the seawater accumulated on the ro-ro deck shall be in place and secured before the ship leaves the berth and remain in place and secured until the ship is at its next berth.

8 Notwithstanding the requirements of para graph 7, the Administration may permit some accesses within such bulkheads to be opened during the voyage but only for sufficient time to permit through passage and, if required, for the essential working of the ship.

9 In all ro-ro passenger ships, the master or th e designated officer shall ensure that,

---CHUNK---

SOURCE: MSC.194(80).pdf
sufficient time to permit through passage and, if required, for the essential working of the ship.

9 In all ro-ro passenger ships, the master or th e designated officer shall ensure that, without the expressed consent of the master or the designated officer, no passengers are allowed access to an enclosed ro-ro deck when the ship is under way.

Regulation 24
Prevention and control of water ingress, etc. in cargo ships

1 Openings in the shell plati ng below the deck limiting the vertical extent of damage shall be kept permanently closed while at sea.

2 Notwithstanding the requirements of paragraph 3, the Administration may authorize that particular doors may be opened at the discretion of the master, if necessary for the operation of the ship and provided that the safety of the ship is not impaired.

3 Watertight doors or ramps fitted to internally subdivide large cargo spaces shall be closed before the voyage commences and shall be kept closed during navigation; the time of opening such doors in port and of closing them before th e ship leaves port shall be entered in the log-book.

---CHUNK---

SOURCE: MSC.194(80).pdf
closed before the voyage commences and shall be kept closed during navigation; the time of opening such doors in port and of closing them before th e ship leaves port shall be entered in the log-book.

4 The use of access doors and hatch covers intended to ensure the watertight integrity of internal openings shall be authorized by the officer of the watch.

RESOLUTION MSC.194(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED-

Regulation 25
Water level detectors on single hold cargo ships other than bulk carriers

1 Single hold cargo ships other than bulk carriers constructed before 1 January 2007 shall comply with the requirements of this regulation not later than 31 December 2009.

2 Ships having a length (L) of less than 80 m, or 100 m if constructed before 1 July 1998, and a single cargo hold below the freeboard deck or cargo holds below the freeboard deck which are not separated by at least one bulkhead made watertight up to that deck, shall be fitte d in such space or spaces with water level detectors.

3 The water level detectors re quired by paragraph 2 shall:

---CHUNK---

SOURCE: MSC.194(80).pdf
below the freeboard deck which are not separated by at least one bulkhead made watertight up to that deck, shall be fitte d in such space or spaces with water level detectors.

3 The water level detectors re quired by paragraph 2 shall:

.1 give an audible and visual alarm at the navigation bridge when the water level above the inner bottom in the cargo hold reaches a height of not less than 0.3 m, and another when such level reaches not more than 15%