within the cargo one transverse two transverse three transverse
area section sections (1) sections (1)
all wind and each bottom plate
water strakes all wind and
water strakes
Selected wind and Selected wind and Selected wind and
water strakes water strakes water strakes
outside the cargo outside the cargo outside the cargo

---CHUNK---

SOURCE: MSC.197(80).pdf
all wind and each bottom plate
water strakes all wind and
water strakes
Selected wind and Selected wind and Selected wind and
water strakes water strakes water strakes
outside the cargo outside the cargo outside the cargo
area area area
~easurements, for ~easurements, for ~easurements, for ~easurements , for
general assessment general assessment general assessment general assessment
and recording of and recording of and recording of and recording of
corrosion pattern, of corrosion pattern, of corrosion pattern, of corrosion pattern, of
those structura l those structural those structural those structural
members subject to members subject to members subject to members subject to
close-up survey close-up survey close-up survey close-up survey
according to according to according to according to
annex 1 annex I annex I annex I
Suspect areas Suspect areas Suspect areas Suspect areas
(1): at least one section should be within O.SL amidships.
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 47 -
ANNEX 3

---CHUNK---

SOURCE: MSC.197(80).pdf
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 47 -
ANNEX 3
MINIMUM REQUIREMENTS FOR TANK TESTING AT RENEWAL SURVEY
OF DOUBLE HULL OIL TANKERS
Age,::::5 years 5<age.:::::10 years Age> I 0 years
I 2 3
All ballast tank boundaries All ballast tank boundarie s All ballast tank boundaries
Cargo tank boundaries Cargo tank boundarie s Cargo tank boundaries
facing ballast tanks, void facing ballast tanks, void facing ballast tanks, void
spaces, pipe tunnels, spaces, pipe tunnels, spaces, pipe tunnels,

representative fuel oil representative fuel oil representative fuel oil
tanks , pump-rooms or tanks, pump-room s or tanks, pump-rooms or
cofferdams cofferdams cofferdams
All cargo tank bulkhead s All remaining cargo tank
which form the boundaries bulkhead s
of segregated cargoes
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 48-
ANNEX 4/Sheet 1

---CHUNK---

SOURCE: MSC.197(80).pdf
of segregated cargoes
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 48-
ANNEX 4/Sheet 1
REQUIREMENTS FOR EXTENT OF THICKNESS MEASUREMENTS AT
AREAS OF SUBSTANTIAL CORROSION
RENEWAL SURVEY OF DOUBLE HULL OIL TANKERS
BOTTOM, INNER BOTTOM AND HOPPER STRUCTURE
Structural member Extent of measurement Pattern of measurement
Bottom, inner bottom and Minimum of three bays across 5-point pattern for each panel
hopper structure plating double bottom tank, including between longitudinals and
aft bay Measurements around floors
and under all suction bell
mouths
Bottom, inner bottom and Minimum of three Three measurements in line
hopper structure longitudinals longitudinals in each bay across flange and three
where bottom plating measurements on vertical web
measured
Bottom girders, including the At fore and aft watertight Vertical line of single
watertight ones floors and in centre of tanks measurement s on girder
plating with one measurement
between each panel stiffener,
or a minimum of three
measurements

---CHUNK---

SOURCE: MSC.197(80).pdf
watertight ones floors and in centre of tanks measurement s on girder
plating with one measurement
between each panel stiffener,
or a minimum of three
measurements
Bottom floors, including the Three floors in bays where 5-point pattern over two
watertight ones bottom plating measured , with square metre area

measurements at both ends
and middle
Hopper structure web frame Three floors in bays where 5-point pattern over one
nng bottom plating measured square metre of plating.
Single measurements on
flange
Hopper structure transverse - lower 1/3 of bulkhead 5-point pattern over one
watertight bulkhead or swash square metre of plating
bulkhead
- upper 2/3 of bulkhead 5-point pattern over two
square metre of plating
- stiffeners (minimum of For web, 5-point pattern over
three) span (two measurements
across web at each end and
one at centre of span). For
flange, single measurements
at each end and centre of span
Panel stiffening Where applicable Single measurements
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS

---CHUNK---

SOURCE: MSC.197(80).pdf
at each end and centre of span
Panel stiffening Where applicable Single measurements
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 49-
ANNEX 4/Sheet 2
REQUIREMENTS FOR EXTENT OF THICKNESS MEASUREMENTS AT
AREAS OF SUBSTANTIAL CORROSION RENEWAL SURVEY OF DOUBLE
HULL OIL TANKERS WITHIN THE CARGO AREA LENGTH
DECK STRUCTURE
Structural member Extent of measurement Pattern of measurement
Deck plating Two transverse bands across Minimum of three
tank measurements per plate per
band
Deck longitudinals Every third longitudinal in Three measurements in line
each of two bands with a vertically on webs and two
minimum of one measurem ents on flange (if
longitudinal fitted)
Deck girders and brackets At fore and aft transverse Vertical line of single
(usually in cargo tanks only) bulkhead, bracket toes and in measurements on web plating
centre of tanks with one measurement
between each panel stiffener,
or a minimum of three
measurements.
Two measurements across
flange . 5-point pattern on

girderfbulkhead brackets

---CHUNK---

SOURCE: MSC.197(80).pdf
centre of tanks with one measurement
between each panel stiffener,
or a minimum of three
measurements.
Two measurements across
flange . 5-point pattern on
girderfbulkhead brackets
Deck transverse webs Minimum of two webs, with 5-point pattern over one
measurements at both ends square metre area.
and middle of span Single measurements on
flange
Vertical web and transverse Minimum of two webs, and 5-point pattern over one
bulkhead in wing ballast tank both transverse bulkheads square metre area
(two metres from deck)
Panel stiffening Where applicable Single measurements
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED