where thickness measurements should be taken in accordance with 2.5.1.
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 57-
10 Minimum thickness of hull structures
This section of the survey programme should specifY the minimum thickness for hull
structures of the ship that are subject to the Guidelines (indicate either (a) or
preferably (b), if such information is available):
(a) o Determined from the attached wastage allowance table and the original
thickness to the hull structure plans of the ship;
(b) o Given in the following table(s):
Original as- Minimum Substantial corrosion Area or location built thickness thickness thickness (mm) (mm) (mm)
Deck
Plating
Longitudinals
Longitudinal girders
Bottom
Plating
Longitudinals
Longitudinal girders
Ship side
Plating
Longitudinals
Longitudinal girders
Longitudinal bulkhead
Plating
Longitudinals
Longitudinal girders
Inner bottom
Plating
Longitudinals
Longitudinal girders
Transverse bulkheads
Plating
Stiffeners
Transverse web frames, floors

---CHUNK---

SOURCE: MSC.197(80).pdf
Plating
Longitudinals
Longitudinal girders
Longitudinal bulkhead
Plating
Longitudinals
Longitudinal girders
Inner bottom
Plating
Longitudinals
Longitudinal girders
Transverse bulkheads

Plating
Stiffeners
Transverse web frames, floors
and stringers
Plating
Flanges
Stiffeners
Cross ties
Flanges
Webs
Note: The wastage allowance tables should be attached to the survey programme.

11 Thickness measurement company
This section of the survey programme should identifY changes, if any, relating to the information on the thickness measurement company provided in the Survey Planning Questionnaire.
12 Damage experience related to the ship
This section of the survey programme should, using the tables provided below, provide details of the hull damages for at least the last three years in way of the cargo and ballast tanks and void spaces within the cargo area. These damages are subject to survey.
Hull damages sorted by location for the ship

---CHUNK---

SOURCE: MSC.197(80).pdf
details of the hull damages for at least the last three years in way of the cargo and ballast tanks and void spaces within the cargo area. These damages are subject to survey.
Hull damages sorted by location for the ship
Tank or Possible Description space of Location Repair Date of number or cause, repair if known the damages area
Hull damages for sister or similar ships (if available) in the case of
design related damage
Tank or Possible Description space of Location Repair Date of number or cause, repair if known the damages area

13 Areas identified with substantial corrosion from previous surveys
This section of the survey programme should identify and list the areas of substantial corrosion from previous surveys.
14 Critical structural areas and suspect areas
This section of the survey programme should identify and list the critical structural areas and the suspect areas, if such information is available.
15 Other relevant comments and information

---CHUNK---

SOURCE: MSC.197(80).pdf
14 Critical structural areas and suspect areas
This section of the survey programme should identify and list the critical structural areas

and the suspect areas, if such information is available.
15 Other relevant comments and information
This section of the survey programme should provide any other comments and information relevant to the survey.
Appendices
Appendix 1 - List of plans
5.1.3.2 requires that main structural plans of cargo and ballast tanks (scantling drawings), including information on regarding use of high tensile steel (HTS), to be available. This appendix of the survey programme should identify and list the main structural plans which form part of the survey programme.
Appendix 2 - Survey Planning Questionnaire
The Survey Planning Questionnaire (annex 6B), which has been submitted by the owner, should be appended to the survey programme.
Appendix 3 - Other documentation
This part of the survey programme should identify and list any other documentation that forms part of the Plan.
Prepared by the owner in co-operation with the Administration for compliance with 5.1.3.
Date: ..... ".
Date: ... ,," " .. " .....

---CHUNK---

SOURCE: MSC.197(80).pdf
forms part of the Plan.
Prepared by the owner in co-operation with the Administration for compliance with 5.1.3.
Date: ..... ".
Date: ... ,," " .. " .....
(name and signature of authorized owner's representative)
(name and signature of authorized representative of the Administration)
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 60-
ANNEX6B
SURVEY PLANNING QUESTIONNAIRE
The following information will enable the owner in co-operation with the Administration to develop a survey programme complying with the requirements of the Guidelines . It is essential that the owner provides , when completing the present questionnaire , up-to-date information. The present questionnaire, when completed, should provide all information and material required by the resolution.
Particulars
Ship's name:
IMO number:
Flag State:
Port of registry:
Owner:
Recognized organization (RO):
Gross tonnage:
Deadweight (metric tonnes):
Date of delivery:

---CHUNK---

SOURCE: MSC.197(80).pdf
and material required by the resolution.
Particulars
Ship's name:
IMO number:
Flag State:
Port of registry:
Owner:
Recognized organization (RO):
Gross tonnage:
Deadweight (metric tonnes):
Date of delivery:
Information on access provision for close-up surveys and thickness measurement:
The owner should indicate, in the table below, the means of access to the structures subject to close-up survey and thickness measurement. A close-up survey is an examination where the details of structural components are within the close visual inspection range of the attending surveyor, i.e. preferably within reach of hand.
Ta nk Structure C (Cargo) / Temporary Rafts Ladders Direct Other
No. B (Ballast) staging access means
(please
specify)
F.P. Fore peak