PLATE
POSITIO N
II '" for
10'"
9
t
"
8'"
7'"
6
th
5'"
4th
3'"
2""
I "
Amid ships
1 sl aft
2""
3'"
4th
5'"
6'"
7"
8'"
9'"
10
th
II '"
- 77-
APPENDIX 2
TMI-DHT Report on thickness measurement of aD deck plating, aD bottom sheD plating or side sheD plating'
Ship's name .. _____ . __ .__ _____ Class identity No. ____ ____ ____ _____ _____ _

---CHUNK---

SOURCE: MSC.197(80).pdf
TMI-DHT Report on thickness measurement of aD deck plating, aD bottom sheD plating or side sheD plating'
Ship's name .. _____ . __ .__ _____ Class identity No. ____ ____ ____ _____ _____ _
Report No .. __ _____ _ . __ . _____ . __ . _____ _
No. Original Forward reading Aft readin
or thickness Gauged Diminution Diminution Gauged Diminution Diminution %
letter {mm} P S P S
P S mIll % mm % P S mm % mm % P S
mm
Operator's signature __ ____ __ _____ ___ ._____ ____ ___ Surveyor's signature _____ _ . ___ _____ . ___ _____ _
NOTES - See reverse
Delete as appropriate .
RESOLUTION MSC.197(80)

(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 78-
NOTES TO THE REPORT TMI-DHT:
This report should be used for recording the thickness measurement of:
.1 All strength deck plating within the cargo area .
. 2 All keel, bottom shell plating and bilge plating within the cargo area .

---CHUNK---

SOURCE: MSC.197(80).pdf
NOTES TO THE REPORT TMI-DHT:
This report should be used for recording the thickness measurement of:
.1 All strength deck plating within the cargo area .
. 2 All keel, bottom shell plating and bilge plating within the cargo area .
. 3 Side shell plating, including selected wind and water strakes outside cargo
area .
.4 All wind and water strakes within cargo area.
2 The strake position should be clearly indicated as follows:
.1 For strength deck indicate the number of the strake of plating inboard from
the stringer plate .
.2 For bottom plating indicate the number of the strake of plating outboard
from the keel plate .
. 3 For side shell plating give number of the strake of plating below
sheerstrake and letter as shown on shell expansion.
3 Measurements should be taken at the forward and aft areas of all and where plates
cross ballast/cargo tank boundaries separate measurements for the area of plating
in way of each type of tank should be recorded.
4 The single measurements recorded are to represent the average of multiple
measurements.
4 The maximum allowable diminution could be stated in an attached document.
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)

---CHUNK---

SOURCE: MSC.197(80).pdf
4 The single measurements recorded are to represent the average of multiple
measurements.
4 The maximum allowable diminution could be stated in an attached document.
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED))
- 79-
TM2- DHT (i) Report on thickness measurement of shell and deck plating (one, two or three transverse sections)
Ship's name .... Class identity No. ....
Report No ....
STRENGTH DECK AND SHEERSTRAKE PLATING
FIRST TRANSVERSE SECTION AT FRAME NUMBER SECOND TRANSVERSE SECTtON AT FRAME NUMBER THIRD TRANSVERSE SECTION AT FRAME NUMBER
STRAKE No. Original Maximum Gauged Diminution Diminution No. Original Maximum Gauged Diminution Diminution

No. or Original Maximum Gauged Diminution Diminution
POStTtON or tltickre;.o; allowable P S or thickness allowable P S Letter thickness allowable P S

---CHUNK---

SOURCE: MSC.197(80).pdf
POStTtON or tltickre;.o; allowable P S or thickness allowable P S Letter thickness allowable P S
Letter diminution r..tter diminution diminution
mm mm P S mm % mm % mm mm P S mm % S % mm mm P S mm % mm %
Stringer
Plate
1st stra ke
inboard
2"
3
4
5
6
7
8
9
10
lHh
12"
13"
14"
Centre srrake
Sheer strake
TOPSIDE
TOTAL
Operator's Signature ..... , ... , .. Surveyor's Signature .... NOTES - See reverse
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)- 80-
NOTES TO THE REPORT TM2-DHT (i)
I This report form should be used for recording the thickness measurements of
strength deck plating and sheerstrake plating transverse sections:
One, two or three sections within the cargo area comprising of the structural items
(0), (I) and (2) as shown on the diagrams of typical transverse sections illustrated
in appendix 3 of annex 10.
2 The topside area comprises deck plating, stringer plate and sheerstrake (including
rounded gunwales).

---CHUNK---

SOURCE: MSC.197(80).pdf
(0), (I) and (2) as shown on the diagrams of typical transverse sections illustrated
in appendix 3 of annex 10.
2 The topside area comprises deck plating, stringer plate and sheerstrake (including
rounded gunwales).
3 The exact frame station of measurement should be stated.
4 The single measurements recorded are to represent the average of multiple

measurements.
5 The maximum allowable diminution could be stated in an attached document.
RESOLUTION MSC.197(80)
(adopted on 20 May 2005)
AMENDMENTS TO THE GUIDELINES ON THE ENHANCED
PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS
AND OIL TANKERS (RESOLUTION A.744(18), AS AMENDED)))
- 81 -
TM2--DHT (ii) Report on thickness measurement of shell and deck plating (one, two or three transverse sections)
Ship's name .... Class identity No. ..... Report No ....
SHELL PLATING
FIRST TRANSVERSE SECTION AT FRAME NUMBER SECOND TRANSVERSE SECTION AT FRAME NUMBER THIRD TRANSVERSE SECTION AT FRAME NUMBER

---CHUNK---

SOURCE: MSC.197(80).pdf
SHELL PLATING
FIRST TRANSVERSE SECTION AT FRAME NUMBER SECOND TRANSVERSE SECTION AT FRAME NUMBER THIRD TRANSVERSE SECTION AT FRAME NUMBER
STRAKE No. Origiool Maximum Gauged Diminution Diminution No. Original Maximum Gauged Diminution Diminution No. or Original Maximum Gauged Diminution Diminution
POSmON or .hid",,,,, allowable P S or thickness allowable P S Letter thickness allowable P S
Le"", diminution Letter diminution diminution
mm mm P S mm % mm % mm mm P S mm % S % mm mm P S mm % mm %
lsrbelow
sheer strake
2
3'
4
5
6