SOURCE: MSC.200(80).pdf
resolution;

2. RECOMMENDS Governments to apply th e annexed amendments when testing life-saving appliances.

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 2

I:\MSC\80\24-ADD-1.DOC

ANNEX

AMENDMENTS TO
THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES
(RESOLUTION MSC.81(70))

PART 1 – Prototype tests for life-saving appliances

1 The existing subparagraph .3 of para graph 1.1 is replaced by the following:

".3 if it is intended to operate the qui ck-release arrangement provided for a self-activated smoke signal and self-igniting light, the lifebuoy has a mass of not less than 4 kg (see 1.8); and"

2 In paragraph 1.2.1.1, the words "8 h cycle at +65°C" are replaced by "8 h exposure at a minimum temperature of +65°C".

3 In paragraphs 1.2.1.2 and 1.2.1.4, the words "at a temperature of 20°C 3°C" are added after the words "under ordinary room conditions".

4 In paragraph 1.2.1.3, the words "8 h cycle at -30°C" are replaced by the words "8 h exposure at a maximum temperature of -30°C".

---CHUNK---

SOURCE: MSC.200(80).pdf
after the words "under ordinary room conditions".

4 In paragraph 1.2.1.3, the words "8 h cycle at -30°C" are replaced by the words "8 h exposure at a maximum temperature of -30°C".

5 The existing paragraph 1.9.3 is replaced by the following:

"1.9.3 The last three smoke signals taken from ordinary room conditions and attached by a line to a lifebuoy having a mass of not more than 4 kg should undergo the drop test into water prescribed in 1.3. The lifebuoy s hould have both a smoke signal and a lifebuoy

light attached in the manner recommended by the manufacturers and be dropped from a quick-release fitting. The smoke signals should not be damaged and should function for a period of at least 15 min."

6 The following new paragraph 1.9.6 is added:

"1.9.6 A force of 225 N should be applied to the fitting that attaches the self-activating smoke signal to the lifebuoy. Neither the fitting nor the signal should be damaged as a result of the test."

7 The existing section 2 is replaced by the following:

"2 LIFEJACKETS

2.1 Temperature cycling test

A lifejacket should be subjected to the temper ature cycling as prescribed in 1.2.1 and

---CHUNK---

SOURCE: MSC.200(80).pdf
result of the test."

7 The existing section 2 is replaced by the following:

"2 LIFEJACKETS

2.1 Temperature cycling test

A lifejacket should be subjected to the temper ature cycling as prescribed in 1.2.1 and should then be externally examined. The lifejacket materials should show no sign of damage such as shrinking, cracking, swelling, dissolution or change of mechanical qualities.

2.2 Buoyancy test

The buoyancy of the lifejacket should be measured before and after 24 h complete submersion to just below the surface in fresh water. The difference between the initial buoyancy and the final buoyancy should not exceed 5% of the initial buoyancy.

2.3 Fire test

A lifejacket should be subjected to the fire te st prescribed in 1.5. The lifejacket should not sustain burning for more than 6 s or c ontinue melting after being removed from the flames.

2.4 Tests of components other than buoyancy materials

---CHUNK---

SOURCE: MSC.200(80).pdf
not sustain burning for more than 6 s or c ontinue melting after being removed from the flames.

2.4 Tests of components other than buoyancy materials

All the materials, other than buoyancy materials, used in the construction of the lifejacket, including the cover, ta pes, seams and closures should be tested to an international standard acceptable to the Organization to establish that they are rot-proof, colour-fast and resistant to deterioratio n from exposure to sunlight and that they are not unduly affected by seawater, oil or fungal attack.

2.5 Strength tests

Body or lifting loop strength tests

2.5.1 The lifejacket should be immersed in water for a period of 2 min. It should then be removed from the water and closed in the same manner as when it is worn by a person. A force of not less than 3,200 N (2,400 N in th e case of a child or in fant-size lifejacket) should be applied for 30 min to the part of th e lifejacket that secures it to the body of the wearer (see figure 1) and separa tely to the lifting loop of the lifejacket. The lifejacket should not be damaged as a result of this test. The test should be repeated for each encircling closure.

---CHUNK---

SOURCE: MSC.200(80).pdf
wearer (see figure 1) and separa tely to the lifting loop of the lifejacket. The lifejacket should not be damaged as a result of this test. The test should be repeated for each encircling closure.

Shoulder lift test

2.5.2 The lifejacket should be immersed in wate r for a period of 2 min. It should then be removed from the water and closed on a form as shown in figure 2, in the same manner as when it is worn by a person. A force of not less than 900 N (700 N in the case of a child- or infant-size lifej acket) should be applied for 30 min across the form and the shoulder section of the lifejacket (see figure 3). The lifejacket should not be damaged as a result of this test. The lifejacket should remain secured on the form during this test.

Refer to the recommendations of the International Organization for Standardization, in particular publication ISO 12402-7 Personal flotation devices – Part 7: Materials and components – Safety requirements and test methods.

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF

---CHUNK---

SOURCE: MSC.200(80).pdf
Safety requirements and test methods.

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17