the water, the test subject should hold on to the lifejacket during water entry to avoid possible injury. Upon entering the water, the te st subject should relax to simulate a state

---CHUNK---

SOURCE: MSC.200(80).pdf
ANNEX 17
Page 12

I:\MSC\80\24-ADD-1.DOC
the water, the test subject should hold on to the lifejacket during water entry to avoid possible injury. Upon entering the water, the te st subject should relax to simulate a state of utter exhaustion. The freeboard to the m outh should be recorded after the test subject comes to rest. The lifejacket and its att achments should be examined for any damage. If injury is believed likely from any jump or dr op test the lifejacket should be rejected or the test delayed until tests from a lower hei ght or with additional precautions demonstrate that the risk from the required test is acceptable.

Assessment

2.8.9 Following the drop test, the lifejacket should:

.1 surface the test subject in a face up position with an average freeboard for all the subjects of not less than the average for the RTD determined in accordance with 2.8.6;

.2 not be dislodged or cause harm to the test subject;

.3 have no damage that would affect its in-water performance or buoyancy; and

.4 have no damage to its attachments.

Stability test

2.8.10 The test subject should attain a relaxe d face-up position of static balance in the

---CHUNK---

SOURCE: MSC.200(80).pdf
.3 have no damage that would affect its in-water performance or buoyancy; and

.4 have no damage to its attachments.

Stability test

2.8.10 The test subject should attain a relaxe d face-up position of static balance in the water. The subject should be instructed to assume a foetal position as follows: “place your elbows against your sides, your hands on your stomach, under the lifejacket if possible, and bring your knees up as close to your chest as possible.” The subject should be rotated clockwise around the longitudinal ax is of the torso by grasping the subject’s

shoulders or upper areas of the li fejacket so that the subject at tains a 55 5 degree list. The subject should then be released. The s ubject should return to a stable face-up position. The test should then be conducted with the subject rotated counter-clockwise. The entire test should then be repeated with the test subject wearing the RTD. The candidate lifejacket should not roll any subj ect face down in the wa ter. The number of subjects who are returned to the stable face- up foetal position in th e candidate lifejacket

---CHUNK---

SOURCE: MSC.200(80).pdf
candidate lifejacket should not roll any subj ect face down in the wa ter. The number of subjects who are returned to the stable face- up foetal position in th e candidate lifejacket should be at least equal to the number who are returned to the stable face-up foetal position in the RTD.

Swimming and water emergence test

2.8.11 All test subjects, withou t wearing the lifejacket, s hould attempt to swim 25 m and board a liferaft or a rigid platform with its surface 300 mm above the water surface. All test subjects who successfu lly complete this task shoul d perform it again wearing the lifejacket. At least two thirds of the test subjects who can accomplish the task without the lifejacket should also be able to perform it with the lifejacket.

2.9 Infant and children’s lifejacket tests

As far as possible, similar tests should be ap plied for approval of lifejackets suitable for infants and children.

Infant and child test subjects

---CHUNK---

SOURCE: MSC.200(80).pdf
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 13

I:\MSC\80\24-ADD-1.DOC
Infant and child test subjects

2.9.1 For child-size lifejackets, tests should be carried out with at least 9 able-bodied persons, and for infant-size lifejackets, te sts should be carried out with at least

5 able-bodied persons. All test subjects should be selected according to table 2.2 or table 2.3 as follows:

.1 One subject should be selected per each cell containing a “1”.

.2 Remaining subjects should be selected from cells containing an “X”, without repeating a cell.

.3 At least 40% of the subjects should be male and at least 40% female.

.4 Devices for infants should be tested on infants as small as 6 kg mass.

.5 A manikin or manikins may be substitute d for infant lifejacket test subjects if the manikin or manikins have been demonstrated to provide representative results compared to human subjects.

Table 2.2 Selection of child test subjects

Weight range (kg) Height
range

---CHUNK---

SOURCE: MSC.200(80).pdf
if the manikin or manikins have been demonstrated to provide
representative results compared to human subjects.

Table 2.2 Selection of child test subjects

Weight range (kg) Height
range
(cm) 14-17 17-20 20-22 22-25 25-28 28-30 30-33 33-36 36-38 38-41 41-43
79-105 1 X
90-118 X 1
102-130 1 X
112-135 X 1
122-150 1 1 X
145-165 X 1 1

Table 2.3 Selection of infant test subjects

Weight range (kg) Height range
(cm) Less than 11 11-14 14-17
Less than 83 1 X
79-105 X 1 1
90-118 X

2.9.2 When conducting water performance tests under 2.8, infant and child-size lifejackets should meet the following requirement s for their critical flotation stability characteristics:

.1 Turning time: The average turn time for all subjects in the candidate lifejacket should not exceed the average time in the appropriate size RTD;

.2 Freeboard: The average results for clea rance of the mouth above the

---CHUNK---

SOURCE: MSC.200(80).pdf
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 14

I:\MSC\80\24-ADD-1.DOC