SOURCE: MSC.200(80).pdf
2.10.4.7.4 After completing the above test, the lifejacket should be removed from the manikin and immersed in water to verify that the auto-inflation system functions."
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 19

I:\MSC\80\24-ADD-1.DOC
8 The existing paragraph 3.1.1 is replaced by the following:

"3.1.1 These tests should be carried out with at least six able-bodied persons of the following heights and weights:

Height Weight

1.4 m - 1.6 m 1 person under 60 kg
1 person over 60 kg

1.6 m - 1.8 m 1 person under 70 kg
1 person over 70 kg

over 1.8 m 1 person under 80 kg
1 person over 80 kg

At least one and not more than two of the persons should be females with not more than one female in the same height range."

9 In paragraph 3.1.5, the word "shall " is replaced by the word "should".

10 At the end of paragraph 3.1.7, the senten ce "The position of the lifejacket light should permit it to be visible over as great a segment of the uppe r hemisphere as is practicable." is added.

---CHUNK---

SOURCE: MSC.200(80).pdf
10 At the end of paragraph 3.1.7, the senten ce "The position of the lifejacket light should permit it to be visible over as great a segment of the uppe r hemisphere as is practicable." is added.

11 In paragraph 3.1.10, the words "and its attachments" are inserted between the words "anti-exposure suit" and "should not be damaged".

12 In paragraph 3.1.15, the words "for more than 6 s" are inserted between "sustain burning" and "or continue melting".

13 At the end of paragraph 10.4.9, the note is deleted.

14 At the end of paragraph 10.4.9, th e following new paragraph is added:

“Flashing lights with a flash duration of not less than 0.3 s may be considered as fixed/steady lights for the measurement of their luminous intensity. Such lights should provide the required luminous intensity in al l directions of the upper hemisphere. The time interval between switching on and reaching the required luminous intensity (incandescence time) and all time spent below the required luminous intensity when the light switches off should be disregarded (see figure 10.4.1.)

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED

---CHUNK---

SOURCE: MSC.200(80).pdf
(incandescence time) and all time spent below the required luminous intensity when the light switches off should be disregarded (see figure 10.4.1.)

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 20

I:\MSC\80\24-ADD-1.DOC

Figure 10.4.1 – “On-time” measurement diagram”

PART 2 – Production and installation tests

15 In paragraph 2.2, the word “shall” is replaced by the word “should”.

16 The words “, using a dummy smoke signal, if necessary” are inserted between the words “should be” and “to demonstrate” in paragraph 3.1. In the same paragraph, the word “will” is inserted between the words “their attachments” and “drop clear”.

17 The following new appendices 1 to 3 are added after part 2:

“APPENDIX 1

ADULT REFERENCE TEST DEVICE (RTD)
DESIGN AND CONSTRUCTION

1 General. The RTD is intended for use only as a test reference standard to represent the desired level of in-water performance of a lifejacket required by the 1974 SOLAS Convention, and is not considered re presentative of any other required lifejacket

---CHUNK---

SOURCE: MSC.200(80).pdf
represent the desired level of in-water performance of a lifejacket required by the 1974 SOLAS Convention, and is not considered re presentative of any other required lifejacket performance. The adult RTD is designed to fit persons from a chest size of 700 mm to 1,350 mm and to be comfortable to wear as a non-reversible device such that it would be obvious to the wearer as to which is the in side and outside of the device, even under reduced lighting conditions. The adult RTD is made with two types of buoyant foam in a vest style using a heavy nyl on cover fabric shell secure d to the body with 25 mm webbing, closures and adjustments. The shell is made with slide fasteners (zippers) in place of closing seams to hold the foam within, in order that the foam inserts can be easily removed to check their buoyancy and renew or supplement them if they are out of tolerance. Hook and loop fasteners are used on the interior foam retainers to position and prevent shifting of the foam panels.

2 Materials. All materials used should comply with ISO 12402-7.

2.1 Foam requirements. The performance of the RTD is dependent on using plastic

---CHUNK---

SOURCE: MSC.200(80).pdf
prevent shifting of the foam panels.

2 Materials. All materials used should comply with ISO 12402-7.

2.1 Foam requirements. The performance of the RTD is dependent on using plastic
foam of the proper stiffness, shape and buoyancy.
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 21

I:\MSC\80\24-ADD-1.DOC

2.1.1 Stiffness. Two different stiffness foams are used: one is a soft foam and the other is a stiff foam. A bridge de flection test is provided to determine acceptability for the intended application. Figure A.1 provides th e setup details and table A.1 provides the specific measured values. For selecting the type of foam for the specific insert, see tables A.2 and A.3. To measure the centre deflection of a foam pa nel of the specified cross-section (a × b) and 110 mm wide, place the foam panel centred across the two equal height, parallel horizontal surfaces separated by the specified distance (c), and then load with a mass of the specified width. Note the length of the load should be at least 110 mm,

---CHUNK---

SOURCE: MSC.200(80).pdf
height, parallel horizontal surfaces separated by the specified distance (c), and then load with a mass of the specified width. Note the length of the load should be at least 110 mm, such that when placed on the foam panel it will extend the full width of the foam panel. It is acceptable for the load to extend beyond th e width of the foam panel provided that it is centred over the panel with equal amounts extending over the sides of the foam panel.

Measure the deflection at the bottom centre location of the fo am panel 30 s after placing the load on the panel.

2.1.2 Shape. The shape of each foam insert is specified in figures A.8 to A.11. For dimensions see tables A.2 and A.4.

2.1.3 Buoyancy. The total design buoyancy of the device is 155,6 N. Table A.3 specifies the foam characteristics, the buoyancy for each insert and its tolerances and the overall buoyancy distribution to be verified when using the RTD for certification testing.

2.2 Other component requirements. See table A.2.

3 Construction. The construction and assembly of the device should be in accordance with tables A.2 to A.4 and figures A.2 to A.14. A tolerance of ± 6 mm is used

---CHUNK---

SOURCE: MSC.200(80).pdf
2.2 Other component requirements. See table A.2.

3 Construction. The construction and assembly of the device should be in accordance with tables A.2 to A.4 and figures A.2 to A.14. A tolerance of ± 6 mm is used throughout for fabric cutting and stitching assembly. A tolerance of ± 6 mm is also used