for foam cutting, however, the buoyancy requirements of table A.3 should be met.

3.1 Seams. The seam allowances are 13 mm, unless otherwise specified. All structural seams use a lock type stitch so th at the seam will not unravel when a force is applied in the direction of the seam on any of the threads forming the stitch. Stitching should have a density of 7 to 12 stitches pe r 25 mm of stitch length. The box-x stitching on the webbing is 15 mm × 18 mm, unless otherwise specified. The bar-tack stitching on the webbing is 15 mm × 2 mm.

3.1.1 On the closing seam of the back section of the outer and inside cover, the cut ends of the fabric are turned under and stitched so th at the fabric will not ravel. The cut ends of webbing should be heat-sealed.

3.1.2 Tabs on the ends of the waist belt are formed by turn ing under 40 mm of material

---CHUNK---

SOURCE: MSC.200(80).pdf
of the fabric are turned under and stitched so th at the fabric will not ravel. The cut ends of webbing should be heat-sealed.

3.1.2 Tabs on the ends of the waist belt are formed by turn ing under 40 mm of material
twice and stitching 19 mm from the end of the folds with box-x or bar tack stitching.

Key
1 Foam at initial setup
2 Centre load
3 Load
4 Foam bridge deflection after 30 seconds

Figure A.1 – Foam bridge deflection test

Table A.1 — Specifications for the foam bridge deflection test

Dimension shown in figure A.1	Load mass
Foam type	
a	
(Length)	
mm	
(Not shown)	
(Width)	
mm	
b	

(Thickness)
mm
c
(Span)
mm
d
(Load width)
mm
e
(Deflection)
mm
kg
Stiff 394 110 83 300 120 < 20 8,6
Soft 394 110 45 150 30 25 0,75

Table A.2 — Parts, quantity and assembly

Component Description Quantity See figure Construction notes
1 Cover fabric 420 denier nylon,
with ravel resistant
coating, orange

1.1 Front outer cover 1 A.2

---CHUNK---

SOURCE: MSC.200(80).pdf
Table A.2 — Parts, quantity and assembly

Component Description Quantity See figure Construction notes
1 Cover fabric 420 denier nylon,
with ravel resistant
coating, orange

1.1 Front outer cover 1 A.2
1.2 Back outer cover 1 A.2
1.3 Inside cover 1 A.3
1.4 Centre gusset 2 A.4

Component Description Quantity See figure Construction notes
1.5 Collar, outer and
inside cover
2 A.5
1.6 Fabric
reinforcement

4 A.6
A.14
Attach to inside of collar cover, as attachment 1, for reinforcement at webbing attachment (see figure A.14).
1.7 Interior fabric retainers for foam inserts 1
2 A.7
A.13
Attach to inside of front cover, as attachment 3, stitch to cover at each side to form a foam retainer for inside front foam insert components 2.2.1 and 2.2.2 (see figure A.13).
1.8 Interior fabric retainers for foam inserts 2
2 A.7
A.14
Attach hoop and loop fasteners to the ends and stitch at centre to the inside of front cover, as

---CHUNK---

SOURCE: MSC.200(80).pdf
inside front foam insert components 2.2.1 and 2.2.2 (see figure A.13).
1.8 Interior fabric retainers for foam inserts 2
2 A.7
A.14
Attach hoop and loop fasteners to the ends and stitch at centre to the inside of front cover, as
attachment 4, to form a foam retainer for front foam insert components 2.1.1 and 2.1.2 (see figure A.13).
2 Foam
2.1 Stiff See tables A.1 and A.3

2.1.1 Front foam insert,

right side
81 mm thick 1 A.8
2.1.2 Front foam insert,
left side
81 mm thick 1 A.8
2.1.3 Collar foam insert 56 mm thick 1 A.10
2.2 Soft See tables A.1 and
A.3

2.2.1 Inside front foam
insert, right side
46 mm thick 1 A.9
2.2.2 Inside front foam
insert, left side
46 mm thick 1 A.9
2.2.3 Back foam insert 32 mm thick 1 A.11
3 Webbing 25 mm,
polypropylene,
with easy
adjustment and no
significant slippage
when used with the
specified hardware.