3.1 Chest strap 127 mm, black 2 A.12 On left side of front cover, attach webbing with male buckle. On right side of front cover attach webbing with female buckle. The free ends of the chest strap are folded under the yellow
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)

---CHUNK---

SOURCE: MSC.200(80).pdf
attach webbing with male buckle. On right side of front cover attach webbing with female buckle. The free ends of the chest strap are folded under the yellow
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 24

I:\MSC\80\24-ADD-1.DOC
Component Description Quantity See figure Construction notes
webbing (collar attachment webbing), with reinforcing fabric (see figure A.6) on inside of cover fabric. A box-x stitch is used to attached the chest strap to the front cover.
3.2 Waist belt 152 mm, black 2 A.12 On left side attach waist belt with slide and buckle clip waist belt. On right side attach bottom belt with D-ring and slide.
3.3 Waist belt 1,867 mm, black 1 A.12
A.13
Form 40 mm tab on each end. Attach to back cover using three box-x stitches (after front and back covers are assembled).
3.4 Belt loop on front cover
76 mm, black 2 A.12 Attach webbing to front outer cover and form a belt loop (one on each side) by

two sets of double bar tack
stitches
3.5 Belt loop on inside
cover

---CHUNK---

SOURCE: MSC.200(80).pdf
are assembled).
3.4 Belt loop on front
cover
76 mm, black 2 A.12 Attach webbing to front
outer cover and form a belt
loop (one on each side) by
two sets of double bar tack
stitches
3.5 Belt loop on inside
cover
89 mm, black 2 A.13 Attach webbing to inside
cover and form a belt loop
(one on each side) by two
box-x stitches
3.6 Collar attachment 1,384 mm, yellow 1 A.14
A.6
A.12
Attach webbing to collar
and reinforcing fabric, in
two places using box-x
stitch
4 Hook and loop
fastener
50 mm × 70 mm,
black generic
2 A.13
A.7
Hook and loop fasteners are
attached to the ends of
interior fabric retainer for
foam insert
5 Thread Generic synthetic AR
6 Hardware
6.1 Buckle Male and female
25 mm, plastic,
890 N single-end
strength
1 Chest strap
6.2 Slide Adjuster 25 mm,
plastic, 1,600 N
single-end strength
2 Waist belt
6.3 Snap hook 25 mm, SS,
1,600 N single-end
strength
1 Waist belt

6.4 D-ring 25 mm, SS,
1,600 N single-end
strength
2 Waist belt
6.5 Zipper 280 mm, plastic
(zipper chain and
pulls)
1 A.14 Foam access for collar
cover
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED

---CHUNK---

SOURCE: MSC.200(80).pdf
6.4 D-ring 25 mm, SS,
1,600 N single-end
strength
2 Waist belt
6.5 Zipper 280 mm, plastic
(zipper chain and
pulls)
1 A.14 Foam access for collar
cover
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 25

I:\MSC\80\24-ADD-1.DOC
Component Description Quantity See figure Construction notes
6.6 Zipper 370 mm, plastic
(zipper chain and
pulls)
1 A.12 Foam access for back cover
6.7 Zipper 440 mm, plastic
(zipper chain and
pulls)
2 A.12
A.13
Foam access for front cover

Table A.3 — Foam insert specifications

Values in Newtons (N)
Front right Front left Inside front right Inside front left Back Collar
Foam typea Stiff Stiff Soft Soft Soft Stiff
Buoyancyb 34 ± 1.2 34 ± 1.2 17.5 ± 0.65 17.5 ± 0.65 18 ± 0.8 28 ± 1
a The buoyancy of most foams will change over time with the greatest change occurring in the first

several months after manufacture. The exact kind of foam selected with need to be evaluated to determine the amount of additional buoyancy needed at the time of manu facture to maintain the values specified.

---CHUNK---

SOURCE: MSC.200(80).pdf
several months after manufacture. The exact kind of foam selected with need to be evaluated to determine the amount of additional buoyancy needed at the time of manu facture to maintain the values specified.

b Buoyancy distribution: 69 % front ± 1.5 percentage points

Table A.4 – List of dimensions shown in figures A.2 to A.14

Dimensions in millimetres

Figure Letter	A.2	A.3	A.4	A.5	A.6,A.7	A.8	A.9	A.10	A.11	A.12	A.13	A.14
a	72	294	23	308	73	198	76	20	188	100	100	25
b	298	100	516	142	73	46	46	56	274	35	35	160
c	438	1,106	618	10	130	76	394	51	414	20	20	53
d	442	199	102	288	205	81	38	216	343	35	300	25