(1) Left and right front buoyancy need not be checked if distribution is within tolerance.

---CHUNK---

SOURCE: MSC.200(80).pdf
(1) Left and right front buoyancy need not be checked if distribution is within tolerance.
(2) If the temperature and pressure at the time of measurement is not at standard conditions, these values should be corrected to standard temperature and pressure.
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 36

I:\MSC\80\24-ADD-1.DOC

COLLAR INSERT BACK INSERT

FRONT INSERT INSIDE FRONT FOAM INSERT

Figure 1 – Adult RTD foam insert nomenclature

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 37

I:\MSC\80\24-ADD-1.DOC

Buoyancy (N) Length (mm) Height (mm)
0.9 84 146
1.3 126 137
1.8 172 126
2.2 222 114
3.1 394 76

Figure 2 – Adult RTD “make-up” foam insert sizes

RESOLUTION MSC.200(80)

---CHUNK---

SOURCE: MSC.200(80).pdf
ANNEX 17
Page 37

I:\MSC\80\24-ADD-1.DOC

Buoyancy (N) Length (mm) Height (mm)
0.9 84 146
1.3 126 137
1.8 172 126
2.2 222 114

3.1 394 76

Figure 2 – Adult RTD “make-up” foam insert sizes

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 38

I:\MSC\80\24-ADD-1.DOC
APPENDIX 2

CHILD REFERENCE TEST DEVICE (RTD)
DESIGN AND CONSTRUCTION

1 General. The RTD is intended for use only as a test reference standard to represent the desired level of in-water performance of a lifejacket required by the 1974 SOLAS Convention, and is not considered re presentative of any other required lifejacket performance. The child RTD is for persons weighing approximately 15 to 43 kg, or 100 to 155 cm in height. The devi ce is designed to fit persons wi th chest sizes from 50 cm to 70 cm. This RTD is made with layers of buoyant foam in a bib-style design using a heavy nylon shell cover fabric secured to the body with a waist belt with quick and

---CHUNK---

SOURCE: MSC.200(80).pdf
70 cm. This RTD is made with layers of buoyant foam in a bib-style design using a heavy nylon shell cover fabric secured to the body with a waist belt with quick and positive closure and adjustment, along with a chest strap at the neck for closure and adjustment. The shell is made with slide fa steners (zippers) in place of closing seams to hold the foam within, in order that the foam inserts can be easily removed to check their buoyancy and renew or supplement them if th ey are out of tolerance. The RTD is designed to be reasonably comfortable to wear as a non-reversible device.

2 Materials. All materials used should comply with ISO 12402-7.

2.1 Foam requirements. The performance of the RTD is dependent on using plastic foam of the proper stiffness, shape and buoyancy.

2.1.1 Stiffness. The buoyant inserts are made of layers of medium stiffness foam to create a flexible but firm buoyancy element.

2.1.2 Shape. The shape of each foam layer is identified in figures B.2 and B.3. Dimensions are in tables B.1, B.2 and B.3.

2.1.3 Buoyancy. The total design buoyancy of the de vice is 88 N. Table B.4 specifies

---CHUNK---

SOURCE: MSC.200(80).pdf
2.1.2 Shape. The shape of each foam layer is identified in figures B.2 and B.3. Dimensions are in tables B.1, B.2 and B.3.

2.1.3 Buoyancy. The total design buoyancy of the de vice is 88 N. Table B.4 specifies foam characteristics, the buoyancy for each in sert and its toleranc es, and the overall buoyancy distribution to be verified when using the RTD for certification testing.

2.2 Other component requirements. See table B.1.

3 Construction. The construction and assembly of the device should be in accordance with tables B.1 and B.5 and figur es B.1 through B.9. A tolerance of ± 6 mm is used throughout for fabric cutting and stitching a ssembly. A tolerance of ± 6 mm is also used for foam cutting, however, the buoyancy requirements of table A.3 should be met.