3.1 Seams. Seam allowances are 13 mm, unless othe rwise specified. All structural seams use a lock type stitch so that the seam will not unravel when a force is applied in the direction of the seam on any of the threads forming the stitch. Stitching should have a density of 7 to 12 stitches per 25 mm of stitch length. Box-x stitching on the webbing is

---CHUNK---

SOURCE: MSC.200(80).pdf
the direction of the seam on any of the threads forming the stitch. Stitching should have a density of 7 to 12 stitches per 25 mm of stitch length. Box-x stitching on the webbing is 30 x 15 mm for the waist belt and 15 x 13 mm for the belt loop and chest strap, unless otherwise specified. The bar-tack stitchi ng on webbing is 30 x 2 mm for the waist belt and 15 x 2 mm for the belt loop and chest strap.

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 39

I:\MSC\80\24-ADD-1.DOC
3.1.1 The fabric reinforcements for the waist belt, belt loop and chest strap should be attached to the inside surface of the outside cover before attaching any of these items. On the closing seam of the top and bottom secti ons of the outside and inside cover, the cut ends of the fabric is turned under and stitch ed when installing the zippers so that the fabric will not ravel and so that the folds are flush with the line where the zipper teeth mesh (zippers installed to be hidden by cover fabric when closed).

Table B.1 Parts, quantity and assembly

---CHUNK---

SOURCE: MSC.200(80).pdf
fabric will not ravel and so that the folds are flush with the line where the zipper teeth mesh (zippers installed to be hidden by cover fabric when closed).

Table B.1 Parts, quantity and assembly

Component Description Quantity See figure Construction notes
1 Cover fabric 420 denier nylon, with ravel resistant coating, orange B.1, B.4, and B.9

1.1 Outside cover

	1 B.1, B.4, and B.9		
1.2 Inside cover	1 B.1, B.4, and B.9		
1.3 Fabric reinforce-ment, chest strap)	2 B.5 and B.9	Attach one each to inside left and right outside covers for the chest strap. Use lock stitches on three sides each (see figure B.9 for locations).	
1.4 Fabric reinforce-ment, belt, and belt loop	2 B.5 and B.9	Attach to inside left and right outside covers for the waist belt and belt loop. Use lock stitches on three sides (see figure B.9 for location).	
2 Foam	7 mm thickness, polyethylene (PE) foam, except for one layer as needed to achieve required buoyancy	B.2 and B.3	Layers stacked per figures B.2 and B.3.
2.1 Front foam insert, left	13 layers	B.2	Trim corner of layers A and B only per figure B.2.
2.2 Front foam insert, right			

---CHUNK---

SOURCE: MSC.200(80).pdf

layer as needed to
achieve required
buoyancy

		B.2 and B.3	
		Layers stacked per figures B.2 and B.3.	
2.1 Front foam insert, left	13 layers	B.2	Trim corner of layers A and B only per figure B.2.
2.2 Front foam insert, right	13 layers	B.2	Trim corner of layers A and B only per figure B.2.
2.3 Back foam insert	11 layers	B.3	
3 Webbing	All cut ends heat-sealed.		
3.1 Waist belt webbing	38 mm, black, polypropylene, with easy adjustment and no significant slippage when used with the specified hardware.	1,285 mm cut length	B.1, B.8 and B.9
	On left side attach waist belt with fixed part of buckle. Tab on the end of belt formed by turning under 40 mm of material twice and stitching 19 mm from the end of the fold with a bar-tack stitch. For location see figure B.9.		
3.2 Belt loop webbing	19 mm, black, polypropylene.	80 mm cut length	B.1 and B.9
	Attach webbing to front outside cover with two sets of double bar tack stitches to form a belt loop. For location see figure B.9.		

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF

---CHUNK---

SOURCE: MSC.200(80).pdf
bar tack stitches to form a belt
loop. For location see
figure B.9.
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17

Component Description Quantity See
figure
Construction notes
3.3 Chest strap
webbing
19 mm, black,