polypropylene.
235 mm
and
80 mm
cut
length
B.1, B.7
and B.9
Attach webbing with female buckle to right outside cover. Attach webbing with male buckle to left outside cover. For location see figure B.9.
Tab formed 75 mm from the free end of the male section of chest strap by folding in “Z” pattern 30 mm apart and stitching 15 mm from the fold with a bar-tack stitch. See figure B.7.
4 Thread Generic synthetic AR
5 Hardware
5.1 Buckle 38 mm, plastic (male and female sections)
1 B.1 and
B.8
Used in waist belt assembly
5.2 Buckle 19 mm, plastic (male and female sections)
1 B.1 and
B.7
Used in chest strap assembly
5.3 Zipper 380 mm, plastic (zipper chain length)
1 B.1 and
B.9

5.4 Zipper 150 mm, plastic separating (zipper chain and box/pin length)
2 B.1 and

---CHUNK---

SOURCE: MSC.200(80).pdf
and female sections)
1 B.1 and
B.7
Used in chest strap assembly
5.3 Zipper 380 mm, plastic (zipper chain length)
1 B.1 and
B.9

5.4 Zipper 150 mm, plastic separating (zipper chain and box/pin length) 2 B.1 and B.9

Table B.2 – List of dimensions shown in figure B.2

Insert layer dimensions (mm) Dimension				
A	B	C	D	E
a	145	140	125	115	95
b	305	300	285	275	255
c	30	30	0	0	0
d	30	30	0	0	0

Table B.3 – List of dimensions shown in figure B.3

Insert layer dimensions (mm) Dimension				
A	B	C	D	E
a	343	335	325	315	305
b	140	133	120	108	95
c	9	5	3	0	-5*
R	46	50	52	55	55

*measured in direction opposite to that shown in figure.

Table B.4 – Foam insert specifications

Left front insert	Right front insert	Back insert
Density	29 ± 5 kg/m3	29 ± 5 kg/m3	29 ± 5 kg/m3
Compressive strength at 25% (ISO 3386-1)	35 ± 10 kPa	35 ± 10 kPa	35 ± 10 kPa
Buoyancy a, b	31.5 ± 1.2 N	31.5 ± 1.2 N	25 ± 1.2 N

---CHUNK---

SOURCE: MSC.200(80).pdf

Left front insert Right front insert Back insert
Density 29 ± 5 kg/m3 29 ± 5 kg/m3 29 ± 5 kg/m3

Compressive
strength at 25%
(ISO 3386-1)
35 ± 10 kPa 35 ± 10 kPa 35 ± 10 kPa
Buoyancy a, b 31.5 ± 1.2 N 31.5 ± 1.2 N 25 ± 1.2 N
a The buoyancy of most foams will change over time with the greatest change occurring in the first several months after manufacture. The exact kind of foam selected with need to be evaluated to determine the amount of additional b uoyancy needed at the time of manufacture to achieve the values specified.
b Buoyancy distribution: 71.5% front 1.5 percentage points

Table B.5 – List of dimensions shown in figures B.4 - B.9

Dimensions (mm)
Figure B.5
Dimension
Figure B.4
Key-1 Key-2
Figure B.6 Figure B.7 Figure B.8 Figure B.9
a 420 75 80 75 90 1,150 * 45
b 210 105 110 40 135
c 92 85
d 210 45
e 356 25
f 230 33
g 460 115
h 375 25
i 580 265
* With webbing assembly fully extended.

---CHUNK---

SOURCE: MSC.200(80).pdf
* With webbing assembly fully extended.
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 42

I:\MSC\80\24-ADD-1.DOC

Left Right

Outside (front) Inside

Key
1 Inside cover fabric
2 Outside cover fabric
3 Adjustable part of waist belt closure
4 Zippers for access to front righ t and left foam compartment
5 Waist belt
6 Fixed part of chest strap
7 Zipper for access to back foam compartment
8 Belt loop
9 Fixed part of waist belt closure
10 Lockstitch to provide foam compartment separation
11 Adjustable part of chest strap

Figure B.1 – General arrangement, right side out (outside and inside)

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED