Table C.1 – Parts, quantity and assembly

Component	Description	Quantity	See figure	Construction notes
1	Cover fabric	420 denier nylon, with ravel resistant coating, orange	C.1, C.4, and C.9	
1.1	Outside cover	1	C.1, C.4, and C.9	
1.2	Inside cover	1	C.1, C.4, & C.9	
1.3	Fabric reinforce-ment, chest strap	2	C.5 and C.9	Attach one each to inside left and right outside covers for the chest strap. Use lock stitches on three sides each (see figure C.9 for locations).

---CHUNK---

SOURCE: MSC.200(80).pdf

	cover	1	C.1, C.4, & C.9	
1.3	Fabric reinforce-ment, chest strap	2	C.5 and C.9	Attach one each to inside left and right outside covers for the chest strap. Use lock stitches on three sides each (see figure C.9 for locations).

1.4	Fabric reinforce-ment, belt			

and belt
loop
2 C.5 and
C.9
Attach to inside left and right
outside covers for the waist
belt and belt loop. Use lock
stitches on three sides (see
figure C.9 for location).
2 Foam 7 mm thickness,
polyethylene (PE) foam,
except for one layer as
needed to achieve
required buoyancy
C.2 and
C.3
Layers stacked per Figures
C.2 and C.3.
2.1 Front
foam
insert, left
15 layers C.2 Trim corners per figure C.2,
except outside layers B to G.
2.2 Front
foam
insert,
right
15 layers C.2 Trim corners per figure C.2,
except outside layers B to G.
2.3 Back
foam
insert
12 layers C.3
3 Webbing All cut ends heat-sealed.
3.1 Waist belt
webbing
38 mm, black,
polypropylene, with easy
adjustment and no
significant slippage when
used with the specified
hardware.
1,085 m
m cut
length
C.1, C.8
and C.9
On left side attach waist belt
with female buckle. Tab on

---CHUNK---

SOURCE: MSC.200(80).pdf
webbing

38 mm, black,
polypropylene, with easy
adjustment and no
significant slippage when
used with the specified
hardware.
1,085 m
m cut
length
C.1, C.8
and C.9
On left side attach waist belt
with female buckle. Tab on
the end of belt formed by
turning under 40 mm of
material twice and stitching
19 mm from the end of the
fold with a bar-tack stitch.
For location see figure C.9.

3.2 Belt loop
webbing
19 mm, black,
polypropylene.
80 mm
cut length
C.1, C.6,
and C.9
Attach webbing to front
outside cover with two sets
of double bar tack stitches to
form a belt loop. For
location see figure C.9.
3.3 Chest
strap
webbing
19 mm, black,
polypropylene.
235 mm
 and
80 mm
cut length
C.1, C.7
and C.9
Attach webbing with female
buckle to right outside cover.

Attach webbing with male buckle to left outside cover. For location see figure C.9. Tab formed 75 mm from the free end of the male section of chest strap by folding in

---CHUNK---

SOURCE: MSC.200(80).pdf and C.9
Attach webbing with female buckle to right outside cover. Attach webbing with male buckle to left outside cover. For location see figure C.9. Tab formed 75 mm from the free end of the male section of chest strap by folding in “Z” pattern 30 mm apart and stitching 15 mm from the fold with a bar-tack stitch. See figure C.7.