4 Thread Generic synthetic AR
5 Hardware
5.1 Buckle 38 mm, plastic (male and female sections)
1 C.1 and C.8
Used in waist belt assembly.
5.2 Buckle 19 mm, plastic (male and female sections)
1 C.1 and C.7
Used in chest strap assembly
5.3 Zipper 350 mm, plastic (zipper chain length)
1 C.1 and C.9
Installed to be hidden by cover fabric when closed.
5.4 Zipper 180 mm, plastic separating (zipper chain and box/pin length)
2 C.1 and C.9
Installed to be hidden by cover fabric when closed.

Table C.2 – List of dimensions shown in figure C.2

Insert layer dimensions (mm) Dimension
A B C D E F G
a 140 133 127 120 108 95 83
b 190 184 178 172 165 160 140
c 28 28 28 28 28

Table C.3 – List of dimensions shown in figure C.3

Insert layer dimensions (mm) Dimension
A B C D E
a 310 303 290 275 255

---CHUNK---

SOURCE: MSC.200(80).pdf
A B C D E F G
a 140 133 127 120 108 95 83
b 190 184 178 172 165 160 140
c 28 28 28 28 28

Table C.3 – List of dimensions shown in figure C.3

Insert layer dimensions (mm) Dimension

A B C D E
a 310 303 290 275 255
b 165 160 140 120 95
c 3 3 3 3 -3*
R 44 44 44 44 44
* measured in direction opposite to that shown in figure.

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 54

I:\MSC\80\24-ADD-1.DOC
Table C.4 Foam insert specifications

Left front insert Right front insert Back insert
Density 29 ± 5 kg/m3 29 ± 5 kg/m3 29 ± 5 kg/m3
Compressive
strength at 25% (ISO
3386-1)
35 ± 10 kPa 35 ± 10 kPa 35 ± 10 kPa
Buoyancy a, b 21 ± 1.2 N 21 ± 1.2 N 29 ± 1.2 N
a The buoyancy of most foams will change over time with the greatest change occurring in the first several months after manufacture. The exact kind of foam selected will need to be evaluated to determine the amount of additional b uoyancy needed at the time of manufacture to achieve the values specified.
b Buoyancy distribution: 59.2 % front 1.5 percentage points

---CHUNK---

SOURCE: MSC.200(80).pdf
determine the amount of additional b uoyancy needed at the time of manufacture to achieve the values specified.
b Buoyancy distribution: 59.2 % front 1.5 percentage points

Table C.5 – List of dimensions shown in figures C.4 - C.9

Dimensions (mm)
Figure C.5 Dimension Figure
C.4 Key-1 Key-2
Figure
C.6
Figure
C.7
Figure
C.8
Figure
C.9
a 390 75 80 75 90 950 * 45
b 195 105 110 40 115

c 85 140
d 220 45
e 245 25
f 241 33
g 482 95
h 260 25
i 490 160
* With webbing assembly fully extended.

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 55

I:\MSC\80\24-ADD-1.DOC

Left Right

Outside (front) Inside

Key
1 Inside cover fabric
2 Outside cover fabric
3 Adjustable part of closure
4 Zippers for access to front righ t and left foam compartment
5 Waist belt
6 Fixed part of chest strap
7 Zipper for access to back foam compartment
8 Belt loop
9 Fixed part of closure
10 Adjustable part of chest strap

---CHUNK---

SOURCE: MSC.200(80).pdf
4 Zippers for access to front righ t and left foam compartment
5 Waist belt
6 Fixed part of chest strap
7 Zipper for access to back foam compartment
8 Belt loop
9 Fixed part of closure
10 Adjustable part of chest strap

Figure C.1 – General arrangement, right side out (outside and inside)

RESOLUTION MSC.200(80)
(adopted on 13 May 2005)

Key
1 Trim upper right corner only for left insert layers per table C.2
2 Trim upper left corner only for right insert layers per table C.2
3 Outside
4 Inside

Figure C.2 – Front foam inserts (right and left sides)

Figure C.3 – Back foam insert