Figure C.4 – Cover cut pattern (outside and inside covers)

Key
1 Fabric reinforcements for chest strap attachments
2 Fabric reinforcement for waist belt and belt loop attachments

---CHUNK---

Figure C.4 – Cover cut pattern (outside and inside covers)

Key
1 Fabric reinforcements for chest strap attachments
2 Fabric reinforcement for waist belt and belt loop attachments

Figure C.5 – Fabric reinforcements

Key
1 Bar-tack
2 Webbing
3 Outer cover and reinforcemen t (shown on lower view only)

Figure C.6 – Belt loop

Key
1 Webbing
2 Double bar-tack (or Box-x) stitch
3 Fixed part of closure
4 Adjustable part of closure
5 Double bar-tack (or Box-x) stitch
6 Webbing
7 Tab
8 Outer cover and reinforcemen t (shown on lower view only)

Figure C.7 – Chest strap assembly (adjustable part left and fixed part right)

I:\MSC\80\24-ADD-1.DOC

Key
1 Fixed part of closure

---CHUNK---

SOURCE: MSC.200(80).pdf
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 59

I:\MSC\80\24-ADD-1.DOC

Key
1 Fixed part of closure

2 Box-x (or double bar-tack) stitch
3 Webbing
4 Tab, double fold webbing and secure with a bar-tack stitch
5 Adjustable part of closure
6 Outer left cover and reinforcement (shown on lower view only)

Figure C.8 – Waist belt assembly

Key
1 Stitching on interior reinforcement for chest strap on right and left sides of outside cover only
2 Stitching on interior reinforcement for waist belt and belt loop on right and left sides of outside cover only
3 Fabric fold and zipper teeth line of e ngagement when attached to outside and inside covers
4 Fabric fold and zipper teeth line of e ngagement when attached to outside and inside covers
5 Lockstitch seams (with fabric face to face)
6 Lockstitch with 5 mm seam allowance and over-edge stitch (with fabric face to face)
7 After stitching seams cut relief

Figure C.9 – Initial assembly (shown right side out, except as noted)
RESOLUTION MSC.200(80)

---CHUNK---

SOURCE: MSC.200(80).pdf
6 Lockstitch with 5 mm seam allowance and over-edge stitch (with fabric face to face)
7 After stitching seams cut relief

Figure C.9 – Initial assembly (shown right side out, except as noted)
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 60

I:\MSC\80\24-ADD-1.DOC
APPENDIX

RTD Serial number: _____

INFANT REFERENCE TEST DEVICE – BUOYANCY TRACKING AND VERIFICATION

To achieve repeatability in human subject and manikin testing, the overall buoyancy and distribution of buoyancy between the front a nd back of the RTD should be maintained within a tight tolerance as specified in table 1.

Table 1 – SOLAS infant RTD buoyancy and tolerance

Limit / Units Front buoyancy (1) (2) Back buoyancy (1) Total buoyancy (1) Buoyancy distribution (3)
Design / N 42 29 71 59.2% in front
Maximum / N 44.4 30.2 74.6 60.7% in front
Minimum / N 39.6 27.8 67.4 57.7% in front
(1) Values at or corrected to standard temperature and pressure.
(2) The left-to-right buoyancy distribution in the front inserts is to be within 1.3 N of each other.

---CHUNK---

SOURCE: MSC.200(80).pdf
Minimum / N 39.6 27.8 67.4 57.7% in front
(1) Values at or corrected to standard temperature and pressure.
(2) The left-to-right buoyancy distribution in the front inserts is to be within 1.3 N of each other.
(3) Buoyancy distribution is calculated by dividing the front buoyancy by the total buoyancy.

The buoyancy of a new RTD may exceed the al lowable tolerance range until the normal shrinkage or compression of the foam inserts stabilizes. Until the buoyancies of the foam inserts have stabilized, buoyancy and distribut ion should be checked at regular intervals (perhaps weekly), and then at least monthly thereafter or whenever used for testing, whichever is longer (frequent use may require more frequent checks). Only RTD’s with buoyancies within tolerance should be used fo r certification testing. A data sheet to