document the buoyancy and buoyancy distribution of the RTD is attached.

To check buoyancy tolerances, foam inserts n eed to be removed from the device. Take care that all trapped air is removed when checking buoyancy and that layers are maintained in their proper sequence when reinstalled (considerable effort would be

---CHUNK---

SOURCE: MSC.200(80).pdf
care that all trapped air is removed when checking buoyancy and that layers are maintained in their proper sequence when reinstalled (considerable effort would be needed to remove entrapped air if testing the intact device).

Adjustment of buoyancy: At the time of manufacture th e left-to-right distribution of buoyancy in the front inserts was adjusted to be within 1.3 N of each other. To achieve this tolerance, the layers were individually selected to achieve the cumulative insert buoyancy. If buoyancy of a new device exceeds the upper limits, one layer per compartment may be altered or replaced to bring the unit into compliance. The test house may need to add make-up layers (see figure 3) from time to time to maintain the front-to-back and side -to-side insert tolerances. If the front buoyancy is under the minimum value, measure the buoyancy of the right and left sides so that the proper distribution of buoyancy (no more than a 1.3 N difference) between the right and left front panels can be maintained.
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF

---CHUNK---

SOURCE: MSC.200(80).pdf
distribution of buoyancy (no more than a 1.3 N difference) between the right and left front panels can be maintained.
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17

Table 2 – SOLAS infant RTD insert design buoyancies

Combined left front inserts (15 layers)	
Combined right front inserts (15 layers)	
Combined back inserts (11 layers)	
Design (N)	21 21 29
S/N _____	
Date:	

RTD BUOYANCY DATA SHEET

RTD Serial number/identification: _____

Date	Left front buoyancy (N)	Right front buoyancy (N)	Total front buoyancy (N)	Total back buoyancy (N)	Total buoyancy (N)	Buoyancy distribution (% in front)	Remarks (1) (2)

(1) Left and right front buoyancy need not be checked if distribution is within tolerance.
(2) If the temperature and pressure at the time of measurement is not at standard conditions, these values should be corrected to standard temperature and pressure.

---CHUNK---

SOURCE: MSC.200(80).pdf
(2) If the temperature and pressure at the time of measurement is not at standard conditions, these values should be corrected to standard temperature and pressure.

Key
1 Trim upper right corner only fo r left insert layers A to E
2 Trim upper left corner only fo r right insert layers A to E

3 Outside
4 Inside
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
LIFE-SAVING APPLIANCESMSC 80/24/Add.1
ANNEX 17
Page 62

I:\MSC\80\24-ADD-1.DOC

Insert layer Insert layer dimensions (mm)

Buoyancy
(N) a b c
A 1.7 140 190 28
B 1.6 133 184 28
C 1.4 127 178 28
D 1.3 120 172 28
E 1.1 108 165 28
F 1.0 95 160 0
G 0.8 83 140 0

Figure 1 – Front foam insert specifications

Insert layer Insert layer dimensions (mm)

Buoyancy
(N) a b c R
A 3.1 310 165 3 44
B 2.9 303 160 3 46
C 2.4 290 140 3 48
D 1.8 275 120 3 50
E 1.3 255 95 -3* 52
* measured in direction opposite to that shown in figure.

Figure 2 – Back foam insert specifications
RESOLUTION MSC.200(80)
(adopted on 13 May 2005)
ADOPTION OF AMENDMENTS TO THE REVISED
RECOMMENDATION ON TESTING OF
SOURCE: MSC.200(80).pdf
E 1.3 255 95 -3* 52
* measured in direction opposite to that shown in figure.

Figure 2 – Back foam insert specifications
RESOLUTION MSC.200(80)

1 Any thickness of foam up to 7 mm is acceptable for a make-up layer.
2 For 7 mm thick foam, 15,300 mm 2 surface area equals approximately 1 N of buoyancy.

Make-up layer dimensions (mm)		Make-up layer (1)	Buoyancy (approx.) (N)
Length (mm) (2)	Width (mm)		