Organization for circulation to the Parties to the present Protocol particulars thereof, for their information.

Regulation 20

Attained Energy Efficiency Design Index (Attained EEDI)

1 The attained EEDI shall be calculated for:

.1 each new ship;

.2 each new ship which has undergone a major conversion; and

.3 each new or existing ship which has undergone a major conversion, that is so extensive that the ship is regarded by the Administration as a newly constructed ship,

which falls into one or more of the categories in regulations 2.25 to 2.35 of this Annex. The attained EEDI shall be specific to each ship and shall indicate the estimated performance of the ship in terms of energy efficiency, and be accompanied by the EEDI technical file that contains the information necessary for the calculation of the attained EEDI and that shows the process of calculation. The attained EEDI shall be verified, based on the EEDI technical file, either by the Administration or by any organization duly authorized by it.

---CHUNK---

SOURCE: MEPC.203(62).pdf

the calculation of the attained EEDI and that shows the process of calculation. The attained EEDI shall be verified, based on the EEDI technical file, either by the Administration or by any organization duly authorized by it.

2 The attained EEDI shall be calculated taking into account guidelines developed by the Organization.

Regulation 21

Required EEDI

1 For each:

.1 new ship;

.2 new ship which has undergone a major conversion; and

.3 new or existing ship which has undergone a major conversion that is so extensive that the ship is regarded by the Administration as a newly constructed ship,

which falls into one of the categories defined in regulations 2.25 to 2.31 of this Annex and to which this chapter is applicable, the attained EEDI shall be as follows:

Attained EEDI ~ Required EEDI = (1-Xl1 00) x Reference line value

where X is the reduction factor specified in Table 1 for the required EEDI compared to the EEDI Reference line.

2 For each new and existing ship that has undergone a major conversion which is so extensive that the ship is regarded by the Administration as a newly

---CHUNK---

SOURCE: MEPC.203(62).pdf

to the EEDI Reference line.

2 For each new and existing ship that has undergone a major conversion which is so extensive that the ship is regarded by the Administration as a newly constructed ship, the attained EEDI shall be calculated and meet the requirement of paragraph 21.1 with the reduction factor applicable corresponding to the ship type and size of the converted ship at the date of the contract of the conversion, or in the absence of a contract, the commencement date of the conversion.

Adopted on 15 July 2011
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 11 -
Table 1. Reduction factors (in percentage) for the EEDI relative to the EEDI Reference line
Phase 0 Phase 1 Phase 2 Phase 3
Ship Type Size 1 Jan 2013- 1 Jan 2015- 1 Jan 2020- 1 Jan 2025
31 Dec 2014 31 Dec 2019 31 Dec2024 and onwards
20,000 DWT 0 10 20 30 and above Bulk carrier 10,000 -
20,000 DWT nfa 0-10' 0-20' 0-30'
10,000 DWT 0 10 20 30 and above Gas carrier 2,000 -
10,000 DWT nfa 0-10' 0-20' 0-30'

---CHUNK---

SOURCE: MEPC.203(62).pdf
31 Dec 2014 31 Dec 2019 31 Dec2024 and onwards
20,000 DWT 0 10 20 30 and above Bulk carrier 10,000 -
20,000 DWT nfa 0-10' 0-20' 0-30'
10,000 DWT 0 10 20 30 and above Gas carrier 2,000 -
10,000 DWT nfa 0-10' 0-20' 0-30'
20,000 DWT 0 10 20 30 and above Tanker 4,000 -
20,000 DWT nfa 0-10' 0-20' 0-30'
15,000 DWT 0 10 20 30 and above Containership 10,000 -
15,000 DWT nfa 0-10' 0-20' 0-30'
15,000 DWT
General Cargo and above 0 10 15 30
,
ships 3,000- nfa 0-10' 0-15' 0-30' 15,000 DWT
5,000 DWT 0 10 15 30 Refrigerated and above
cargo carrier 3,000 - nfa 0-10' 0-15' 0-30' 5,000 DWT
20,000 DWT 0 10 20 30 Combination and above
carrier 4,000 - nfa 0-10' 0-20' 0-30' 20,000 DWT
Reduction factor to be linearly interpolated between the two values dependent upon vessel size. The lower value of the reduction factor is to be applied to the smaller ship size.
nfa means that no required EEDI applies.
3 The Reference line values shall be calculated as follows:
Reference line value = a xb -c
where a, band c are the parameters given in Table 2.
RESOLUTION MEPC.203(62)
Adopted on 15 July 2011
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE

---CHUNK---

SOURCE: MEPC.203(62).pdf
Reference line value = a xb -c
where a, band c are the parameters given in Table 2.
RESOLUTION MEPC.203(62)
Adopted on 15 July 2011
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE
INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM

SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 12 -
Table 2. Parameters for determination of reference values for the different ship types
Ship type defined in reaulation 2 a b c
2.25 Bulk carrier 961.79 OWT of the ship 0.477
2.26 Gas carrier 1120.00 OWT of the ship 0.456
2.27 Tanker 1218.80 OWT of the sh~ 0.488
2.28 Containership 174.22 OWT of the ship 0.201
2.29 General cargo ship 107.48 OWT of the ship 0.216
2.30 Refrigerated cargo carrier 227.01 OWT of the ship 0.244
2.31 Combination carrier 1219.00 OWT of the ship 0.488
4 If the design of a ship allows it to fall into more than one of the ship type definitions specified in table 2. the required EEOI for the ship shall be the most stringent (the lowest) required EEOI.
5 For each ship to which this regulation applies. the installed propulsion power shall not be less than the propulsion power needed to maintain the

---CHUNK---

SOURCE: MEPC.203(62).pdf
stringent (the lowest) required EEOI.
5 For each ship to which this regulation applies. the installed propulsion power shall not be less than the propulsion power needed to maintain the manoeuvrability of the ship under adverse conditions as defined in the guidelines to be developed by the Organization.
6 At the beginning of Phase 1 and at the midpoint of Phase 2. the Organization shall review the status of technological developments and. if proven necessary. amend the time periods. the EEOI reference line parameters for relevant ship types and reduction rates set out in this regulation.
Regulation 22
Ship Energy Efficiency Management Plan (SEEMP)
1 Each ship shall keep on board a ship specific Ship Energy Efficiency Management Plan (SEEMP). This may form part of the ship 's Safety Management System (SMS).
2 The SEEMP shall be developed taking into account guidelines adopted by the Organization.
Regulation 23
Promotion of technical co-operation and transfer of technology relating to the improvement of energy efficiency of ships
1 Administrations shall. in co-operation with the Organization and other

---CHUNK---

SOURCE: MEPC.203(62).pdf
the Organization.
Regulation 23
Promotion of technical co-operation and transfer of technology relating to the improvement of energy efficiency of ships
1 Administrations shall. in co-operation with the Organization and other international bodies. promote and provide. as appropriate . support directly or through the Organization to States. especially developing States. that request technical assistance .
2 The Administration of a Party shall co-operate actively with other Parties. subject to its national laws. regulations and policies. to promote the development

and transfer of technology and exchange of information to States which request technical assistance. particularly developing States. in respect of the implementation of measures to fulfil the requirements of chapter 4 of this Annex. in particular regulations 19.4 to 19.6."
RESOLUTION MEPC.203(62)
Adopted on 15 July 2011
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 13 - 23 A new appendix VIII is added at the end of the Annex as follows :
"APPENDIX VIII

---CHUNK---

SOURCE: MEPC.203(62).pdf
INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 13 - 23 A new appendix VIII is added at the end of the Annex as follows :
"APPENDIX VIII
Form of International Energy Efficiency (lEE) Certificate
INTERNATIONAL ENERGY EFFICIENCY CERTIFICATE
Issued under the provisions of the Protocol of 1997. as amended by resolution MEPC.203(62). to amend the International Convention for the Prevention of Pollution by