1.1 General

1.1.1 In 2003, the Marine Environment Protection Committee adopted the Revised guidelines and specifications for pollution prevention equipment for machinery space bilges of ships (resolution MEPC.107(49)). The main purpose of this revision of the specifications of oil filtering equipment was to improve their capability of treating emulsified oil.

1.1.2 The present Guidelines have been developed to provide further assistance for

---CHUNK---

SOURCE: MEPC.205(62).pdf
of oil filtering equipment was to improve their capability of treating emulsified oil.

1.1.2 The present Guidelines have been developed to provide further assistance for upgrading systems installed on board ships prior to 1 January 2005, and of which oil filtering equipment was approved under resolution MEPC.60(33).

1.1.3 It has been recognized that the best measure to prevent pollution resulting from oily bilge water is installation of Integrated Bilge Water Treatment System (IBTS) in accordance with MEPC.1/Circ.642 as may be amended. IBTS prevents generation of oily bilge water. Although it may not be easy or practicable to fit complete IBTS on existing ships, pre-cleaning of oily bilge water, e.g., provision of a primary tank between bilge wells and bilge tank, should be seriously considered in order to remove impurities in bilge through surfacing or sedimentation, which is an effective way of preventing clogging of bilge separators.

1.2 Scope

These guidelines apply to add-on post-treatment equipment for resolution MEPC.60(33)-compliant oil filtering equipment in order to improve their capabilities of

---CHUNK---

SOURCE: MEPC.205(62).pdf
1.2 Scope

These guidelines apply to add-on post-treatment equipment for resolution MEPC.60(33)-compliant oil filtering equipment in order to improve their capabilities of treating emulsified oil so that emulsion-breaking performance of oily bilge separators to be achieved by installation of add-on equipment could be equivalent to that of resolution MEPC.107(49)-compliant equipment.

1.3 Upgrading options

Equipment for upgrading existing oil filtering equipment are the following two types:

.1 equipment which could upgrade specific make of oil filtering equipment. Such equipment should be tested in accordance with Part 1 of the test specifications contained in the annex hereto, connected to a resolution MEPC.60(33) oil filtering equipment and type approved for use in conjunction with that specific make of oil filtering equipment tested, subject to: 1) environmental testing contained in Part 3 of the annex to resolution MEPC.107(49) and 2) the limiting conditions of the certification of the

upgraded equipment.

.2 equipment which could upgrade any make of resolution MEPC.60(33)-compliant oil filtering equipment. Such equipment should be

---CHUNK---

SOURCE: MEPC.205(62).pdf
MEPC.107(49) and 2) the limiting conditions of the certification of the upgraded equipment.

.2 equipment which could upgrade any make of resolution MEPC.60(33)-compliant oil filtering equipment. Such equipment should be tested in accordance with Part 2 of the test specifications contained in the annex hereto and type approved for use in conjunction with any make of oil filtering equipment, subject to: 1) environmental testing contained in Part 3 of the annex to resolution MEPC.107(49) and 2) the limiting conditions of the certification of the upgraded equipment.

2 DEFINITIONS

Unless otherwise specified, definitions of the terms used in the Revised guidelines and specifications for pollution prevention equipment for machinery space bilges of ships (resolution MEPC.107(49)) apply to these Guidelines.
RESOLUTION MEPC.205(62)
Adopted on 15 July 2011
2011 GUIDELINES AND SPECIFICATIONS FOR ADD-ON EQUIPMENT FOR UPGRADING RESOLUTION MEPC.60(33)-COMPLIANT OIL FILTERING EQUIPMENTMEPC 62/24/Add.1
Annex 24, page 4

I:\MEPC\62\24-Add-1.doc
3 TECHNICAL SPECIFICATIONS

3.1 The add-on equipment should be strongly constructed and suitable for shipboard

---CHUNK---

SOURCE: MEPC.205(62).pdf
MEPC.60(33)-COMPLIANT OIL FILTERING EQUIPMENTMEPC 62/24/Add.1
Annex 24, page 4

I:\MEPC\62\24-Add-1.doc
3 TECHNICAL SPECIFICATIONS

3.1 The add-on equipment should be strongly constructed and suitable for shipboard use, bearing in mind its intended location on the ship.

3.2 It should, if intended to be fitted in locations where flammable atmospheres may be present, comply with the relevant safety regulations for such spaces. Any electrical equipment which forms part of the add-on equipment should be based in a non-hazardous area, or should be certified by the Administration as safe for use in a hazardous area. Any moving parts which are fitted in hazardous areas should be arranged so as to avoid the

formation of static electricity.

3.3 The add-on equipment should be so designed that it functions automatically in conjunction with the existing equipment.

3.4 The add-on equipment should require the minimum of attention to bring it into operation. In the case of equipment used for engine room bilges, there should be no need for any adjustment to valves and other equi pment to bring the add-on equipment into

---CHUNK---

SOURCE: MEPC.205(62).pdf
operation. In the case of equipment used for engine room bilges, there should be no need for any adjustment to valves and other equi pment to bring the add-on equipment into operation. The equipment should be capable of operating for at least 24 hours of normal duty without attention.

3.5 It should be understood that the complete type approval with the test fluid C should be performed without interruption to attend, clean or maintain the bilge water separator. This test would be regarded as a simulation of the 24 hours of unattended operation not requiring any crew attention.

3.6 It should be understood that the 15 ppm bilge separator should operate continuously and automatically without any interruptions. It should be assured that back flushing if performed during the certification test does not cause:

.1 dilution of the test fluid C, or

.2 dilution of the test sample sent to the laboratory for analysis.

3.7 If input flow of test fluid C is interrupted during the performance of the test it should be assured that the total quantities of test fluid C processed automatically are not less than the

---CHUNK---

SOURCE: MEPC.205(62).pdf
3.7 If input flow of test fluid C is interrupted during the performance of the test it should be assured that the total quantities of test fluid C processed automatically are not less than the nominal flow of the tested equipment multiplied by the specified test duration of 150 minutes (2.5 hours). While all the time, the tested equipment operates continuously and automatically without human intervention.

3.8 The continuous and automatic operation should apply to the performance tests with the test fluid C according to the test result diagrams in the appendix to appendix 1 of resolution MEPC.107(49) as it relates to test fluid C. However, if due to the separation process any interruption in feeding the test fluid with nominal flow rate, e.g., for back flushing, is deemed necessary, the time for these interruptions should be added to the required time of the test step which was interrupted during the performance test. While all the time, the tested equipment operates continuously and automatically without human intervention.

3.9 All working parts of the add-on equipment which are liable to wear or to damage should be easily accessible for maintenance.

---CHUNK---

SOURCE: MEPC.205(62).pdf
tested equipment operates continuously and automatically without human intervention.

3.9 All working parts of the add-on equipment which are liable to wear or to damage should be easily accessible for maintenance.

RESOLUTION MEPC.205(62)
Adopted on 15 July 2011
2011 GUIDELINES AND SPECIFICATIONS FOR ADD-ON EQUIPMENT FOR UPGRADING RESOLUTION MEPC.60(33)-COMPLIANT OIL FILTERING EQUIPMENTMEPC 62/24/Add.1
Annex 24, page 5

I:\MEPC\62\24-Add-1.doc
4 SPECIFICATION FOR TYPE APPROVAL TESTING OF ADD-ON EQUIPMENT

4.1 Testing requirements

4.1.1 The production model of add-on equipment, for which the approval will apply, should be identical to the equipment, type-tested in accordance with the performance and test specifications contained in part 1 or 2 of the annex to these Guidelines. The equipment should also be type-tested in accordance with the specifications for environmental testing