2.1 Ships required to carry an IAFS Certificate or Declaration on Anti-Fouling Systems (Parties of the AFS Convention)

2.1.1 The PSCO should check the validity of the IAFS Certificate or Declaration on Anti-Fouling Systems, and the attached Record of Anti-Fouling Systems, if appropriate.

2.1.2 The only practical way to apply paint to the ship's bottom (underwater part) is in a dry dock. This means that the date of application of paint on the IAFS Certificate should be checked by comparing the period of dry-docking with the date on the certificate.

2.1.3 If the paint has been applied during a scheduled dry-dock period, it has to be registered in the ship's logbook (in order to be legal). Furthermore, this scheduled dry-docking can be verified by the endorsement date on the (statutory) Safety Construction Certificate (SOLAS, regulation I/10).

2.1.4 In case of an unscheduled dry-dock period, it could be verified by the registration in the ship's logbook (in order to be legal).

2.1.5 It can be additionally verified by the endorsement date on the (Class) Hull Certificate,

---CHUNK---

SOURCE: MEPC.208(62).pdf
2.1.4 In case of an unscheduled dry-dock period, it could be verified by the registration in the ship's logbook (in order to be legal).

2.1.5 It can be additionally verified by the endorsement date on the (Class) Hull Certificate, the dates on the Manufacturer's Declaration or by confirmation of the shipyard.

2.1.6 The IAFS Certificate includes a series of tick boxes indicating:

.1 if an anti-fouling system controlled under Annex 1 of the AFS Convention has or has not been applied, removed or been covered with a sealer coat;

.2 if an anti-fouling system controlled under Annex 1 of the AFS Convention was applied on the ship prior to 1 January 2003 or a later date if specified by the Administration; and

.3 if an anti-fouling system controlled under Annex 1 of the AFS Convention was applied on the ship on/after 1 January 2003 or a later date if specified by the Administration.

2.1.7 Particular attention should be given to verifying that the survey for issuance of the

---CHUNK---

SOURCE: MEPC.208(62).pdf
was applied on the ship on/after 1 January 2003 or a later date if specified

by the Administration.

2.1.7 Particular attention should be given to verifying that the survey for issuance of the current IAFS Certificate matches the dry-dock period listed in the ship's log(s) and that only one tick box is marked.

2.1.8 The Record of Anti-Fouling Systems should be attached to the IAFS Certificate and be up to date. The most recent record should agree with the tick box on the front of the IAFS Certificate.

2.2 Ships of non-Parties to the AFS Convention

2.2.1 Ships of non-Parties to the AFS Convention are not entitled to be issued with an IAFS Certificate. Therefore the PSCO should ask for documentation that contains the same information as in an IAFS Certificate and take this into account in determining compliance with the requirements.

2.2.2 If the existing anti-fouling system is declared not to be controlled under Annex 1 of the Convention, without being documented by an International Anti-Fouling System Certificate, verification should be carried out to confirm that the anti-fouling system complies

---CHUNK---

SOURCE: MEPC.208(62).pdf
the Convention, without being documented by an International Anti-Fouling System Certificate, verification should be carried out to confirm that the anti-fouling system complies with the requirements of the Convention. This verification may be based on sampling and/or testing and/or reliable documentation, as deemed necessary, based on experience gained and the existing circumstances. Documentation for verification could be, e.g., MSDSs (Material Safety Data Sheets), or similar, a declaration of compliance from the anti-fouling system manufacturer, invoices from the shipyard and/or the anti-fouling system manufacturer.

2.2.3 Ships of non-Parties may have Statements of Compliance issued in order to comply with regional requirements, for example, Regulation (EC) 782/2003 as amended by Regulation (EC) 536/2008, which could be considered as providing sufficient evidence of compliance.

2.2.4 In all other aspects the PSCO should be guided by the procedures for ships required to carry an IAFS Certificate.

2.2.5 The PSCO should ensure that no more favourable treatment is applied to ships of non-Parties to the AFS Convention.

3 MORE DETAILED INSPECTION

---CHUNK---

SOURCE: MEPC.208(62).pdf
to carry an IAFS Certificate.

2.2.5 The PSCO should ensure that no more favourable treatment is applied to ships of non-Parties to the AFS Convention.

3 MORE DETAILED INSPECTION

3.1 Clear ground

3.1.1 A more detailed inspection may be carried out when there has been clear grounds to believe that the ship does not substantially meet the requirements of the AFS Convention. Clear grounds for a more detailed inspection may be when:

.1 the ship is from a flag of a non-Party to the Convention and there is no AFS documentation;

.2 the ship is from a flag of a Party to the Convention but there is no valid IAFS Certificate;

.3 the painting date shown on the IAFS Certificate does not match the dry-dock period of the ship;

.4 the ship's hull shows excessive patches of different paints; and

.5 the IAFS Certificate is not properly completed.

3.1.2 If the IAFS Certificate is not properly completed, the following questions may be pertinent:

---CHUNK---

SOURCE: MEPC.208(62).pdf
.4 the ship's hull shows excessive patches of different paints; and

.5 the IAFS Certificate is not properly completed.

3.1.2 If the IAFS Certificate is not properly completed, the following questions may be pertinent:

.1 "When was the ship's anti-fouling system last applied?";

.2 "If the anti-fouling system is controlled under Annex 1 to the AFS Convention and was removed, what was the name of the facility and date of the work performed?";

.3 "If the anti-fouling system is controlled under Annex 1 of the AFS Convention and has been covered by a sealer coat, what was the name of the facility and date applied?";

.4 "What is the name of the anti-fouling/sealer products and the manufacturer or distributor for the existing anti-fouling system?"; and

.5 "If the current anti-fouling system was changed from the previous system, what was the type of anti-fouling system and name of the previous

manufacturer or distributor?".

3.2 Sampling

3.2.1 A more detailed inspection may include sampling and analysis of the ship's anti-fouling system, if necessary, to establish whether or not the ship complies with the

---CHUNK---

SOURCE: MEPC.208(62).pdf
manufacturer or distributor?".

3.2 Sampling

3.2.1 A more detailed inspection may include sampling and analysis of the ship's anti-fouling system, if necessary, to establish whether or not the ship complies with the AFS Convention. Such sampling and analysis may involve the use of laboratories and detailed scientific testing procedures.

3.2.2 If sampling is carried out, the time to process the samples cannot be used as a reason to delay the ship.

3.2.3 Any decision to carry out sampling should be subject to practical feasibility or to