using an oxygen content meter (Note: National requirements may
determine a safe atmosphere range);

.2 where the preliminary assessment has determined that there is potential for
flammable gases or vapours, the concentration of those gases or vapours
is not higher than 1 per cent of their lower flammable limit (LFL), measured
using a suitably sensitive combustible gas indicator; and

.3 the concentration of any toxic vapours and gases is not higher
than 50 per cent of their occupational exposure limit (OEL)1.

If these conditions cannot be met, the space should be ventilated further and retested after a
suitable interval.

3.3.4.1.2 Competent person for Safe-for-entry determination

---CHUNK---

SOURCE: MEPC.210(63).pdf
than 50 per cent of their occupational exposure limit (OEL)1.

If these conditions cannot be met, the space should be ventilated further and retested after a
suitable interval.

3.3.4.1.2 Competent person for Safe-for-entry determination

Regulation 1 of the Convention defines "Competent person". The Competent Authority
should define the appropriate criteria for designation of a Competent person. However, the
Competent person(s) for Safe-for-entry and/or Safe-for-hot-work determination should be
able to determine oxygen content, concentration of flammable vapours and gases and the
presence of toxic, corrosive, irritant or fumigated atmospheres and residues. The Competent
person should possess sufficient knowledge and practical experience to make an informed
assessment based on the structure, location and designation of spaces where work is done.
The Competent person should possess the ability to inspect, test and evaluate spaces to
determine the need for further testing. The Competent person should also monitor the
maintenance of appropriate conditions in spaces.

3.3.4.1.3 Safe-for-entry inspection and testing procedures

---CHUNK---

SOURCE: MEPC.210(63).pdf
determine the need for further testing. The Competent person should also monitor the
maintenance of appropriate conditions in spaces.

3.3.4.1.3 Safe-for-entry inspection and testing procedures

Designation as "Safe-for-entry" is not sufficient for hot work, as additional criteria must be
met to address safety issues related to hot work. Testing should be carried out by
a Competent person using appropriate and pr operly certified and calibrated equipment,
including, but not limited to, an oxygen content meter, combustible gas indicator, toxicity
meter and gas or vapour detection equipment.

3.3.4.1.4 Oxygen

The Ship Recycling Facility should ensure that spaces are tested by a Competent person to determine the atmosphere's oxygen content prior to initial entry into the space by workers, and also that the space is periodically monitor ed and recorded for as long as it is occupied. Spaces that warrant particular consideration include the following:

spaces that have been sealed;

1 It should be noted that the term occupational exposure limit (OEL) includes the permissible exposure limit

---CHUNK---

SOURCE: MEPC.210(63).pdf
spaces that have been sealed;

1 It should be noted that the term occupational exposure limit (OEL) includes the permissible exposure limit (PEL), maximum allowable concentration (MAC) and threshold limit value (TLV), or any other internationally recognized terms.

spaces and adjacent spaces that contain or have recently contained combustible or flammable liquids or gases;

spaces and adjacent spaces that contain or have recently contained liquids, gases or solids that are toxic, corrosive, or irritant;

spaces and adjacent spaces that have been fumigated; and

spaces containing materials or residues of materials that create an oxygen-deficient atmosphere.

A worker should only enter a space where the oxygen content, by volume, has the value noted in 3.3.4.1.1. In such a case, the space should be labelled "Safe-for-entry". If an oxygen-deficient or oxygen-enriched atmosphere is found, ventilation should be

---CHUNK---

SOURCE: MEPC.210(63).pdf
noted in 3.3.4.1.1. In such a case, the space should be labelled "Safe-for-entry". If an oxygen-deficient or oxygen-enriched atmosphere is found, ventilation should be
provided at volumes and flow rates sufficient to ensure that the oxygen content is maintained at the value noted in 3.3.4.1.1. The label may be reattached when the oxygen content returns to the value noted in 3.3.4.1.1, and after it has been tested and inspected by the Competent person.

3.3.4.1.5 Flammable atmospheres

The Ship Recycling Facility should ensure that spaces and adjacent spaces that contain or have contained combustible or flammable liquids or gases are visually inspected and tested by the Competent person prior to entry by workers, and that they are periodically monitored and the results recorded throughout the time that the spaces are occupied.

If the concentration of flammable vapours or gases in the space to be entered is equal to or greater than 1 per cent of the lower flammable limit, then no one should enter the space and the label "Safe-for-entry" should be removed. Ventilation should be provided at volumes and

---CHUNK---

SOURCE: MEPC.210(63).pdf
greater than 1 per cent of the lower flammable limit, then no one should enter the space and the label "Safe-for-entry" should be removed. Ventilation should be provided at volumes and flow rates sufficient to ensure that the concentration of flammable vapours is maintained below 1 per cent of the lower flammable limit. The label may be reattached when the concentration of flammable vapours falls below 1 per cent of the lower flammable limit and after it has been tested and inspected by the Competent person.

3.3.4.1.6 Toxic, corrosive, irritant or fumigated atmospheres and residues

The Ship Recycling Facility should ensure that spaces or adjacent spaces that contain or have contained liquids, gases or solids that are toxic, corrosive or irritant are visually inspected and tested by a Competent person prior to initial entry by workers.

If a space contains an air concentration of a material which exceeds 50 per cent of their OEL, then no one should enter the space and it should not be labelled "Safe-for-entry". Ventilation should be provided at volumes and flow rates sufficient to ensure that air concentrations are

---CHUNK---

SOURCE: MEPC.210(63).pdf
then no one should enter the space and it should not be labelled "Safe-for-entry". Ventilation should be provided at volumes and flow rates sufficient to ensure that air concentrations are maintained below 50 per cent of their OEL. The label may be reattached when the concentration of contaminants is maintained below 50 per cent of their OEL and after it has been tested and inspected by the Competent person.

3.3.4.1.7 Safe-for-entry determination by a Competent person

A Competent person should visually inspect and test each space certified as "Safe-for-entry" as often as necessary to ensure that atmospheric conditions within that space are maintained within the conditions established by the certificate. However, at a minimum, the space should be inspected and tested at least once in an eight-hour shift period. The results of these tests should be recorded on the Safe-for-entry certificate.

When a change occurs that could alter conditions within a tested enclosed space or other

---CHUNK---

SOURCE: MEPC.210(63).pdf
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 15

I:\MEPC\63\23.doc
When a change occurs that could alter conditions within a tested enclosed space or other dangerous atmosphere, work in the affected space or area should be stopped. Work may not be resumed until the affected space or area is visually inspected and retested by the Competent person and found to comply with the certification. It is recommended that the space should be ventilated and the atmospheric conditions returned to the acceptable limits after a space has been found to exceed limits.

If the Competent person has initially determined that a space is safe for an employee to enter and they subsequently find that the conditions within the tested space fail to meet the requirements, work should be stopped until the conditions in the tested space are corrected to comply with the certification requirements. If it is safe to do so, the Competent person may be asked to investigate the reason for the space's non-compliance and to ensure that the remedial action to be taken will prevent a reoccurrence.