---CHUNK---

SOURCE: MEPC.210(63).pdf
to comply with the certification requirements. If it is safe to do so, the Competent person may be asked to investigate the reason for the space's non-compliance and to ensure that the remedial action to be taken will prevent a reoccurrence.

3.3.4.1.8 Safe-for-entry certificate, warning signs and labels

Any determination of a space as "Safe-for-entry" should be accompanied by a certificate which, at a minimum, should clearly indicate the following information:

name and title of the Competent person performing the test(s) and inspection(s);
signature of the above person;
name of vessel and location;
the areas of the ship that are Safe-for-entry;
date and time of the inspection;
location of inspected spaces;
tests performed;
type of equipment used in testing;
test results;
period of retesting of the spaces;
results of periodic retesting undertaken;
conditions when the Competent person should be recalled or conditions that void the certificate;
safety designation(s) ("Safe-for-entry", "Not Safe-for-entry");
validity period and expiration date of the certificate, recommended to be

---CHUNK---

SOURCE: MEPC.210(63).pdf
conditions when the Competent person should be recalled or conditions that void the certificate;
safety designation(s) ("Safe-for-entry", "Not Safe-for-entry");
validity period and expiration date of the certificate, recommended to be a maximum of 24 hours, with periodic retesting intervals not exceeding eight hours;
type of ventilation; and
any additional relevant information or instructions.

Safe-for-entry certificates should be posted at every access point between ashore and the ship. A record of inspection of atmospheric tests should be appended to the certificate.

The certificate and/or the spaces themselves should be clearly marked and presented in a manner that can be seen and understood by all workers in the working language of the yard and, if possible, with pictorial representations.

If an entire work area has been tested and labelled with the proper signage (for example, as being "Safe-for-entry") at all points of access to the work area, an individual tank or other

---CHUNK---

SOURCE: MEPC.210(63).pdf
Annex 4, page 16

If an entire work area has been tested and labelled with the proper signage (for example, as being "Safe-for-entry") at all points of access to the work area, an individual tank or other space located within the work area need not be labelled separately.

The certificate, updates and any other records should be kept on file for a period of at least three months from the completion date of the specific job for which they were generated.

If a space at any time ceases to meet the Safe -for-entry criteria, the label "Safe-for-entry" should be removed.

3.3.4.1.9 Safe-for-entry operational measures

In addition to ensuring certification as "Safe-for-entry", the following operational measures should also be observed:

no person may open or enter an enclosed space unless authorized by the Competent person of the Ship Recycling Facility and unless the appropriate safety procedures have been followed;

a permit for entry has been issued for those intended to enter the space by the same individual(s) who is/are responsible for maintaining the certificate on

---CHUNK---

SOURCE: MEPC.210(63).pdf
safety procedures have been followed;

a permit for entry has been issued for those intended to enter the space by the same individual(s) who is/are responsible for maintaining the certificate on
behalf of the Ship Recycling Facility, confirming that all certification processes and operational measures for safe entry have been completed and are in effect;

the space is properly illuminated;

there is appropriate access and egress to the space and the working area in the enclosed space is suitable for the work that is being considered, specifically for heavy, large or complex lifting operations;

a suitable system of communication between all parties for use during entry is agreed upon, tested and used;

the space is adequately isolated from gases, liquids or other identified hazardous substances that could inadvertently be released into the space in which work is being undertaken;

a fully-trained supervisor, who may be in charge of one or more work teams, has oversight of the area and frequently monitors the conditions to which the workers are exposed;

the style of ventilation equipment is such that no ignition sources are introduced

---CHUNK---

SOURCE: MEPC.210(63).pdf
has oversight of the area and frequently monitors the conditions to which the workers are exposed;

the style of ventilation equipment is such that no ignition sources are introduced into a hazardous space;

the ventilation provided for the space is adequate for the work to be undertaken and for any diurnal variation in environmental conditions that may be experienced in hot or humid regions;

the ventilation system is designed to prevent the persistence of gas pockets within tanks/spaces owing either to the complex structure of the tank/space or to the fact that the gas pockets are heavier than air vapours in the tank which may be achieved by suction/evacuation style ventilation rather than blower ventilation;
RESOLUTION MEPC.210(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 17

I:\MEPC\63\23.doc
in the event of ventilation system failure, some means of alert is provided so that any persons in the space can leave immediately;

appropriate rescue and fire control plans are in place;

appropriate personal protective equipment (PPE), protective clothing and safety

---CHUNK---

SOURCE: MEPC.210(63).pdf
that any persons in the space can leave immediately;

appropriate rescue and fire control plans are in place;

appropriate personal protective equipment (PPE), protective clothing and safety equipment (including harnesses and lifelines) are provided to the workers, and used during entry to and work in the designated spaces; and

adequate and functioning rescue and resuscitation equipment has been provided and is positioned ready for use at the entrance of the space.

If the fire alarm is activated, the space should be evacuated until the all-clear for re-entry is

given by the Competent person.

3.3.4.2 Safe-for-hot-work procedures

The Ship Recycling Facility should ensure that no hot work commences on a ship unless the area is deemed "Safe-for-hot-work".

Safe-for-hot-work certification, inspection and testing apply to all of the following:

enclosed spaces and all other spaces enclosed by bulkheads and decks (including cargo holds, tanks, quarters, and machinery and boiler spaces) that potentially contain dangerous atmospheres;

within, on, or immediately adjacent to spaces that contain or have contained

---CHUNK---

SOURCE: MEPC.210(63).pdf
(including cargo holds, tanks, quarters, and machinery and boiler spaces) that potentially contain dangerous atmospheres;

within, on, or immediately adjacent to spaces that contain or have contained combustible or flammable liquids or gases;