"Safe-for-hot-work". The need for localized manual cleaning should be considered. Ventilation should allow an adequate flow of air to all parts of the space to prevent a build-up of gases either from the hot work or from the tank coatings;

ventilation should be provided at volumes and flow rates sufficient to ensure that the concentration of flammable vapours is maintained below 1 per cent of the lower flammable limit;

general mechanical ventilation should be of sufficient capacity and so arranged as to produce sufficient air changes to maintain safe levels of welding fumes and smoke; and

the Ship Recycling Facility's fire safety procedures should be followed.

3.3.4.3 Welding, cutting, grinding and heating

The SRFP should include procedures for ventilation, personnel monitoring for heavy-metals exposure, protection of personnel, training, respiratory protection, torch cutting, permits and inspections (including hot-work certification). The SRFP should include procedures for

---CHUNK---

SOURCE: MEPC.210(63).pdf
exposure, protection of personnel, training, respiratory protection, torch cutting, permits and inspections (including hot-work certification). The SRFP should include procedures for transporting, moving, securing, storing and using hoses and torches.
RESOLUTION MEPC.210(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 20

I:\MEPC\63\23.doc
3.3.4.4 Drums, containers and pressure vessels

The SRFP should include procedures for handling, transporting and storing pressure vessels containing flammable gases, such as acetylene (C 2H2), propane gas (C 3H8) or oxygen (O 2) for welding, heating and cutting works, in order to avoid any human injuries, caused by external forces, shock or heat to such vessels.

Procedures for removing pressure vessels containing carbon dioxide (CO 2), nitrogen (N 2) and other ozone-depleting substances used in fire -fighting and refrigeration systems should also be included.

Procedures for transporting and storing drums and containers containing hazardous liquids, using appropriate PPEs, should also be described in the SRFP.

---CHUNK---

SOURCE: MEPC.210(63).pdf
also be included.

Procedures for transporting and storing drums and containers containing hazardous liquids,

using appropriate PPEs, should also be described in the SRFP.

3.3.4.5 Prevention of falling from heights and accidents caused by falling objects

The SRFP should include procedures for using personal flotation devices, guarding deck openings, deck edges and platforms, utilizing personal fall arrest systems and guard rails and ensuring safe access to ships to prevent slip-and-fall accidents and the dropping and scattering of objects.

3.3.4.6 Gear and equipment for rigging and materials handling

The SRFP should include procedures for testing and inspecting ropes, chains, slings, hooks, chain-falls and hoisting and hauling equipment. It should further include a description of operations using cranes, machines, mobile equipment and aerial and man-lift systems and a list of qualifications required for the operators.

3.3.4.7 Housekeeping and illumination

The SRFP should include procedures for work areas, such as aisles, passageways and temporary deck openings.

3.3.4.8 Maintenance and decontamination of tools and equipment

---CHUNK---

SOURCE: MEPC.210(63).pdf
3.3.4.7 Housekeeping and illumination

The SRFP should include procedures for work areas, such as aisles, passageways and temporary deck openings.

3.3.4.8 Maintenance and decontamination of tools and equipment

The SRFP should include procedures for inspection and maintenance of equipment, regulatory requirements for third-party ins pections and decontamination procedures. These activities and the result of the inspections should be recorded.

The Ship Recycling Facility should ensure that the quantity and the deployment of tools and equipment are suitable for the corresponding recycling activities, especially when a number of ships are to be recycled at the same time.

3.3.4.9 Health and sanitation

The SRFP should include a description of washing facilities, showers, eating and recreation areas, toilet facilities and changing rooms. It is recommended that appropriate changing rooms and sanitary and washing facilities should be provided by the Ship Recycling Facility to control exposure and avoid the spread of Hazardous Materials. Sanitary and washing facilities should be conveniently accessible and si tuated so that they are not at risk of

---CHUNK---

SOURCE: MEPC.210(63).pdf
to control exposure and avoid the spread of Hazardous Materials. Sanitary and washing facilities should be conveniently accessible and si tuated so that they are not at risk of

contamination from the workplace. Separat e and appropriate changing rooms and sanitary and washing facilities should be provided for exclusive use by workers handling asbestos. It is also recommended that the Ship Recy cling Facility should designate separate and uncontaminated areas for workers to use for eating, drinking and other breaks.
RESOLUTION MEPC.210(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 21

I:\MEPC\63\23.doc
3.3.4.10 Personal protective equipment

The SRFP should include information on procedures and equipment used for the protection of employees from various risks associated with ship recycling.

Respiratory protection and hearing conservation programmes should be developed for all employees who could be exposed to excessive levels. The SRFP should describe how the programmes are in compliance with national regulations. In the absence of domestic law,

---CHUNK---

SOURCE: MEPC.210(63).pdf
employees who could be exposed to excessive levels. The SRFP should describe how the programmes are in compliance with national regulations. In the absence of domestic law, the Ship Recycling Facility should utilize best industry practices to provide effective respiratory protection and hearing conservation programmes.

3.3.4.11 Worker exposure and medical monitoring

The SRFP should include procedures to be used for monitoring exposure and for medical surveillance.

3.3.5 Emergency preparedness and response plan (EPRP)

Regulations 18.5 and 21 of the Convention specify that Ship Recycling Facilities shall establish and maintain an emergency preparedness and response plan (EPRP). While the EPRP could be incorporated into the SRFP, it is highly recommended that the EPRP should be a separate, self-contained document. By having it as a self-contained document, the information contained within is more readily available and easily accessible, and the Ship Recycling Facility may want to distribute copies to several locations at the site. It is also helpful to have a summary page at the front of the document for quick access,

---CHUNK---

SOURCE: MEPC.210(63).pdf
Recycling Facility may want to distribute copies to several locations at the site. It is also helpful to have a summary page at the front of the document for quick access, showing 24-hour contact information (including telephone numbers) for the appropriate contact personnel (such as management personnel and emergency response personnel).

The SRFP should identify the locations where the EPRP will be readily available, and should contain a brief summary of the EPRP, so that the appropriate entities (such as those that are authorizing facilities) or other relevant stak eholders can easily confirm that it exists.

The EPRP should take into consideration a wide variety of potential scenarios, including, but not limited to, human injuries, environmental accidents, extreme acts of nature and the activities of the surrounding community (such as an emergency at a nearby chemical processing plant).

The EPRP should, at a minimum, include the Facility's response to:

fire or explosion or ingress of water on the ship being recycled or awaiting recycling, within the perimeter of the Facility, or in an adjacent facility;

accidents to workers within the Facility;

---CHUNK---

SOURCE: MEPC.210(63).pdf
fire or explosion or ingress of water on the ship being recycled or awaiting recycling, within the perimeter of the Facility, or in an adjacent facility;

accidents to workers within the Facility;

spillages of Hazardous Materials; and

probable acts of nature in the area concerned, such as earthquakes or flooding.