3.4.1 Environmental monitoring

The SRFP should describe the environmental monitoring programme aimed at preventing

---CHUNK---

SOURCE: MEPC.210(63).pdf
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 24

I:\MEPC\63\23.doc
3.4.1 Environmental monitoring

The SRFP should describe the environmental monitoring programme aimed at preventing possible negative impacts to the environment during ship recycling.

Possible negative impacts during ship recycling may be divided into four main categories:

releases of Hazardous Materials to ground and sediments;
releases of Hazardous Materials to water;
emissions of Hazardous Materials to air; and
noise/vibrations.

The monitoring programme, if included in the SRFP, should be Facility-specific, taking into account the Facility's characteristics, such as the use of dry dock, jetty/piers and/or recycling plots on land-sea interface, and should identify chemical, biological and physical changes in the environment surrounding the Ship Recycling Facility.

The monitoring programme, if included in the SRFP, should utilize well-established standards for the sampling and analysis of relevant environmental parameters.

3.4.2 Management of Hazardous Materials

---CHUNK---

SOURCE: MEPC.210(63).pdf
The monitoring programme, if included in the SRFP, should utilize well-established standards for the sampling and analysis of relevant environmental parameters.

3.4.2 Management of Hazardous Materials

Prior to recycling, the IHM shall, in addition to the properly maintained and updated Part I, incorporate Part II for operationally generated wastes and Part III for stores (regulation 5.4).

Ships destined to be recycled shall conduct operations in the period prior to entering the Ship Recycling Facility in a manner that minimizes the amount of cargo residues, fuel oil and wastes remaining on board (regulation 8.2).

The following Hazardous Materials, at the very least, should be addressed in the SRFP:

(a) Hazardous materials contained in the ship's structure and equipment
(IHM, Part I):

Asbestos
Polychlorinated biphenyls (PCBs)
Ozone-depleting substances (ODSs)
Anti-fouling compounds and systems
Cadmium and cadmium compounds
Hexavalent chromium and hexavalent chromium compounds
Lead and lead compounds
Mercury and mercury compounds
Polybrominated biphenyls (PBBs)
Polybrominated diphenyl ethers (PBDEs)
Polychlorinated naphthalenes (PCNs)

---CHUNK---

SOURCE: MEPC.210(63).pdf
Hexavalent chromium and hexavalent chromium compounds
Lead and lead compounds
Mercury and mercury compounds
Polybrominated biphenyls (PBBs)
Polybrominated diphenyl ethers (PBDEs)
Polychlorinated naphthalenes (PCNs)
Radioactive substances
Certain short-chain chlorinated paraffins

RESOLUTION MEPC.210(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 25

I:\MEPC\63\23.doc
(b) Operationally generated wastes (IHM, Part II):

Waste oil (sludge)
Bilge and/or waste water generated by the after-treatment systems fitted on machineries
Oily liquid cargo residues
Ballast water
Raw sewage
Treated sewage
Non-oily liquid cargo residues
Dry cargo residues
Medical/infectious waste
Incinerator ash
Garbage
Fuel tank residues
Oily solid cargo tank residues
Oily or chemical contaminated rags

Dry tank residues
Cargo residues

(c) Stores including regular consumable goods (IHM, Part III). A list of these is shown in appendix 6 to these guidelines.

Regular consumable goods potentially containing Hazardous Materials comprise goods

---CHUNK---

SOURCE: MEPC.210(63).pdf
Dry tank residues
Cargo residues

(c) Stores including regular consumable goods (IHM, Part III). A list of these is shown in appendix 6 to these guidelines.

Regular consumable goods potentially containing Hazardous Materials comprise goods which are not integral to a ship and are unlikely to be dismantled or treated at a Ship Recycling Facility.

The Ship Recycling Facility's approach for properly managing each of the Hazardous Materials found on board a ship should be described in its SRFP.

The SRFP should describe the Ship Recycling Facility's process, control procedures and abatement methodologies used for the removal, labelling, storage, segregation, transport, treatment and disposal of all such Hazardous Materials, which should be developed in accordance with national requirements, as applicable.

It is important to describe the sequence of removal of Hazardous Materials as part of the ship recycling activities.

It is recommended that the following aspects of proper management of Hazardous Materials should be clearly addressed for each of the potentially Hazardous Materials identified above:

---CHUNK---

SOURCE: MEPC.210(63).pdf
recycling activities.

It is recommended that the following aspects of proper management of Hazardous Materials should be clearly addressed for each of the potentially Hazardous Materials identified above:

identification, marking and labelling and potential on-board locations;
recycling approach;
removal, handling and remediation;
storage and labelling; and
treatment, transportation and disposal.

I:\MEPC\63\23.doc
The Facility's approach to the safe and environmentally sound removal and treatment of any non-hazardous wastes on board should be described in the SRFP. The SRFP should describe the Facility's processes, control procedures and capabilities for removing and treating all such non-hazardous wastes, taking into account applicable IMO guidance, including but not limited to the Comprehensive Manual on Port Reception Facilities.

3.4.2.1 Potentially containing Hazardous Materials

The prerequisite for classification as "potentially containing Hazardous Materials" (PCHM)

---CHUNK---

SOURCE: MEPC.210(63).pdf
including but not limited to the Comprehensive Manual on Port Reception Facilities.

3.4.2.1 Potentially containing Hazardous Materials

The prerequisite for classification as "potentially containing Hazardous Materials" (PCHM) is "a comprehensible justification such as the impossibility of conducting sampling without compromising the safety of the ship and its operational efficiency" (paragraph 4.2.3 of the 2011 Guidelines for the Development of the Inventory of Hazardous Materials , hereafter