water)

The Ship Recycling Facility should identify the location and volume of hazardous liquids remaining on board by actively utilizing the IHM. Identification, marking and labelling of the

---CHUNK---

SOURCE: MEPC.210(63).pdf
RESOLUTION MEPC.210(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 33

I:\MEPC\63\23.doc
tanks and other areas should be conducted by the Ship Recycling Facility before the liquids are removed.

The residual oil storage tank should be protected against leakage, overflow, fire and other potential accidents.

Hazardous liquids, residues and sediments in stores, tanks, machines, equipment and piping should be removed under safe and environmentally sound conditions.

Ballast water should be handled in accordance with relevant national requirements.

3.4.3.6 Heavy metals (lead, mercury, cadmium and hexavalent chromium)

As indicated in the Inventory Guidelines, heavy metals are found in batteries, galvanized materials, level switches, gyro compasses, thermometers, coatings, etc. Radioactive substances may be found in level indicators and smoke detectors.

Equipment and other instruments containing heavy metals should be removed carefully to ensure that they do not break and to avoid contamination of the environment. Reusable

---CHUNK---

SOURCE: MEPC.210(63).pdf
substances may be found in level indicators and smoke detectors.

Equipment and other instruments containing heavy metals should be removed carefully to ensure that they do not break and to avoid contamination of the environment. Reusable equipment and instruments should be stored properly. Broken equipment and instruments should be delivered to the appropriate companies for repair, recycling or disposal in accordance with national requirements.

Anodes fitted to the ship's hull as sacrificial metal should be removed in the course of block

cutting and should be managed properly.

3.4.3.7 Other Hazardous Materials

Other Hazardous Materials not listed above and which are not part of the ship's structure those materials listed in the IHM, Parts II and III should be removed under safe conditions.

To the maximum extent possible, these materials should be removed prior to cutting according to the provisions of national laws and regulations. After the materials have been removed from ships, safe and environmentally sound methods should be used for storing and processing

---CHUNK---

SOURCE: MEPC.210(63).pdf
to the provisions of national laws and regulations. After the materials have been removed from ships, safe and environmentally sound methods should be used for storing and processing them; for example, electric cable insulation containing chlorinated compounds should not be burned.

3.4.4 Prevention of adverse effects to the environment

3.4.4.1 Spill prevention, control and countermeasures

The purpose of developing and implementing a progr amme for spill prevention, control and countermeasures is to minimize the risk of spills and leaks that could adversely impact the environment. The SRFP should include a programme that defines the Ship Recycling Facility's procedures for spill prevention, response and countermeasures. The programme should define proactive approaches to spill prevention and procedures to be implemented in the event of spills.

RESOLUTION MEPC.210(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 34

I:\MEPC\63\23.doc
At a minimum, the programme should demonstrate that the Ship Recycling Facility has

---CHUNK---

SOURCE: MEPC.210(63).pdf
Adopted on 2 March 2012
2012 GUIDELINES FOR SAFE AND ENVIRONMENTALLY SOUND SHIP RECYCLINGMEPC 63/23
Annex 4, page 34

I:\MEPC\63\23.doc
At a minimum, the programme should demonstrate that the Ship Recycling Facility has adequate containment and spill clean-up equipment and procedures, by identifying the following:

containment and diversionary structures in place to prevent discharged Hazardous Materials from contaminating soil and water;

Facility drainage areas;
location of spill response equipment;
environmental protection measures to be implemented during transfer and offloading of fuels;
location of other oils and bilges;
fuel storage locations;
inspection and record-keeping procedures;
security measures;
personnel training programmes;
spill prevention and reporting procedures; and
the history of incidents at the Ship Recycling Facility.

As part of the procedures for spill prevention, response and countermeasures, the SRFP should identify the designated in-house and subcontracted personnel who will be responsible for managing the programme and for responding to spills or similar emergencies, as well as

---CHUNK---

SOURCE: MEPC.210(63).pdf
should identify the designated in-house and subcontracted personnel who will be responsible for managing the programme and for responding to spills or similar emergencies, as well as the local authorities (such as the fire department) that may have jurisdiction at the Ship Recycling Facility. This SRFP should include 24-hour contact information. The SRFP should include both a narrative and graphic description of the Facility layout, including the location of any water bodies or other routes of migration, the storage location of oil or other Hazardous Materials, procedures for fuel transfer from ship to shore, procedures to be implemented in the event of a spill and the types and locations of emergency-response equipment (such as absorbent materials, personal protective equipment and first-aid equipment).

By identifying the potential sources of spills or leaks, the Ship Recycling Facility can then identify proactive measures to be implemented in order to minimize the risk associated with Facility activities. It is helpful for the Ship Recycling Facility to review the potential sources

---CHUNK---

SOURCE: MEPC.210(63).pdf
identify proactive measures to be implemented in order to minimize the risk associated with Facility activities. It is helpful for the Ship Recycling Facility to review the potential sources for spills and leaks and to determine the types of failures associated with them in order to determine the most appropriate and effective prevention measures. For example, drums should not be left open unless being filled, should be within a secondary containment or beamed structure and should not be exposed to rainfall that could corrode them over time.

The programme for spill prevention, control and countermeasures can be used as a tool by the Ship Recycling Facility to communicate practices on preventing and responding to spills and leaks, as a resource during emergency response and as a repository for information on storage, inspection and testing. It is important to maintain records on maintenance, inspections and employee training. Periodic review of the programme for spill prevention, control and countermeasures is also an effective tool for determining which procedures are fulfilling their intended function and for identifying weaknesses in the programme.

---CHUNK---

SOURCE: MEPC.210(63).pdf

control and countermeasures is also an effective tool for determining which procedures are fulfilling their intended function and for identifying weaknesses in the programme.

3.4.4.2 Storm-water pollution prevention

Storm-water run-off from industrial facilities has the potential to adversely affect the environment. Improper storage and handling of Hazardous Materials and wastes could increase the risk of environmental degradation through contact with water. The SRFP should include a programme that defines measures to be implemented and maintained to minimize the potential for storm-water contamination at the Ship Recycling Facility.

A programme for the prevention of storm-water pollution should include the identification of all potential pollutant sources at the Ship Recycling Facility that could come into contact with storm water, with the nearby receiving wate rs and with storm water-conveyance systems. A site map should be developed that depicts such information.